

Volume

#

R0592

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1

R592

ORIGINAL
FIELD NOTES

OF THE

REMONUMENTATION OF CORNERS

IN

TOWNSHIP 2 NORTH, RANGE 19 EAST

TOWNSHIP 2 NORTH, RANGE 21 EAST

TOWNSHIP 2 NORTH, RANGE 23 EAST

TOWNSHIP 3 NORTH, RANGE 20 EAST

TOWNSHIP 3 NORTH, RANGE 21 EAST

TOWNSHIP 3 NORTH, RANGE 22 EAST

OF THE

SALT LAKE MERIDIAN, UTAH

Of the SALT LAKE

In the State of UTAH

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH
DEC 23 PM 1:56
BUREAU OF LAND MGMT.

EXECUTED BY

Ferrel D. Reynolds

Surveying Technician

Under special instructions dated February 15, 19 61, which provided for the surveys
included under Group Number 447, approved February 16, 1961,
and assignment instructions dated May 26, 19 69.

Survey commenced June 4, 19 69

Survey completed June 25, 19 69

INDEX DIAGRAM

Township _____, Range _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 2 N. R. 19 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 2 N. R. 21 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 2 N. R. 23 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 3 N. R. 20 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
		10	8	7	7
30	29	28	27	8	25
			9	8	
31	32	33	9	34	35
					36

Tp. 3 N. R. 21 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
			12	11	
31	32	33	34	35	36

Tp. 3 N. R. 22 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	14	14	36
		13	13	12	

Blank

Page

Remonumentation of Corners

CHAINS

The following field notes are those of the remonumentation of certain identified corners selected by the U. S. Forest Service as being located in or controlling the boundaries of Forest Service lands, situated in the Ashley National Forest. A Forester's Compass was used to determine the bearings of new corner accessories. The mean magnetic declination was found to be as follows:

T. 2 N., R. 19 E., Salt Lake Meridian,	15° 30' E.
T. 2 N., R. 21 E., " " "	15° 20' E.
T. 2 N., R. 23 E., " " "	15° 15' E.
T. 3 N., R. 20 E., " " "	15° 30' E.
T. 3 N., R. 21 E., " " "	15° 20' E.
T. 3 N., R. 22 E., " " "	15° 15' E.

The position of each corner was marked by the original monument or determined from corner accessories recorded in the survey records. The monumentation was requested by and accomplished in cooperation with the Forest Service.

Remonumentation of Corners in T. 2 N., R. 19 E.

Township 2 North, Range 19 East, Salt Lake Meridian, is located partially within the Ashley National Forest. This corner was established by Andrew Nelson in 1923.

At the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., marked with a limestone, 18x9x6 ins., firmly set and plainly mkd. with 4 notches on the W. and 2 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone, 3½ ft. base, 1½ ft. high, to W. Brass cap mkd.

T3N R19E

S34|S35
S3|S2

T2N R19E

1969

Deposit the original stone alongside the corner.

This cor. is located on N. slope of hill 35 lks. S. and 60 lks. W. of creek, 10 lks. wide, 1 ft. deep, that flows S. 70° E., in scattered cedar growth.

Remonumentation of Corners in T. 2 N., R. 21 E.

Remonumentation of Corners in T. 2 N. R. 21 E.

CHAINS

Township 2 North, Range 21 East, Salt Lake Meridian, is located within the Ashley National Forest. The following corners were established by S. P. and J. R. Stewart in 1906.

At the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., marked with a sandstone, 18x10x5 ins., firmly set and plainly mkd. with 4 notches on the W. and 2 on the E. edge.

From which,

A pinon pine, 8 ins. in diam., bears N. 24° E., 54 lks., mkd. T3N R21E S35 BT. (Record N. 24° E. 55 lks.)

A pinon pine, 6 ins. in diam., bears S. 25° 20' E., 29 lks. dist., mkd. T2N R21E S2 BT. (Same as record)

A cedar, 8 ins. in diam., bears S. 45° W., 29 lks. dist., mkd. T2N R21E S3 BT. (Record S. 49° 40' W. 29 lks.)

A pinon pine, 10 ins. in diam., bears N. 35° 12' W., 78 lks. dist., mkd. T3N R21E S34 BT. (Same as record)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 4 ins. in the ground and in a mound of stone 4 ft base to brass cap mkd.

T3N R21E

S34 | S35

S3 | S2

T2N R21E

1969

The original stone in mound alongside the corner.

This cor. is located on top of small spur projecting N. 70° W., 4 chs. dist., E. of draw that drains N. approx. 8 chs. dist. N. of trail road that bears E. and W. in pine and cedar growth.

At the cor. of secs. 2, 3, 10 and 11, marked with a sandstone, 20x13x6 ins., firmly set and plainly mkd. with 5 notches on S. and 2 on E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and raise a mound of stone, 3½ ft. base, 1½ ft. high, to the W. Brass cap mkd.

T2N R21E

S3 | S2

S10 | S11

1969

Remonumentation of Corners in T. 2 N., R. 21 E.

CHAINS

Deposit the original stone alongside the corner.

This cor. is located on gentle N. slope of hill approx. $5\frac{1}{2}$ chs. dist. E. of trail road that bears N. and S. in sagebrush clearing, No timber.

Remonumentation of Corners in T. 2 N., R. 23 E.

Township 2 North, Range 23 East, Salt Lake Meridian, is located partially within the Ashley National Forest. The following corners were established by S. P. and J. R. Stewart in 1906.

At the cor. of secs. 10, 11, 14 and 15, marked with a sandstone, 18x9x5 ins., firmly set and plainly mkd. with 4 notches on the S. and 2 on the E. edge.

From which,

A cedar, 7 ins. in diam., bears N. $64^{\circ} 30'$ E., 52 lks. dist., mkd. T2N R23E S11 BT. (Record N. $62^{\circ} 40'$ E., 64 lks.)

A cedar, 12 ins. in diam., bears S. 63° W., 28 lks. dist., mkd. T2N R23E S15 BT. (Record S. 63° W., 27 lks. dist.)

A cedar, 7 ins. in diam., bears N. 68° W., 25 lks. dist., mkd. T2N R23E S10 BT. (Record N. $62^{\circ} 40'$ W., 64 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone, 4 ft. base to brass cap mkd.

T2N R23E

S10	S11
S15	S14

1969

Deposit the original stone alongside the corner.

This cor. is located on steep broken S. slope of hill approx. 5 chs. dist. N. of power line that bears N. 83° W. and S. 83° E. about 10 chs. dist. N. of trail road that bears E. and W. in scattered cedar growth.

At the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, marked with a sandstone, 18x9x5 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

There is no remaining evidence of the original bearing trees.

Remonumentation of Corners in T. 2 N., R. 23 E.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

T2N R23E

$\frac{1}{4}$ — $\frac{S10}{S15}$

1969

From which I mark

A cedar, 8 ins. in diam., bears N. 25° W., 100 lks. dist., mkd. $1/4$ S10 BT.

A cedar, 7 ins. in diam., bears S. 37° E., 34 lks. dist., mkd. $1/4$ S15 BT.

Deposit the original stone alongside the corner.

This cor. is located on gentle E. slope of hill 80 lks. dist. W. of wash, 15 lks. wide, 3 ft. deep, that drains S. 45° E., 54 lks. dist. S. of 4 strand power line that bears S. 83° E. and N. 83° W. in scattered pinon and cedar growth.

At the cor. of secs. 9, 10, 15 and 16, marked with a sandstone, $16 \times 14 \times 9$ ins., firmly set and plainly mkd. with 4 notches on S. and 3 on E. edge witnessed by a mound of stones, W. of corner.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of corner. Brass cap mkd.

T2N R23E

$\frac{S9}{S16} | \frac{S10}{S15}$

1969

From which I mark

A cedar, 5 ins. in diam., bears S. $53^\circ 30'$ E., 36 lks. dist., mkd. T2N R23E S15 BT.

A power line pole, 12 ins. in diam., bears S. $26^\circ 30'$ W., 137 lks. dist., mkd. B0.

Deposit the original stone alongside the corner.

This cor. is located on steep E. slope of draw 60 lks. dist. E. of top of spur projecting S. 4 chs. dist. W. of draw that drains S. 104 lks. dist. N. of four strand power line that bears N. $72^\circ 30'$ E. and S. $72^\circ 30'$ W. in scattered cedar and pinon growth.

Remonumentation of Corners in T. 2 N., R. 23 E.

CHAINS

At the cor. of secs. 8, 9, 16 and 17, marked with a sandstone, 20x14x5 ins., firmly set and plainly mkd. with 4 notches on the S. and E. edges.

From which,

A pinon pine, 8 ins. in diam., bears N. 10° E., 46 lks. dist., mkd. T2N R23E S9 BT. (Same as record.)

A pinon pine, 10 ins. in diam., bears S. 44° 40' E., 21 lks. dist., mkd. T2N R23E S16 BT. (Same as record.)

A pinon pine, 7 ins. in diam., bears S. 38° W., 31 lks. dist., mkd. T2N R23E S17 BT. (Same as record.)

A pinon pine, 8 ins. in diam., bears N. 23° 40' W., 50 lks. dist., mkd. T2N R23E S8 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 8 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T2N R23E	
S8	S9
S17	S16
1969	

Deposit the original stone alongside the corner.

This cor. is located on SW. slope of hill among large boulders in scattered cedar and pinon growth.

At the cor. of secs. 4, 5, 8 and 9, marked with a sandstone, 18x9x5 ins., firmly set and plainly mkd. with 5 notches on S. and 4 on E. edge.

From which,

A cedar, 12 ins. in diam., bears N. 55° E., 118 lks. dist., mkd. T2N R23E S4 BT. (Record N. 38° 30' E., 84 lks. dist.)

A cedar, 8 ins. in diam., bears S. 73° E., 64 lks. dist., mkd. T2N R23E S9 BT. (Record S. 46° E., 29 lks. dist.)

A pinon pine, 10 ins. in diam., bears S. 48° W., 44 lks. dist., mkd. T2N R23E S8 BT. (Record S. 66° W., 82 lks. dist.)

A cedar, 6 ins. in diam., bears N. 55° W., 33 lks. dist., mkd. T2N R23E S5 BT. (Record N. 54° 30' W., 32 lks. dist.)

At the cor. point

Remonumentation of Corners in T. 2 N., R. 23 E.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 8 ins. in the ground and in a mound of stone, 4 ft. base to brass cap mkd.

T2N R23E

S5	S4
S8	S9

1969

Deposit the original stone alongside the corner.

This cor. is located on SW. slope of hill among large boulders, in scattered cedar and pinon growth.

At the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, marked with a sandstone, 18x8x5 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

From which,

A pinon pine, 7 ins. in diam., bears N. $36^{\circ} 30'$ E., 61 lks. dist., mkd. $\frac{1}{4}$ S4 BT. (Record N. $26^{\circ} 30'$ E., 60 lks. dist.)

A cedar, 10 ins. in diam., bears N. 59° W., 176 lks. dist., mkd. $\frac{1}{4}$ S5 BT. (Record N. 60° W. 187 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T2N R23E

S5	S4
----	----

1969

Deposit the original stone alongside the corner.

This cor. is located on gentle S. slope of hill approx. 10 chs. dist. S. of small wash that drains S. 30° E. in scattered pine and cedar growth.

At the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, marked with a sandstone, 18x9x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

From which,

A cedar, 10 ins. in diam., bears N. 83° E., 21 lks. dist., mkd. $\frac{1}{4}$ S6 BT. (Record N. 87° E., 21 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

Remonumentation of Corners in T. 2 N., R. 23 E.

CHAINS

T2N R23E

$$\frac{1}{2} \frac{S6}{S7}$$

1969

From which I mark

A pinon pine, 7 ins. in diam., bears S. 8° E., 45 lks. dist., mkd. 1/4 S7 BT.

Deposit the original stone alongside the corner.

This cor. is located on gentle S. slope of hill 4 chs. dist. E. of trail road that bears N. and S. in thick cedar and pinon growth.

Remonumentation of Corners in T. 3 N., R. 20 E.

Township 3 North, Range 20 East, Salt Lake Meridian, is located partially within the Ashley National Forest. The following corners were surveyed by A. D. Ferron in 1878, and partially resurveyed by S. P. and J. R. Stewart in 1906.

At the cor. of secs. 23, 24, 25 and 26, marked with a sandstone, 18x10x4 ins., firmly set and plainly mkd. with 2 notches on S. and 1 on E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone, 3½ ft. base, 1½ ft. high to the W. Brass cap mkd.

T3N R20E

$$\frac{S23}{S26} \frac{S24}{S25}$$

1969

Deposit the original stone alongside the corner.

This cor. is located on gentle N. slope of hill 360 lks. dist. S. of trail road that bears E. and W. in sagebrush growth, no timber.

At the 1/4 sec. cor. of secs. 23 and 26, marked with a sandstone, 15x10x4 ins., firmly set and plainly mkd. 1/4 on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, N. of cor. Brass cap mkd.

T3N R20E

$$\frac{1}{2} \frac{S23}{S26}$$

1969

Remonumentation of Corners in T. 3 N., R. 20 E.

CHAINS

Deposit the original stone alongside the corner.

This cor. is located on gentle N. slope of hill 3 chs. dist. S. of steep descent into canyon that drains E. approx. 12 chs. dist. N. of trail road that bears E. and W. in sagebrush growth, no timber.

At the cor. of secs. 22, 23, 26 and 27, marked with a sandstone, 18x7x5 ins., firmly set and plainly mkd. with 2 notches on the S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, W. of corner. Brass cap mkd.

T3N R20E

S22|S23
S27|S26

1969

Deposit the original stone alongside the corner.

This cor. is located on gentle N. slope of hill approx. 6 chs. dist. S. of wash, 50 lks. wide, 15 ft. deep that drains N. 70° E. about 5 chs. N. of trail road that bears E. and W. in sagebrush growth.

At the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, marked with a sandstone, 20x10x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

From which,

A cedar, 8 ins. in diam., bears N. $61^{\circ} 20'$ E., 12 lks. dist., mkd. $\frac{1}{4}$ S26 BT. (Same as record.)

A cedar, 6 ins. in diam., bears N. $61^{\circ} 50'$ W., 54 lks. dist., mkd. $\frac{1}{4}$ S27 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T3N R20E

$\frac{1}{2}$
S27|S26

1969

Deposit the original stone alongside the corner.

This cor. is located on steep N. slope of hill and at head of draw that drains N. in scattered cedar growth.

At the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, marked with a sandstone, 18x10x5 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

Remonumentation of Corners in T. 3 N., R. 20 E.

CHAINS

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 12 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

T3N R20E
 $\frac{1}{4}$ S27
 S34
 1969

Deposit the original stone alongside the corner.

This cor. is located on sandy S. slope 100 lks. dist. S. of sandstone ledges, 40 ft. high, that bears E. and W. approx. 10 chs. dist. N. of trail road in sagebrush flat, that bears E. and W, in lightly scattered cedar growth.

At the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, marked with a sandstone, 18x10x5 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

From which,

A cedar, 14 ins. in diam., bears N. 80° E. 67 lks. dist., mkd. $\frac{1}{4}$ S34 BT. (Record N. 8° E., 69 lks.)

A cedar, 12 ins. in diam., bears S. 14° W., 41 lks. dist., mkd. $\frac{1}{4}$ S33 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of corner. Brass cap mkd.

T3N R20E
 $\frac{1}{4}$
 S33|S34
 1969

Deposit the original stone alongside the corner.

This cor. is located 35 lks. dist. W. of small wash in canyon that drains N. in scattered cedar and pine growth.

At the cor. of secs. 27, 28, 33 and 34, marked with a sandstone, 20x12x7 ins., plainly mkd. with 3 notches on E. and 1 on S. edge. Set on N. slope of large boulder, 30x15 ft., 12 ft. above ground.

From which,

A cedar, 10 ins. in diam., bears N. $29^{\circ} 50'$ E., 143 lks. dist., mkd. T3N R20E S27 BT. (Same as record.)

Remonumentation of Corners in T. 3 N., R. 20 E.

CHAINS

A cedar, 8 ins. in diam., bears S. $32^{\circ} 50' E.$, 97 lks. dist., mkd. T3N R20E S34 BT. (Same as record.)

No remaining evidence of the other two bearing trees.

True point for the cor. cannot be perpetuated with $2\frac{1}{2}$ inch iron post.

Therefore at a point, S. 15 lks. dist.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor. for the witness cor. mkd.

T3N R20E

W | C

S28 | S27

S33 | S34

1969

Leave original stone in place at true point.

This cor. is located on gentle S. slope of hill 180 lks. dist. N. of wash in canyon, 20 lks. wide, 1 ft. deep, that drains W. 120 lks. dist. N. of trail road that bears E. and W. in lightly scattered cedar growth.

At the closing cor. of secs. 27 and 28, on the S. bdy. of sec. 22, marked with a sandstone, 18x9x6 ins., firmly set and plainly mkd. with 3 notches on the E. and 2 on the S. edge, CC on S. face.

From which,

The cor. of secs. 21 and 22, bears N. $89^{\circ} 50' W.$, 66 lks. dist. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, S. of cor. Brass cap mkd.

T3N R20E

S22

S28 | S27

C | C

1969

Deposit the original stone alongside the corner.

This cor. is located on rocky S. slope of ridge, 100 lks. dist. N. of top of ridge, bears N. $80^{\circ} E.$ and S. $80^{\circ} W.$ approx. 14 chs. dist. N. of trail road in flat that bears E. and W. in scattered scrub cedar growth.

At the cor. of secs. 21 and 22, on the N. bdy. of sec. 28, marked with a sandstone, 18x7x7 ins., firmly set and plainly mkd. with 3 notches on the E. and 2 on the S. edge.

Remonumentation of Corners in T. 3 N., R. 20 E.

CHAINS

From which,

The closing cor. of secs. 27 and 28, bears S. 89° 50' E., 66 lks. dist. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Brass cap mkd.

T3N R20E

S21|S22

S28

1969

Deposit the original stone alongside the corner.

This cor. is located on rocky south slope of ridge, 100 lks. dist. S. of top that bears N. 80° E., and S. 80° W. approx. 14 chs. dist. N. of trail road that bears E. and W. in scattered cedar growth.

Remonumentation of Corners in T. 3 N., R. 21 E.

Township 3 North, Range 21 East, Salt Lake Meridian, is located partially within the Ashley National Forest. The following cor. was established by S. P. and J. R. Stewart in 1906.

At the cor. of secs. 25, 26, 35 and 36, marked with a red sandstone, 14x9x5 ins., firmly set and plainly mkd. with 1 notch on the S. and E. edge.

From which,

A cedar, 10 ins. in diam., bears S. 14° 30' E., 132 lks. dist., mkd. T3N R21E S36 BT. (Same as record.)

A cedar, 12 ins. in diam., bears S. 63° W., 81 lks. dist., mkd. T3N R21E S35 BT. (Same as record.)

A cedar, 8 ins. in diam., bears N. 30° W., 103 lks. dist., mkd. T3N R21E S26 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone, 3½ ft. base, 1½ ft. high, W. of cor. Brass cap mkd.

T3N R21E

S26|S25

S35|S36

1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 3 N., R. 21 E.

CHAINS

This cor. is located on NE. slope of hill and at head of draw that drains N. 45° E. in scattered cedar growth.

At the cor. of secs. 26, 27, 34 and 35, marked with a sandstone, 18x9x5 ins., firmly set and plainly mkd. with 2 notches on E. and 1 on S. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of the cor. Brass cap mkd.

T3N R21E

S27 | S26
S34 | S35

1969

Deposit the original stone alongside the corner.

This cor. is located in nearly level sagebrush draw 150 lks. dist. N. of wash 15 ft. deep, 30 lks. wide, that drains N. 45° W. No timber.

Remonumentation of Corners in T. 3 N., R. 22 E.

Township 3 North, Range 22 East, Salt Lake Meridian, is located partially within the Ashley National Forest. The S. bdy. and subdivisional lines were surveyed by S. P. and J. R. Stewart in 1906.

At the $1/4$ sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., marked with a sandstone, 16x10x5 ins., firmly set and plainly mkd. $1/4$ on N. face.

From which,

A cedar, 8 ins. in diam., bears N. 28° E., 142 lks. dist., mkd. $1/4$ S34 BT. (Record N. 26° 20' E., 138 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Brass cap mkd.

T3N R22E

$\frac{1}{4}$ S34
S3

T2N R22E

1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 3 N., R. 22 E.

CHAINS

This cor. is located on gentle NW. slope of hill about 8 chs. dist. E. of small wash in draw that drains S. 45° W. approx. 5 chs. dist. N. of trail road that bears N. 60° W. and S. 60° E. in scattered cedar and pine growth.

At the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., marked with a sandstone, 14x10x6 ins., firmly set and plainly mkd. with 3 notches on the E. and W. edges.

From which,

A cedar, 12 ins. in diam., bears S. $57^{\circ} 30'$ E., 140 lks. dist., mkd. T2N R22E S3 BT. (Same as record.)

A cedar, 12 ins. in diam., bears S. $70^{\circ} 12'$ W., 348 lks. dist., mkd. T2N R22E S4 BT. (Record S. $70^{\circ} 12'$ W., 340 lks. dist.)

A cedar, 10 ins. in diam., bears N. $48^{\circ} 25'$ W., 315 lks. dist., mkd. T3N R22E S33 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Brass cap mkd.

T3N R22E
S33 | S34
S4 | S3
 T2N R22E
 1969

Deposit the original stone alongside the corner.

This cor. is located on nearly level land approx. 10 chs. dist. N. of Highway 260 that bears N. 60° W. and S. 60° E. in very scattered pinon and cedar growth.

At the $\frac{1}{4}$ sec. cor. of secs. 4 and 33 on the S. bdy. of the Tp., marked with a sandstone, 18x10x5 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

A pinon pine, 10 ins. in diam., bears N. $34^{\circ} 05'$ E., 145 lks. dist., mkd. $\frac{1}{4}$ S33 BT. (Record N. $34^{\circ} 05'$ E., 153 lks. dist.)

A pinon pine, 8 ins. in diam., bears S. $41^{\circ} 50'$ E., 107 lks. dist., mkd. $\frac{1}{4}$ S4 BT. (Record S. $41^{\circ} 0'$ E., 89 lks. dist.)

At the cor. point

Remonumentation of Corners in T. 3 N., R. 22 E.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 16 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T3N R22E

$\frac{1}{4}$ S33
S4

T2N R22E

1969

Deposit the original stone alongside the corner.

This cor. is located on top of small spur projecting E. approx. 6 chs. dist. W. of trail road that bears N. and S. in scattered pinon growth.

At the $1/4$ sec. cor. of secs. 34 and 35, marked with a sandstone, $20 \times 14 \times 6$ ins., firmly set and plainly mkd. $1/4$ on W. face.

From which,

A pinon pine, 7 ins. in diam., bears N. 75° E., 108 lks. dist., mkd. $1/4$ S35 BT. (Record N. 75° E., 110 lks. dist.)

A pinon pine, 10 ins. in diam., bears N. 51° W., 15 lks. dist., mkd. $1/4$ S34 BT. (Record N. 40° W., 14 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 4 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base to brass cap mkd.

T3N R22E

$\frac{1}{4}$
S34|S35

1969

Original stone in mound alongside the corner.

This cor. is located on gentle SE. slope of hill 150 lks. dist. N. of dirt road in canyon that bears N. 60° E. and S. 60° W. in scattered pinon and cedar growth.

At the $1/4$ sec. cor. of secs. 33 and 34, marked with a sandstone, $20 \times 9 \times 5$ ins., firmly set and plainly mkd. $1/4$ on W. face.

From which,

A cedar, 20 ins. in diam., bears N. $64^\circ 30'$ E., 21 lks. dist., mkd. $1/4$ S34 BT. (No record of bearing trees.)

Remonumentation of Corners in T. 3 N., R. 22 E.

CHAINS

A pinon pine, 8 ins. in diam., bears S. 31° W., 47 lks. dist., mkd. $1/4$ S33 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of corner. Brass cap mkd.

T3N R22E

$\frac{1}{4}$
S33|S34

1969

Deposit the original stone alongside the corner.

This cor. is located on steep broken S. face of hill 60 lks. dist. N. of small draw that drains S. 45° W. in thick pinon and cedar growth.

Blank Page

CERTIFICATE OF SURVEY

I, Ferrel D. Reynolds, HEREBY CERTIFY upon honor that,
 in pursuance of special instructions bearing date of the 15th day of February, 19 61,
 I have remonumented corners in T. 2 N., R. 19 E., T. 2 N., R. 21 E., T. 2 N.,
 R. 23 E., T. 3 N., R. 20 E., T. 3 N., R. 21 E., T. 3 N., R. 22 E.

of the Salt Lake Meridian, in the State of Utah, which
 are represented in the foregoing field notes as having been executed by me and under my direction;
 and that said survey has been made in strict conformity with said special instructions, the Manual
 of Instructions for the Survey of the Public Lands of the United States, and in specific manner
 described in the foregoing field notes.

February 12, 1970
 (Date)

Ferrel D. Reynolds
 (Signature)
 Surveying Technician

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date JUN 2 1970

BUREAU OF LAND MANAGEMENT,
 Washington, D. C.

The foregoing field notes of the remonumentation of corners in T. 2 N., R. 19 E.,
 T. 2 N., R. 21 E., T. 2 N., R. 23 E., T. 3 N., R. 20 E., T. 3 N., R. 21 E.,
 T. 3 N., R. 22 E., of the Salt Lake Meridian, Utah

executed by Ferrel D. Reynolds, Surveying Technician

having been critically examined and found correct, are hereby approved.

DEC 1 1971
 (Date)

Clark F. Lamm
 (Signature)
 Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Engineering)

Blank

Page

2

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF THE

REMONUMENTATION OF CORNERS

IN

TOWNSHIP 13 NORTH, RANGE 15 WEST

TOWNSHIP 13 NORTH, RANGE 16 WEST

TOWNSHIP 14 NORTH, RANGE 12 WEST

TOWNSHIP 14 NORTH, RANGE 14 WEST

TOWNSHIP 14 NORTH, RANGE 15 WEST

TOWNSHIP 14 NORTH, RANGE 16 WEST

RECEIVED
BUREAU OF LAND MANAGEMENT
DEC 28 PM 1:55
DEPT. OF INTERIOR
BUREAU OF LAND MGMT.

Of the SALT LAKE Meridian,

In the State of UTAH

EXECUTED BY

LaVern Griffin Surveying Technician

Under the supervision of Andrew Nelson, Cadastral Surveyor

(Now deceased)

Under special instructions dated February 15, 19 61, which provided for the surveys
included under Group Number 447, approved February 16, 1961,
and assignment instructions dated July 16, 19 65.

Survey commenced September 14, 19 65

Survey completed September 29, 19 65

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 13 N. R. 15 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	2 ¹⁶	15	14	13
19	20	21 ₁	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 13 N. R. 16 W. Mer. Salt Lake

6	5	5	4	3	2	1
7	4	8	9	10	11	12
18	3	17	16	15	14	13
19	3	20	21	22	2	24
30	29	28	27	26	25	
31	32	33	34	35	36	

Tp. 14 N. R. 12 W. Mer. Salt Lake

6	5	4	3	2	1 6
7	8	9	10	11	6 12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 14 N. R. 14 W. Mer Salt Lake

6	5	4	3	2	1
			7	6	
7	8	9	10	11	12
10		8			
18	17	16	15	14	13
9	9	7			
19	8	20	21	22	23
	8				24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 14 N. R. 15 W. Mer Salt Lake

6	5	4	3	2	1
					12
7	8	9	10	11	12
					12 11 10
18	17	16	15	14	13
16	15	13	13		
19	20	21	22	23	24
16	14	14	12		
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 14 N. R. 16 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
				22	
18	17	16	15	21	13
		22		21	19
19	20	21	22	20	18
	24	25		23	18
30	24	29	22	20	18
	23	24	27	26	19
31	23	32	33	34	35
	17	17	16		36

Blank

Page

Remonumentation of Corners in T. 13 N., R. 15 W.

CHAINS

The following field notes are those of the remonumentation of certain identified original corners selected by the U.S. Forest Service as being adjacent to or controlling the boundaries of Forest Service lands, situated in the Sawtooth National Forest. A Forester's Compass was used to determine the bearings of new corner accessories. The mean magnetic declinations were found to be as follows:

T. 13 N., R. 15 W.,	Salt Lake Meridian,	17° 10' E.
T. 13 N., R. 16 W.,	" " "	17° 10' E.
T. 14 N., R. 12 W.,	" " "	17° 05' E.
T. 14 N., R. 14 W.,	" " "	17° 05' E.
T. 14 N., R. 15 W.,	" " "	17° 10' E.
T. 14 N., R. 16 W.,	" " "	17° 10' E.

The position of each corner was marked by the original monument or determined from corner accessories recorded in the survey record. The monumentation was requested by and accomplished in cooperation with the Forest Service.

Remonumentation of Corners in Township 13 North, Range 15 West.

Township 13 North, Range 15 West, Salt Lake Meridian, is located in the Sawtooth National Forest; the subdivisions were surveyed by Andrew P. Hanson in 1893.

At the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, marked by a quartzite stone, 16x8x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and in a collar of stone, orig. stone buried on N. side of post; brass cap mkd.

T13N R15W

$\frac{1}{4}$ $\frac{S21}{S28}$

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 6 lks. W. of cor.

Corner is located on S. slope 15 lks. N. of fence bearing E. and W.

o

At the cor. of secs. 16, 17, 20 and 21, marked by a quartzite stone, 20x12x4 ins., firmly set and plainly mkd. 3 notches on S. and 4 notches on E. edges.

At the cor. point

Remonumentation of Corners in T. 13 N. R. 15 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and in a collar of stone, orig. stone buried on W. side of post; brass cap mkd.

T13N R15W

S17	S16
S20	S21

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 10 lks. W. of cor., and one 10 lks. S. of cor.

Corner is located on steep NW. slope of spur.

Remonumentation of Corners in
Township 13 North, Range 16 West

Township 13 North, Range 16 West, Salt Lake Meridian, is situated within the Sawtooth National Forest. The W. 2 miles of the N. bdy. were surveyed by Nephi P. Anderson in 1892. The subdivisions were surveyed by Nephi P. Anderson in 1903.

At the cor. of secs. 14, 15, 22 and 23, mkd. by a quartzite stone, 16x10x6 ins., firmly set and plainly mkd. 3 notches on S. and 2 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and in a collar of stone. Orig. stone buried on W. side of post; brass cap mkd.

T13N R16W.

S15	S14
S22	S23

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 10 lks. E. of corner.

Corner is located on steep W. slope in fence line bearing E. and W. 8.00 chs. W. is a road in bottom of draw bearing N. and S.

At the cor. of secs. 17, 18, 19 and 20, mkd. by a quartzite stone, 16x8x6 ins., firmly set and plainly mkd. 3 notches on S. and 5 notches on E. edges.

At the cor. point

Remonumentation of Corners in T. 13 N., R. 16 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T13N R16W

S18	S17
S19	S20

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 6 lks. N. of corner and one 6 lks. E. of corner.

Corner is located on N. slope in fence line bearing N. and S., 2.00 chs. E. is a dirt road which bears irregularly NW. and SE.

At the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, marked by a quartzite stone, 14x8x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T13N R16W

$\frac{1}{4}$	
S18	S17

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. S. of cor.

Corner is located on a S. slope in fence bearing N. and S. and about 30.00 chs. E. of Lynn Lake.

At the cor. of secs. 7, 8, 17 and 18, marked by a quartzite stone, 18x10x6 ins., firmly set and plainly mkd. 4 notches on S. and 5 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T13N R16W

S7	S8
S18	S17

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 5 lks. N. of corner.

Remonumentation of Corners in T. 13 N., R. 16 W.

CHAINS	<p>Corner is located on N. slope of spur in fence line bearing N. and S.</p>
	<p>At the $\frac{1}{2}$ sec. cor. of secs. 7 and 8, marked by a quartzite stone, 16x10x6 ins., firmly set and plainly mkd. $\frac{1}{2}$ on W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.</p> <p style="text-align: center;">T13N R16W $\frac{1}{2}$ S7 S8 1965</p> <p>No bearing trees available.</p> <p>Set a steel fence post, 6 ft. long, 2 ft. in the ground, 4 lks. S. of corner.</p> <p>Corner is located on gentle W. slope in fence cor., fences bearing N., S. and W., and in reseeded area.</p>
	<p>At the cor. of secs. 5, 6, 7 and 8, marked by a quartzite stone, 14x10x6 ins., firmly set and plainly mkd. 5 notches on the S. and E. edges.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.</p> <p style="text-align: center;">T13N R16W S6 S5 S7 S8 1965</p> <p>No bearing trees available.</p> <p>Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. S. of corner.</p> <p>Corner is located on steep NW. slope in fence line bearing N. and S., and about 8.00 chs. N. of Rock Canyon.</p>
	<p>At the closing cor. of secs. 5 and 6, on the N. bdy. of the Tp., marked by a quartzite stone, 14x10x4 ins., firmly set and plainly mkd. 1 notch on W., 5 notches on the E. edges and CC on the S. face.</p> <p>At the cor. point</p>

Remonumentation of Corners in T. 13 N., R. 16 W.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on N. side of post; brass cap mkd.

T14N R16W
S32
S6 | S5
C | C
T13N R16W
1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 10 lks. S. of corner, and one 5 lks. W. of corner.

At the closing cor. of secs. 4 and 5, on the N. bdy. of the Tp., marked by a quartzite stone, 16x12x6 ins., firmly set and plainly mkd. 2 notches on W. and 4 notches on E. edges, and CC on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on S. side of post; brass cap mkd.

T14N R16W
S33
S5 | S4
C | C
T13N R16W
1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 6 lks. E. of corner.

Corner is located on SW. slope and in a fence line bearing E. and W., and in a reseeded area.

Remonumentation of Corners in T. 14 N., R. 12 W.

Township 14 North, Range 12 West, Salt Lake Meridian, is situated within the Sawtooth National Forest. The subdivisions were surveyed by Edward W. Koeber in 1887. Secs. 1 thru 6 were resurveyed by Andrew P. Hanson in 1896.

At the ¼ sec. cor. of secs. 11 and 12, marked by a quartzite stone, 14x10x8 ins., firmly set and plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

Remonumentation of Corners in T. 14 N., R. 12 W.

CHAINS

T14N R12W

 $\frac{1}{2}$

S11|S12

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground;
4 lks. S. of corner.

Corner is located on gentle E. slope and in a fence line
bearing N. and S.

At the cor. of secs. 1, 2, 11 and 12, marked by a
quartzite stone, 18x16x10 ins., firmly set and plainly
mkd. 1 notch on E. and 5 notches on S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground; orig. stone buried on W. side of post;
brass cap mkd.

T14N R12W

$$\begin{array}{r|l} S2 & S1 \\ \hline S11 & S12 \end{array}$$

1965

No bearing trees available.

Corner is located on gentle N. slope and 2 lks. W. of
cor. of fences bearing N., S. and E.

Remonumentation of Corners in T. 14 N., R. 14 W.

Township 14 North, Range 14 West, Salt Lake Meridian, is
situated within the Sawtooth National Forest. The west
bdy. was surveyed by Andrew P. Hanson in 1893, and re-
surveyed by Nephi P. Anderson in 1902. The subdivisions
were surveyed by Andrew P. Hanson in 1893.

At the cor. of secs. 2, 3, 10 and 11, marked by a
quartzite stone, 22x10x6 ins., firmly set and plainly
mkd. 5 notches on S. and 2 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground and in a collar of stone; orig. stone
buried on W. side of post; brass cap mkd.

T14N R14W

$$\begin{array}{r|l} S3 & S2 \\ \hline S10 & S11 \end{array}$$

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground,
5 lks. W. of corner.

Remonumentation of Corners in T. 14 N., R. 14 W.

CHAINS

Corner is located on W. slope of spur and in a fence line bearing N. and S.

At the cor. of secs. 3, 4, 9 and 10, marked by a quartzite stone, 12x9x4 ins., firmly set and plainly mkd. 5 notches on S. and 3 notches on E. edges(record calls for a quartzite stone, 24x9x4 ins.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R14W

S4	S3
S9	S10

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside corner.

Corner is located 10 lks. S. of fence bearing E. and W. and 70 lks. W. of cor. of fences bearing S. and E.

At the cor. of secs. 16, 17, 20 and 21, marked by a slatestone, 18x12x4 ins., firmly set and plainly mkd. 3 notches on S. and 4 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R14W

S17	S16
S20	S21

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside corner.

Corner is located on a steep NW. slope in corner of fences bearing N. and E.

At the cor. of secs. 8, 9, 16 and 17, marked by a quartzite stone, 18x10x4 ins., firmly set and plainly mkd. 4 notches on the S. and E. edges.

Remonumentation of Corners in T. 14 N., R. 14 W.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R14W

S8	S9
S17	S16

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside corner.

Corner is located on a steep NE. slope in corner of fences bearing N., S., E. and W.

At the cor. of secs. 19, 20, 29 and 30, marked by a quartzite stone, 18x8x4 ins., firmly set and plainly mkd. 2 notches on S. and 5 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R14W

S19	S20
S30	S29

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 10 lks. W. of corner, and one 5 lks. N. of corner.

Corner is located on a steep E. slope and 10 lks. S. of cor. of fences bearing N. and W.

At the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, marked by a quartzite stone, 16x14x4 ins., firmly set and plainly mkd. $\frac{1}{2}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R14W

$\frac{1}{2}$
S19
S20

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 4 lks. S. of corner.

Remonumentation of Corners in T. 14 N., R. 14 W.

CHAINS

Corner is located on W. slope of sagebrush bench and 5 lks. N. of fence bearing E. and W.

At the cor. of secs. 17, 18, 19 and 20, marked by a quartzite stone, 20x12x6 ins., firmly set and plainly mkd. 3 notches on S. and 5 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R14W

S18	S17
S19	S20

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 4 lks. W. of corner.

Corner is located on SW. slope of spur, 30 lks. E. of fence bearing N. and S., and 50 lks. S. of road with cattle guard in road, bearing E. and W.

At the ½ sec. cor. of secs. 18 and 19, marked by a quartzite stone, 18x14x6 ins., firmly set and plainly mkd. ½ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on N. side of post; brass cap mkd.

T14N R14W

½	S18
	S19

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 6 lks. N. of corner.

Corner is located on W. slope covered with sagebrush, 5 lks. N. of fence bearing E. and W., and 40 lks. S. of dirt road bearing E. and W.

At the cor. of secs. 7 and 18 on the W. bdy. of the Tp., marked by a quartzite stone, 18x10x7 ins., firmly set and plainly mkd. 2 notches on N. and 4 notches on S. edges.

Remonumentation of Corners in T. 14 N., R. 14 W.

CHAINS

Original bearing trees have been destroyed.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on E. side of post; brass cap mkd.

T14N	
R15W	R14W
	S7
S12	
	S18
1965	

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. S. of corner.

Corner is located on S. slope about 2.00 chs. W. of dirt road bearing N. and S.

Remonumentation of Corners in T. 14 N., R. 15 W.

Township 14 North, Range 15 West, Salt Lake Meridian, is situated within the Sawtooth National Forest. The east boundary was surveyed by Andrew P. Hanson in 1893, and resurveyed by Nephi P. Anderson in 1902. A portion of the subdivisional lines were surveyed by Nephi P. Anderson in 1892, the remainder were surveyed and a portion were resurveyed by Nephi P. Anderson in 1902.

At the closing cor. of secs. 12 and 13, on the E. bdy. of the Tp., marked by a quartzite stone, 17x8x8 ins., firmly set and plainly mkd. 2 notches on N. and 4 notches on S. edges, and CC on W. face.

From which,

The remains of old juniper bearing tree, bears N. $40^{\circ} 45'$ W., 90 lks. dist. (same as record); only visible markings are S12 BT.

Other bearing tree has been destroyed.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N	
R15W	R14W
C S12	
	S18
C S13	
1965	

No suitable bearing trees available.

Remonumentation of Corners in T. 14 N., R. 15 W.

CHAINS

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 2 lks. W. of corner, and one 2 lks. E. of corner.

Corner is located on W. slope at cor. of fences bearing S. and W., 1.50 chs. W. of dirt road bearing N. and S., 12.48 chs. S. of the cor. of secs. 7 and 18, T. 14 N., R. 14 W.

At the $\frac{1}{2}$ sec. cor. of secs. 12 and 13, marked by a quartzite stone, 20x12x4 ins., firmly set and plainly mkd. $\frac{1}{2}$ on N. face.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on N. side of post; brass cap mkd.

T14N R15W

$\frac{1}{2}$ $\frac{S12}{S13}$
1965

From which,

A juniper, 6 ins. diam., bears S. 55° E., 25 lks. dist., mkd. $\frac{1}{2}$ S13 BT.

A juniper, 6 ins. diam., bears N. 60° W., 10 lks. dist., mkd. $\frac{1}{2}$ S12 BT.

Corner is located on W. slope at cor. of fences bearing E., W. and S. 45° E.

At the cor. of secs. 11, 12, 13 and 14, marked by a quartzite stone, 14x10x6 ins., firmly set and plainly mkd. 4 notches on S. and 1 notch on E. edges.

From which,

A juniper, 10 ins. diam., bears N. 2° E., 37 lks. dist., mkd. T14N R15W S12 BT (record N. $2^\circ 08'$ E., 36 lks. dist.).

A juniper stump, 8 ins. diam., bears S. 7° E., 14 lks. dist., mkd. T14N R15W S13 BT (record S $11^\circ 45'$ E., 16 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

Re monumentation of Corners in T. 14 N., R. 15 W.

CHAINS

T14N R15W

S11	S12
S14	S13

1965

No other bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 5 lks. N. of corner, and one 5 lks. E.

Corner is located on a steep S. slope 5 lks. S. of cor. of fences bearing N. and E.

At the $\frac{1}{2}$ sec. cor. of secs. 1 and 2, marked by a quartzite stone, 18x16x6 ins., firmly set and plainly mkd. $\frac{1}{2}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R15W

 $\frac{1}{4}$

S2	S1
----	----

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 5 lks. N. of corner.

Corner is located on top of a small spur which slopes N., 20 lks. E. of fence bearing N. and S.

At the cor. of secs. 21, 22, 27 and 28, marked by a quartzite stone, 20x14x4 ins., firmly set and plainly mkd. 2 notches on S. and 3 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R15W

S21	S22
S28	S27

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. E. of corner, and one 3 lks. N. of corner.

Corner is located on top of spur which slopes NW., 3 lks W. of cor. of fences bearing N. and E. about 8.00 chs. E. of Johnson Creek which drains N. and a dirt road runs along the E. side of creek.

Remonumentation of Corners in T. 14 N., R. 15 W.

CHAINS

At the cor. of secs. 15, 16, 21 and 22, marked by a quartzite stone, 14x10x8 ins., firmly set and plainly mkd. 3 notches on the S. and E. edges.

At the cor. point .

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R15W

S16 | S15
S21 | S22

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 4 lks. W. of corner, and one 4 lks. S. of corner.

Corner is located on gentle N. slope at cor. of fences bearing N., S. and W., about 2 chs. E. of Johnson Creek which drains N., about 8.00 chs. W. of dirt road bearing N. and S., and about 8.00 chs. E. of steep ascent.

At the $\frac{1}{2}$ sec. cor. of secs. 16 and 21, marked by a quartzite stone, 18x12x6 ins., firmly set and plainly mkd. $\frac{1}{2}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R15W

$\frac{1}{2}$ — S16
 S21

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. W. of corner.

Corner is located on SW. slope of small spur and in a fence line bearing E. and W.

At the closing cor. of secs. 28 and 29, marked by a quartzite stone, 15x10x5 ins., firmly set and plainly mkd. 4 notches on E. and 2 notches on W. edges, and CC on the S. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on S. side of post; brass cap mkd.

Remonumentation of Corners in T. 14 N., R. 15 W.

CHAINS	<div><div>S21 S29 S28 C C T14N R15W 1965</div><p>No bearing trees available.</p><p>Corner is located on W. slope, 1.72 chs. easting from cor. of secs. 20 and 21.</p></div>
	<p>At the cor. of secs. 20 and 21, monumented with a quartzite stone, 12x8x6 ins., firmly set in the ground, and plainly mkd. 2 notches on S. and 3 on E. edges.</p> <p>Original bearing trees have been destroyed.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.</p> <div><div>T14N R15W S20 S21 S29 1965</div><p>Cor. is located on W. slope at cor. of fences bearing E., N. and W.</p><p>Trees have been cleared for reseeding.</p></div>
	<p>At the S. ½ sec. cor. of sec. 20, monumented with a quartzite stone, 16x12x8 ins., firmly set and plainly mkd. ½ on N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on N. side of post; brass cap mkd.</p> <div><div>T14N R15W ½ S20 1965</div><p>No bearing trees available.</p><p>Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. W. of cor.</p><p>Cor. is located on spur, slopes N. and in fence line bearing E. and W. and about 10.00 chs. W. of draw draining N.</p></div>
	<p>At the closing cor. of secs. 29 and 30, monumented with a quartzite stone, 15x10x5 ins., firmly set and plainly mkd. 5 notches on E. and 1 on W. edges and CC on S. face</p> <p>At the cor. point</p>

Remonumentation of Corners in T. 14 N., R. 15 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. cor. buried on S. side of post; brass cap mkd.

S20
 S30 | S29
 C | C
 T14N R15W
 1965

No bearing trees available.

Cor. is located on sagebrush spur sloping N.

At the cor. of secs. 19 and 20, monumented with a quartzite stone, 21x6x5 ins., firmly set and plainly mkd. 5 notches on E. and 1 on S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on N. side of post; brass cap mkd.

T14N R15W
S19 | S20
 S30
 1965

No bearing trees available.

Cor. is located on gentle NW. slope 3.11 chs. (measured) dist. from the closing cor. of secs. 29 and 30 and 1.00 ch. W. of small draw draining N.

At the cor. of secs. 17, 18, 19 and 20, monumented with a quartzite stone, 14x10x8 ins., firmly set and plainly mkd. 5 notches on E. and 3 on S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground; orig. stone buried on W. side of post; brass cap mkd.

T14N R15W
S18 | S17
 S19 | S20
 1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 5 lks. S. of cor.

Cor. is located on gentle N. slope in fence line bearing N. and S. 1.50 chs.; thence E. and about 16.00 chs. N. of knoll and 10.00 chs. N. of draw, drains W. and in reseeded area.

Remonumentation of Corners in T. 14 N., R. 15 W.

CHAINS

At the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with a quartzite stone, 20x10x4 ins., firmly set and plainly mk $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground; orig. stone buried on N. side of post, and in a collar of stone, with brass cap mkd.

T14N R15W

$\frac{1}{4}$ $\frac{S18}{S19}$

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 4 lks. E. of cor.

Cor. is located on gentle N. slope 35 lks. N. of fence bearing E. and W., 1.50 chs. W. of draw, drains N. and in reseeded area.

Remonumentation of Corners in T. 14 N., R. 16 W.

Township 14 North, Range 16 West, Salt Lake Meridian, is located within the Sawtooth National Forest. The E. bdy., the W. 2 miles of the S. bdy., and a portion of the subdivisional lines were surveyed by Nephi P. Anderson in 1892. A portion of the subdivisional lines were resurveyed and the remainder surveyed by Nephi P. Anderson in 1902.

At the cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with a quartzite stone, 18x16x4 ins., firmly set and plainly mkd. 4 notches on E. and 2 on W. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground; orig. stone buried on N. side of post; brass cap mkd.

T14N R16W

S32|S33
S5

T13N R16W

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 4 lks. W. of cor.

Cor. located on SW. slope in fence line bearing E. and W. and 3.65 chs. dist. from the closing cor. of secs. 4 and 5, T. 13 N., R. 16 W. and about 8.00 chs. dist. W. from draw, drains NW.

Remonumentation of Corners, T. 14 N., R. 16 W.

CHAINS

At the $\frac{1}{2}$ sec. cor. of sec. 32 on the S. bdy. of the Tp., monumented with a quartzite stone, 24x18x4 ins., firmly set and plainly mkd. $\frac{1}{2}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground; orig. stone buried on N. side of post; brass cap mkd.

T14N R16W

$\frac{1}{2}$ S32

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 2 lks. W. of post.

Cor. located on gentle W. slope 20 lks. N. of fence line bearing E. and W. and about 15.00 chs. W. of dirt road, bears N. and S.

At the cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with a quartzite stone, 24x16x4 ins., firmly set and plainly mkd. 5 notches on E. and 1 on W. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground; orig. stone buried on N. side of post; brass cap mkd.

T14N R16W

S31 | S32

S6

T13N R16W

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 5 lks. E. of cor.

Cor. is located on N. slope and in cor. of fences bearing N., S. and E. and 4.80 chs. W. of closing cor. of secs. 5 and 6, T. 13 N., R. 16 W.

At the $\frac{1}{2}$ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with a quartzite stone, 16x16x6 ins., firmly set and plainly mkd. $\frac{1}{2}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground; orig. stone buried on W. side of post; brass cap mkd.

Remonumentation of Corners in T. 14 N., R. 16 W.

CHAINS

T14N
R16W R15W
 $\frac{1}{2}$
S25|S30
1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground,
4 lks. S. of cor.

Cor. is located on steep N. slope about 6.00 chs. S. of
draw, drains NW. and about 4.00 chs. E. of spur, slopes
N.

At the cor. of secs. 19, 24, 25 and 30, on the E. bdy.
of the Tp., monumented with a quartzite stone, 20x14x4
ins., firmly set and plainly mkd. 2 notches on S. and
4 on N. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a collar of stone, original stone
buried on W. side of post; brass cap mkd.

T14N
R16W R15W
S24|S19
S25|S30
1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground,
2 lks. N. and one 4 lks. W. of cor.

Cor. is located 2 lks. S. of fence cor.; fences bear N.
and W. and about 2.00 chs. E. of draw, drains N. and
4.00 chs. W. of spur, slopes N.

At the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on the E. bdy.
of the Tp., monumented with a quartzite stone, 18x16x8
ins., firmly set and plainly mkd. $\frac{1}{2}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a collar of stone; orig. stone
buried on W. of post; brass cap mkd.

T14N
R16W R15W
 $\frac{1}{2}$
S24|S19
1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground,
alongside cor.

Remorimentation of Corners in T. 14 N., R. 16 W.

CHAINS

Cor. is located on N. slope in fence line bears N. and S. and about 4.00 chs. E. of dirt road, bears N. and S. and 2.00 chs. W. of wash, drains N.

At the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a quartzite stone, 24x10x4 ins., firmly set and plainly mkd. 3 notches on S. and N. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N
R16W R15W
S13|S18
S24|S19

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 5 lks. S. and one 5 lks. E. of cor.

Cor. is located on gentle N. slope in fence line, bears N. and S., and about 12.00 chs. W. of dirt road, bears NE. and SW.

At the ¼ sec. cpr. of secs. 25 and 26, monumented with a quartzite stone, 16x10x4 ins., firmly set and plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. of post; brass cap mkd.

T14N R16W
¼
S26|S25
1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside cor.

Cor. is located on steep N. slope in fence line, bears E. and W. and about 4.00 chs. W. of draw, drains N.

At the cor. of secs. 23, 24, 25 and 26, monumented with a quartzite stone, 18x16x4 ins., firmly set and plainly mkd. 2 notches on S. and 1 on E. edges.

Remonumentation of Corners in T. 14 N., R. 16 W.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

S23	S24
S26	S25

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 2 lks. W. of cor.

Cor. is located on gentle N. slope at cor. of new fence bears N. and S. and old fence line bears W. and is in mouth of Little Pole Creek.

At the cor. of secs. 22, 23, 26 and 27, monumented with a quartzite stone, 22x8x6 ins., firmly set and plainly mkd. 2 notches on S. and 2 on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

S22	S23
S27	S26

1965

No suitable bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. N. and 1.03 chs. E. of cor.

Cor. is located on steep E. slope of spur and 1.00 ch. N. of road bears E. and W., and about 4.00 chs. W. of fence, bears NW. and SE.

At the $\frac{1}{2}$ sec. cor. of secs. 22 and 23, monumented with a quartzite stone, 24x16x4 ins., firmly set and plainly mkd. $\frac{1}{2}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

S22	S23
-----	-----

1965

Remonumentation of Corners in T. 14 N., R. 16 W.

CHAINS

No suitable bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside cor.

Cor. is located on spur, slopes N. and in cor. of fences bearing N. and E. and 15 lks. E. of new fence bears N. and S. and about 3.00 chs. E. of draw, drains N.

At the cor. of secs. 14, 15, 22 and 23, monumented with a quartzite stone, 14x11x10 ins., firmly set and plainly mkd. 3 notches on S. and 2 on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

S15|S14
S22|S23

1965

No suitable bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. S. of cor.

Cor. is located on NE. slope 14 lks. E. of fence bears N. and S. and about 7.00 chs. E. of dirt road, bears N. and S.

At the ¼ sec. cor. of secs. 14 and 15, monumented with a quartzite stone, 24x18x8 ins., firmly set and plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14S R16W

¼
S15|S14

1965

No suitable bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 4 lks. N. of cor.

Cor. is located on gentle N. slope 10 lks. E. of fence, bears N. and S. and 5 lks. W. of small wash, drains N. and 6.00 chs. E. of dirt road, bears N. and S.

Remonumentation of Corners in T. 14 N., R. 16 W.

CHAINS

At the corner of secs. 10, 11, 14 and 15, monumented with a quartzite stone, 18x16x10 ins., firmly set and plainly mkd. 4 notches on S. and 2 on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14S R16W

S10	S11
S15	S14

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. S. of cor. and one 3 lks. W. of cor.

Cor. is located on gentle N. slope and in cor. of fence, bears S. and W. and 30 lks. W. of wash, drains N.

At the ¼ sec. cor. of secs. 28 and 29, monumented with a quartzite stone, 16x12x4 ins., firmly set and plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

S29	S28
-----	-----

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 2 lks. S. of cor.

Cor. is located on NW. slope, 2 lks. N. of wire fence, bears E. and W. and about 9.00 chs. S. of draw, drains W. and 4.00 chs. N. of top of spur, slopes W.

At the cor. of secs. 16, 17, 20 and 21, monumented with a quartzite stone, 18x10x8 ins., firmly set and plainly mkd. 3 notches on S. and 4 on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried along W. side of post; brass cap mkd.

T14N R16W

S17	S16
S20	S21

1965

Remonumentation of Corners in T. 14 S., R. 16 W.

CHAINS

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside iron post.

Cor. is located on NE. slope in fence line, bears N. and S. and about 8.00 chs. S. of draw, drains NW. and 4.00 chs. N. of spur, slopes NW.

At the $\frac{1}{2}$ sec. cor. of secs. 31 and 32, monumented with a quartzite stone, 24x8x6 ins., firmly set and plainly mkd. $\frac{1}{2}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

$\frac{1}{2}$
S31 | S32

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 2 lks. S. of cor.

Cor. is located on gentle NW. slope 3 lks. N. of fences bears N., S. and W.

At the cor. of secs. 29, 30, 31 and 32, monumented with a quartzite stone, 18x12x6 ins., firmly set and plainly mkd. 1 notch on S. and 5 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

S30 | S29
S31 | S32

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 2 lks. S. of cor.

Cor. is located on S. slope of spur, slopes W. and in cor. fences bearing N., S. and W. and about 2.00 chs. N. of draw, drains W. and 3.00 chs. S. of dirt road, bears S., E. and N.

Remonumentation of Corners in T. 14 N., R. 16 E.

CHAINS

At the $\frac{1}{2}$ sec. cor. of secs. 29 and 32, monumented with a quartzite stone, 24x14x10 ins., firmly set and plainly mkd. $\frac{1}{2}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on N. side of post; brass cap mkd.

T14N R16W

$\frac{1}{2}$ S29
S32

1965

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. S. of cor.

Cor. is located on gentle SW. slope in reseeded area and about 3.00 chs. E. of draw, drains NW. and about 12.00 chs. W. of dirt road, bears N. and S.

At the $\frac{1}{2}$ sec. cor. of secs. 29 and 30, monumented with a quartzite stone, 32x16x6 ins., firmly set and plainly mkd. $\frac{1}{2}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

$\frac{1}{2}$
S30 | S29

1965

No suitable bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 3 lks. S. of cor.

Cor. is located on S. slope in fence line bears N. and S. and about 3.00 chs. N. of small draw, drains W. and about 12.00 chs. S. of spur, slopes S.

At the cor. of secs. 19, 20, 29 and 30, monumented with a quartzite stone, 22x18x4 ins., firmly set and plainly mkd. 2 notches on S. and 5 on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

S19 | S20
S30 | S29

1965

Remonumentation of Corners in T. 14 N., R. 16 W.

CHAINS

No bearing trees available.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, 5 lks. S. and one 5 lks. W. of cor.

Cor. is located on steep S. slope at cor. of fences, bears S. and E. and about 9.00 chs. N. of road to Lynn Spring, bears E. and W.

At the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with a quartzite stone, 17x13x4 ins., firmly set and plainly mkd. $\frac{1}{4}$ on S. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone; orig. stone buried on W. side of post; brass cap mkd.

T14N R16W

$\frac{1}{4}$ $\frac{S20}{S29}$

1965

From which,

A juniper, 20 ins. diam., bears S. $38^{\circ} 30'$ E., 32 lks. dist., dim scribe mks. visible (No record of this tree found.).

Set a steel fence post, 5 lks. W. of cor.

Cor. located on SW. slope of spur in fence line, bears E. and W., 30 lks. S. of dozed road, bears E. and W. and 3.00 chs. N. of draw, drains NW.

CHAINS

Blank

Page

FIELD ASSISTANTS

[illegible]

CERTIFICATE OF SURVEY

(I) ~~(We)~~, LaVern Griffin, under the supervision of Andrew Nelson. (Now deceased), **HEREBY**
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day
 of February, 19 61, (I) ~~(We)~~ have remonumented corners in Tps. 13 N.,
 Rs. 15 and 16 W., and Tp. 14 N., Rs. 12, 14, 15 and 16 W.

of the Salt Lake Meridian, in the State of Utah, which
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

April 24, 1970
 (Date)

LaVern Griffin
 (Cadastral Surveyor)

Surveying Technician

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date JUN 2 1970

BUREAU OF LAND MANAGEMENT
 Washington, D.C.

The foregoing field notes of the remonumentation of corners in Tp. 13 N., Rs.
 15 and 16 W., and Tp. 14 N., Rs. 12, 14, 15 and 16 W., Salt Lake
 Meridian, Utah

executed by LaVern Griffin, Surveying Technician

having been critically examined and found correct, are hereby approved.

DEC 1 1971
 (Date)

Clark F. Lamm
 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey) GPO 549-020

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

63

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE

NORTH HALF MILE OF THE EAST BOUNDARY

OF

TOWNSHIP 2 SOUTH, RANGE 1 EAST

REPT. OF INTERIOR
BUREAU OF LAND MGMT.

74 JUL 25 PM 12:43

RECEIVED
STATE OFFICE

Of the SALT LAKE Meridian,

In the State of UTAH

EXECUTED BY

Glen B. Hatch Supervisory Cadastral Surveyor

Under special instructions dated May 24, 19 73, which provided for the surveys
included under Group Number 546, approved May 25, 1973,
and assignment instructions dated May 29, 19 73.

Survey commenced June 5, 19 73

Survey completed June 5, 19 73

INDEX DIAGRAM

Township 2 South , Range 1 East ,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township 2 South, Range 1 East

CHAINS

The following field notes are those of the dependent resurvey of the north half mile of the east boundary, Township 2 South, Range 1 East, Salt Lake Meridian, Utah.

The north one mile of the east boundary was surveyed by A. D. Ferron, Deputy Surveyor, in 1891. The northeast corner of the township was remonumented by Howard W. Miller, Cadastral Engineer, in 1926, in connection with surveys in Township 1 South, Range 2 East. The north half mile of the east boundary was dependently resurveyed by Fred R. Chappell and Dell Cazier, Cadastral Surveyors, in 1958.

The dependent resurvey was conducted in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated May 24, 1973.

The direction of the line of this resurvey was determined by reference to the true meridian established on line by hour angle observations on Polaris, and verified by angular ties from the cor. of Tps. 1 and 2 S., Rs. 1 and 2 E., as shown in the official record of 1927 survey of T. 1 S., R. 2 E., as follows:

Center dome on State Capitol Building, Salt Lake City, Utah, bears N. 41° 37' W.

Center of large chimney at smelter in Murray, Utah, bears S. 74° 26' W.

Distances to several points along line were determined by a Hewlett-Packard electronic measuring device, with intermediate distances to items of topography determined by chaining.

The geographic position of the $\frac{1}{4}$ section corner of sections 1 and 6, on the east boundary of the township is at Latitude 40° 40' 30" N., and Longitude 111° 46' 34" W., as scaled from U.S.G.S. quadrangle sheet "Sugar House", 1963, and revised 1969, 7 $\frac{1}{2}$ ' series.

The mean magnetic declination was found to be 16° 00' East.

Dependent Resurvey of the North Half Mile
of the East Boundary, Township 2 South,
Range 1 East, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A. D. Ferron, Deputy Surveyor, in 1891, and the Dependent Resurvey executed by Fred R. Chappell and Dell Cazier, Cadastral Surveyors, in 1958.

Beginning at the cor. of Tps. 1 and 2 S., Rs. 1 and 2 E., monumented with an iron post, 3 ins. diam., extending 8 ins. above the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the North Half Mile
of the East Boundary, Township 2 South,
Range 1 East, Salt Lake Meridian Utah

CHAINS

T1S
R1E R2E
S36 | S31
S1 | S6
T2S
1926

from which,

Center of large chimney at smelter in Murray, Utah
bears S. 74° 26' W.

Center dome of State Capitol in Salt Lake City,
Utah, bears N. 41° 37' W.

Thence,

S. 0° 14' W., bet. secs. 1 and 6.

Asc. along W. slope.

- 1.55 U.S. Forest Service boundary marker on a spur, sloping
W., desc. along SW. slope.
- 13.30 Draw, drains S. 75° W.
- 18.80 Road, 30 lks. wide, bears SE. and curves nearly W.
- 21.30 Small draw, near head, drains W.
- 23.20 Same road (now oiled), on curve, bears SE. and NE.
- 25.85 Same road, curves SW. and NE., on small spur sloping
W., small reservoir bears SE. about 4.00 chs., to
center, desc.
- 26.25 U.S. Forest Service boundary marker on a steel fence
post.
- 27.60 Dirt road, bears NW. and SE., curving to E. and N.
- 31.40 Small house bears W. 1.00 chs.; desc. SW. slope.
- 32.25 Neff's Creek, drains irregularly N. 20° W., asc. NE.
slope.
- 32.75 Small house, bears W., 10 lks.
- 35.37 NE. cor. of carport, bears E., 2 lks. dist., long
side bears N. 69° W.
- 38.01 N. wall and fence enclosing tennis court, bears W.
and E. 20½ lks. to cor., thence S., enter tennis court.
- 39.59 Extending bearing of trail road bearing NE. and SW.
(Road along line destroyed by construction of tennis
court).
- 39.80 Concrete wall and fence, bears W. and E. 20½ lks. dist.
to cor., thence N., leave tennis court.
- 40.29 The ¼ sec. cor. of secs. 1 and 6, reestablished and re-
monumented in 1972 from calls of the original field note
record, under the remonumentation program between the
U.S. Forest Service and BLM, (See following note),
as follows:

3

Dependent Resurvey of the North Half Mile
of the East Boundary, Township 2 South,
Range 1 East, Salt Lake Meridian, Utah

CHAINS

A track road, bearing NE. and SW. is 70 lks. N.

Foundation of Andrew Lundgreen's cabin (destroyed)
bears East 75 lks. dist.

Note:

The U. S. Forest Service reported that trespass action was being initiated against a private adjacent land owner, with said 1/4 sec. cor. being the basis for the action. Therefore, due to this new development the remonumentation was not submitted for approval because it was deemed advisable to retrace the north 1/2 mile between secs. 1 and 6, T. 2 S., Rs. 1 and 2 E., to confirm and verify the 1/4 sec. cor. point position as reestablished and remonumented in 1972. Prior to the preparation of the special instructions for this retracement the remonumented 1/4 sec. cor. was reported missing, this then required a resurvey of said north 1/2 mile and the special instructions are written as such in order to reestablish the 1/4 sec. cor. of secs 1 and 6. However, during the resurvey the cor. was found firmly set at record bearing and dist. from the cor. of Tps. 1 and 2 S., Rs. 1 and 2 E., in a new lawn, with the brass cap being flush with the surface due to a recent earth fill. A check on this corner point showed it to be in accordance with the calls of the 1958 resurvey field note record, described above. The bearing of this line is further verified by U.S. Forest Service markers established on line during the 1958 resurvey by the U.S. Forest Service.

The 1/4 sec. cor. point is monumented with an iron post, 30 ins. long, 2 1/2 ins. diam., with brass cap set flush with ground and mkd.

T2S
R1E R2E
1/4
S1|S2
1972
1973

from which

SE. cor. of concrete retaining wall and fence around tennis court bears N. 22° 30' E., 53.4 lks. dist.

SE. cor. of garage, bears S. 18° 33' W., 65.8 lks. dist.

NE. cor. of same garage, bears N. 82° 73' W., 21.2 lks. dist.

Most northerly SE. cor. of house, bears N. 66° 02' W., 77.3 lks. dist.

Land, rolling and mountainous.

Soil, rocky loam.

Timber, scattered pine, maple and oak.

Undergrowth, dense young oak brush and grass.

Dependent Resurvey of the North Half Mile
of the East Boundary, Township 2 South,
Range 1 East, Salt Lake Meridian, Utah

CHAINS

General Description

The land east of this line is rugged mountains covered with dense oakbrush, maple and scattered pine. The land west of this line is all private subdivision, with many valuable homes and other improvements. Soil is rocky loam, and the drainage is westerly.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

[illegible]

CERTIFICATE OF SURVEY

(I) ~~XXX~~ Glen B. Hatch


, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 24th day of May, 1973, (I) ~~XXX~~ have dependently resurveyed the north half mile of the east boundary, Township 2 South, Range 1 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~XXX~~ and under (my) ~~XXX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 7, 1973

(Date)



(Cadastral Surveyor)

Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date OCT 29 1973

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of the north half mile of the east boundary, Township 2 South, Range 1 East, Salt Lake Meridian, Utah

executed by Glen B. Hatch, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

JUL 2 1974

(Date)



(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~
~~is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey)

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

73

ORIGINAL

FIELD NOTES

OF THE

REMONUMENTATION OF CORNERS

IN

TOWNSHIP 24 SOUTH, RANGE 2 EAST

TOWNSHIP 24 SOUTH, RANGE 4 WEST

TOWNSHIP 24 SOUTH, RANGE 5 WEST

TOWNSHIP 25 SOUTH, RANGE 2 EAST

TOWNSHIP 25 SOUTH, RANGE 6 WEST

TOWNSHIP 26 SOUTH, RANGE 1 WEST

TOWNSHIP 26 SOUTH, RANGE 2 WEST

TOWNSHIP 26 SOUTH, RANGE 4½ WEST

TOWNSHIP 26 SOUTH, RANGE 5 WEST

TOWNSHIP 27 SOUTH, RANGE 1 WEST

TOWNSHIP 27 SOUTH, RANGE 2 WEST

TOWNSHIP 27 SOUTH, RANGE 3 WEST

TOWNSHIP 29 SOUTH, RANGE 3 WEST

TOWNSHIP 29 SOUTH, RANGE 4 WEST

Of the SALT LAKE

In the State of UTAH

EXECUTED BY

Ferrel D. Reynolds

Surveying Technician

Under special instructions dated February 15, 19 61, which provided for the surveys
included under Group Number 447, approved February 16, 1961,
and assignment instructions dated May 26, 19 69.

Survey commenced June 30, 19 69

Survey completed August 21, 19 69

RECEIVED
BUREAU OF LAND MANAGEMENT
OFFICE
Meriden
71 DEC 23 PM 1:55

INDEX DIAGRAM

Township

Range

Section

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTINDEX TO SECTION
CORNER MONUMENTSTp. 24 S. R. 2 E. Mer. Salt Lake

6	5	4	3	2	1
				2	
7	8	9	10	11	12
				2	
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 24 S. R. 4 W. Mer. Salt Lake

6	5	4	3	2	1
				4	
7	8	9	10	11	12
	4				
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 24 S. R. 5 W. Mer. Salt Lake

6	5	4	5	5	5
			3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 25 S. R. 2 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	8 7 25
31	32	33	9 34	7 6 35	7 36

Tp. 25 S. R. 6 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20 11	21	22	23	24
30	10 29	28	27	26	25
31	32	10 9 33	34	35	36

Tp. 26 S. R. 1 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14 11	13
19	20	21	22 12 12	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 27 S. R. 1 W. Mer. Salt Lake

6	5 24	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19 24	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 27 S. R. 2 W. Mer. Salt Lake

6	5	4	3	26 25 ¹	25 ¹
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 27 S. R. 3 W. Mer. Salt Lake

6	5	4	3	2	1	R. 2½ W.
7	8	9	10	11	12	27 5
18	17	16	15	14	13	27 8
19	20	21	22	23	24	27
30	29	28	27	26	25	17
31	32	33	34	35	36	26

Blank Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTINDEX TO SECTION
CORNER MONUMENTSTp. 29 S. R. 3 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19 28	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 29 S. R. 4 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	29 26	25
31	32	33	34	35	36

Tp. _____ R. _____ Mer. _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank

Page

Remonumentation of Corners

CHAINS

The following field notes are those of the remonumentation of certain identified corners selected by the U. S. Forest Service as being located in or controlling the boundaries of Forest Service lands, situated in the Fishlake National Forest. A Forester's Compass was used to determine the bearings of new corner accessories. The magnetic declination was found to be as follows:

T. 24 S., R. 2 E.,	Salt Lake Meridian,	15° 20' E.
T. 24 S., R. 4 W.,	" " "	15° 30' E.
T. 24 S., R. 5 W.,	" " "	15° 35' E.
T. 25 S., R. 2 E.,	" " "	15° 20' E.
T. 25 S., R. 6 W.,	" " "	15° 50' E.
T. 26 S., R. 1 W.,	" " "	15° 35' E.
T. 26 S., R. 2 W.,	" " "	15° 35' E.
T. 26 S., R. 4½ W.,	" " "	15° 40' E.
T. 26 S., R. 5 W.,	" " "	15° 40' E.
T. 27 S., R. 1 W.,	" " "	15° 25' E.
T. 27 S., R. 2 W.,	" " "	15° 25' E.
T. 27 S., R. 3 W.,	" " "	15° 30' E.
T. 29 S., R. 3 W.,	" " "	15° 20' E.
T. 29 S., R. 4 W.,	" " "	15° 20' E.

The position of each corner was marked by the original monument or determined from corner accessories recorded in the survey record. The monumentation was requested by and accomplished in cooperation with the Forest Service.

Remonumentation of Corners in T. 24 S., R. 2 E.

Township 24 South, Range 2 East, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by Andrew P. Hanson in 1895.

At the closing cor. of secs. 1 and 2, on the N. bdy. of the Tp., marked with a lava stone, 26x12x7 ins., firmly set and plainly mkd. with 5 notches on the W. and 1 on the E. edge, CC on the S. face.

From which,

An aspen, 10 ins. in diam., bears S. 43° 45' E., 12 lks. dist., mkd. dimly T24S R2E S1 BT, (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone, 4 ft. base to brass cap mkd.

T23S R2E

S35
S2 | S1
|
CC

T24S R2E

1969

Remonumentation of Corners in T. 24 S., R. 2 E.

CHAINS

From which I mark

A pine, 6 ins. in diam., bears S. $26^{\circ} 30'$ W.,
28 lks. dist., mkd. T24S R2E S2 BT.

Deposit the original stone alongside the corner.

The cor. is located on NW. slope of hill in thick aspen
and pine growth 3 chs. dist. E. of draw, that drains N.
 25° E.

At the cor. of secs. 2, 3, 10 and 11, marked with a
lava stone 24x11x6 ins., firmly set and plainly mkd.
with 5 notches on the S. and 2 on the E. edge.

From which,

A pine, 20 ins. in diam., bears N. $43^{\circ} 30'$ E.,
25 lks. dist., mkd. T24S R2E S2 BT. (record N.
 $36^{\circ} 50'$ E., 26 lks. dist.)

A pine, 30 ins. in diam., bears S. $2^{\circ} 12'$ W., 83
lks. dist., mkd. T24S R2E S10 BT. (same as record)

There is no remaining evidence of the other bearing
tree.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18
ins. in the ground and in a collar of stone; raise a
mound of stone, 4 ft. base, $1\frac{1}{2}$ ft. high to W. Brass
cap mkd.

T24S R2E

S3	S2
S10	S11

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle NW. slope of hill, in
scattered pine growth 78 lks. dist. E. of trail road
that bears N. 20° E. and S. 20° W.

At the $\frac{1}{2}$ sec. cor. of secs. 10 and 11, marked with a
trachyte stone 17x10x8 ins., firmly set and plainly mkd.
 $\frac{1}{2}$ on W. face.

From which,

A pine, 40 ins. in diam., bears S. $48^{\circ} 30'$ E.,
18 lks. dist., mkd. $\frac{1}{2}$ S11 BT, (same as record.)

A pine, 20 ins. in diam., bears S. $61^{\circ} 30'$ W., 89
lks. dist., mkd. $\frac{1}{2}$ S10 BT, (record S. $63^{\circ} 35'$ W.,
91 lks. dist.)

At the cor. point

Remonumentation of Corners in T. 24 S., R. 2 E.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 16 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T24S R2E

$\frac{1}{2}$
S10|S11

1969

Deposit the original stone alongside the corner.

The cor. is located on W. slope of ridge that bears N. and S., in scattered pine growth approx. 20 chs. dist. E. of trail road that bears N. and S.

Remonumentation of Corners in T. 24 S., R. 4 W.

Township 24 South, Range 4 West, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by A. P. Hanson in 1891.

At the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., marked with a trachyte stone 18x10x9 ins., firmly set and plainly mkd. with 4 notches on the N. and 2 on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 8 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T24S
R4W R3W
S24|S19
S25|S30

1969

Original stone in mound alongside the corner.

The cor. is located on S. slope in sagebrush growth at E. edge of canyon, 2 chs. wide, that drains S. 16° E.

At the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., marked with a trachyte stone 18x16x10 ins., firmly set and dimly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 8 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T24S
R4W R3W
 $\frac{1}{2}$
S25|S30

1969

Remonumentation of Corners in T. 24 S. R. 4 W.

CHAINS

Original stone in mound alongside the corner.

The cor. is located on rocky NE. slope of hill in sagebrush growth approx. 19 chs. dist. S. of dirt road that bears E. and W. in canyon.

At the cor. of secs. 2, 3, 10 and 11, marked with a trachyte stone 20x14x10 ins., firmly set and plainly mkd. with 5 notches on the S. and 2 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 6 ins. in the ground and in a mound of stone 5 ft. base to brass cap mkd.

T24S R4W

S3	S2
S10	S11

1969

The original stone in mound alongside the corner.

The cor. is located on W. slope of hill in oak and mahogany growth in 4 strand fence that bears N. and S. approx. 12 chs. dist. N. of trail road that bears E. and N. 45° W., on turn.

At the cor. of secs. 7, 8, 17 and 18, marked with a limestone 18x10x6 ins., firmly set and plainly mkd. with 5 notches on the E. and 4 on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T24S R4W

S7	S8
S18	S17

1969

Deposit the original stone alongside the corner.

The cor. is located on NW. slope of hill in thick oak brush 1 ch. N. of top of spur projecting W. 8 lks. dist. W. of 6 strand fence that bears N. and S. approx. 9 chs. dist. S. of Trail Springs Road that bears S. 45° W. and N. 10° E.

Remonumentation of Corners in T. 24 S., R. 5 W.

Township 24 South, Range 5 West, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by Henry Fitzhugh in 1882.

Remonumentation of Corners in T. 24 S., R. 5 W.

CHAINS

At the closing cor. of secs. 1 and 2 on the N. bdy. of the Tp., marked with a sandstone 20x14x6 ins., firmly set and plainly mkd. with 5 notches on the W. and 1 on the E., C C on S. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base $1\frac{1}{2}$ ft. high, to S. Brass cap mkd.

T23S R5W
 $\frac{S33}{S2 | S1}$
 CC
 T24S R5W
 1969

Deposit the original stone alongside the corner.

The cor. is located on NE. slope of rolling foothills, in oak and scattered cedar growth, 19 lks. dist. S. of four strand fence that bears E. and W.

At the closing cor. of secs. 2 and 3, on the N. bdy. of the Tp., marked with a sandstone 20x14x10 ins., firmly set and plainly mkd. with 4 notches on the W. and 2 on the E., C C on the S. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T23S R5W
 $\frac{S32}{S3 | S2}$
 CC
 T24S R5W
 1969

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope of rolling foothills, in scattered cedar growth at the cor. of four strand fence that bears E., W. and S.

At the closing cor. of secs. 3 and 4, on the N. bdy. of the Tp., marked with a sandstone 18x6x4 ins., firmly set and plainly mkd. with 3 notches on the E. and W. edges, CC on S. face.

At the cor. point

Remonumentation of Corners in T. 24 S., R. 5 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 16 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T23S R5W

S31

S4 | S3

CC

T24S R5W

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope of rolling foothills in scattered cedar growth 7 lks. dist. N. of four strand fence that bears E. and W.

Remonumentation of Corners in T. 25 S., R. 2 E.

Township 25 South, Range 2 East, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by T. C. Bailey and J. G. Burrill in 1876.

At the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp. (The Fifth Standard Parallel South), marked with a trachyte stone 16x10x8 ins., firmly set and plainly mkd. with 4 notches on the W. and 2 on the E., SC on N. face.

There is no remaining evidence of the original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T25S R2E

SC

S34 | S35

S2

T26S R2E

1969

From which I mark:

A pine, 7 ins. in diam., bears N. 41° E., 11 lks. dist., mkd. T25S R2E S35 BT.

A pine, 5 ins. in diam., bears N. 73° W., 9 lks. dist., mkd. T25S R2E S34 BT.

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 25 S., R. 2 E.

CHAINS

The cor. is located on NW. slope of hill in thick aspen and pine growth approx. 4 chs. dist. S. of horse trail from Lake Creek to Fremont River about 25 chs. dist. E. of base of hill that bears N. and S.

At the 1/4 sec. cor. of secs. 35 and 36, marked with a trachyte stone 18x9x7 ins., firmly set and plainly mkd. 1/4 on W. face.

From which,

An aspen, 7 ins. in diam. (dead), bears N. 3° 12' E. 21 lks. dist., with dim scribe mks. (same as record).

An aspen, 9 ins. in diam., (dead), bears S. 6° 40' E., 32 lks. dist., with dim scribe mks. (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 6 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T25S R2E

½
S35|S36

1969

From which I mark

A pine, 6 ins. in diam., bears N. 87° E., 59 lks. dist., mkd. 1/4 S36 BT.

A pine, 16 ins. in diam., bears S. 6° W., 54 lks. dist., mkd. 1/4 S35 BT.

The original stone in mound alongside the corner.

The cor. is located on top of flat ridge that bears N. 45° E. and S. 45° W., in thick pine and aspen growth.

At the cor. of secs. 25, 26, 35 and 36, marked with a trachyte stone 16x12x10 ins., firmly set and plainly mkd. with 1 notch on the S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3½ ft. base, 1½ ft. high, to W. Brass cap mkd.

T25S R2E

S26|S25
S35|S36

1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 25 S., R. 2 E.

CHAINS

The cor. is located on SE. slope of hill in sagebrush growth 275 lks. dist. N. of draw, 3 chs. wide, that drains N. 40° E., into Johnson Reservoir.

At the 1/4 sec. cor. of secs. 25 and 26, marked with a trachyte stone 14x10x10 ins., firmly set and plainly mkd. 1/4 on W. face.

At the 1/4 sec. cor. of secs. 25 and 26, marked with a trachyte stone 14x10x10 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 4 ft. base, 1½ ft. high, W. of cor. Brass cap mkd.

T25S R2E

½
S26 | S25

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope in sagebrush growth 182 lks. dist. S. of trail road and high water mark on the S. shore of Johnson Reservoir that bears E. and W. 130 lks. dist. N. of timber line that bears E. and W.

At the 1/4 sec. cor. of secs. 34 and 35, marked with a trachyte stone 14x12x6 ins., firmly set and plainly mkd. 1/4 on W. face.

There is no remaining evidence of the original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T25S R2E

½
S34 | S35

1969

From which I mark

An aspen, 7 ins. in diam., bears N. 67° E., 41 lks. dist., mkd. 1/4 S35 BT.

An aspen, 6 ins. in diam., bears S. 11° W., 25 lks. dist., mkd. 1/4 S34 BT.

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 25 S., R. 2 E.

CHAINS

The cor. is located on nearly level land in aspen and scattered pine growth approx. 9 chs. dist. W. of trail road that bears N. and S.

At the 1/4 sec. cor. of secs. 33 and 34, marked with a trachyte stone 14x12x8 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone. Raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T25S R2E

1
S33|S34

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle SE. slope, at the base of hill that bears N. 15° E. and S. 45° W. in sagebrush growth, no timber.

Remonumentation of Corners in T. 25 S., R. 6 W.

Township 25 South, Range 6 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following corners were established by M. T. Burgess in 1877.

At the cor. of secs. 28, 29, 32 and 33, marked with a red sandstone 12x12x8 ins., firmly set and plainly mkd. with 1 notch on the S., 2 on the W., 4 on the E., and 5 on the N., (same as record).

From which,

A cedar, 30 ins. in diam., bears S. 55° E., 348 lks. dist., mkd. with a blaze (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T25S R6W

S29|S28
S32|S33

1969

Remonumentation of Corners in T. 25 S., R. 6 W.

CHAINS

From which I mark

A cedar, 6 ins. in diam., bears N. 55° W., 2 lks. dist., mkd. T25S R6W S29 BT.

Deposit the original stone alongside the corner.

The cor. is located on NE. slope of hill in thick cedar growth 2 chs. dist. S. of small creek, 10 lks. wide, 6 ins. deep, that flows N. 45° W.

At the 1/4 sec. cor. of secs. 29 and 32, marked with a granite stone 14x12x9 ins., firmly set and plainly mkd. 1/4 on N. face.

From which,

A cedar, 15 ins. in diam., bears S. 15° E., 113 lks. dist., mkd. with a blaze, (same as record).

A cedar, 14 ins. in diam., bears N. 22° 30' W., 173 lks. dist., mkd. with a blaze, (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3½ ft. base, 1½ ft. high, to N. Brass cap mkd.

T25S R6W

½ $\frac{S29}{S32}$

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle NW. slope of hill in thick cedar growth approx. 20 chs. dist. S. of Highway 4, that bears E. and W.

At the 1/4 sec. cor. of secs. 29 and 30, marked with a sandstone 14x10x6 ins., firmly set and plainly mkd. 1/4 on W. face.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 15 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T25S R6W

½ $\frac{S30}{S29}$

1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 25 S., R. 6 W.

CHAINS

The cor. is located on nearly level land at W. edge of railed and reseeded area that bears N. and S. 7 lks. dist. E. of four strand fence that bears N. and S. in scattered cedar growth on W.

At the cor. of secs. 19, 20, 29 and 30, marked with a quartzite stone, 14x8x5 ins., firmly set and plainly mkd. with 5 notches on the E., 4 on the N., 2 on the S. and 1 on the W. (same as record)

From which,

A cedar, 14 ins. in diam., bears N. 70° W., 319 lks. dist., mkd. T25S R6W S19 BT, (record N. 70° W., 323 lks. dist.).

There is no remaining evidence of the other bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T25S R6W

S19	S20
S30	S29

1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land at the W. edge of railed and reseeded area that bears N. and S. 12 lks. dist. E. of four strand fence that bears N. and S. in scattered cedar growth to W. of corner.

Remonumentation of Corners in T. 26 S., R. 1 W.

Township 26 South, Range 1 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following cors. were established by J. G. Burrill in 1874.

At the cor. of secs. 14, 15, 22 and 23, marked with a flintstone, 18x8x6 ins., firmly set and plainly mkd. with 3 notches on the S., and 2 on the E. edge.

From which,

A cedar, 12 ins. in diam., bears S. 30° W., 34 lks. dist., mkd. T26S R1W S22 BT. (record a pine, S. 55° W., 60 lks. dist.).

A pine, 12 ins. in diam., bears N. 10° 30' W., 116 lks. dist., mkd. T26S R1W S15 BT. (record a cedar, N. 82° W., 85 lks. dist.).

Remonumentation of Corners 'n 26 S

CHAINS

There is no remaining evidence of the other two bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base to brass cap mkd.

T26S R1W

S15	S14
S22	S23

1969

The original stone in mound alongside the corner.

The cor. is located on S. slope of hill in scattered pine and cedar growth 2 chs. dist. S. of top of spur projecting E. approx. 6 chs. dist. N. of draw that drains E.

At the cor. of secs. 21, 22 27 and 28, marked with a trachyte stone 16x12x6 ins., firmly set and plainly mkd. with 3 notches on the E. and 2 on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T26S R1W

S21	S22
S28	S27

1969

Deposit the original stone alongside the corner.

The cor. is located on N. slope of small rise in sagebrush growth 40 lks. dist. S. of wash, 10 lks. wide, $1\frac{1}{2}$ ft. deep, that drains E. approx, 12 chs. dist. W. of trail road that bears N. 60° W. and S. 60° E.

At the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, marked with a basalt stone 16x12x8 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

T26S R1W

$\frac{1}{4}$	S22
	S27

1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 26 S., R. 1 W.

CHAINS

The cor. is located on SW. slope of small hill, in cedar and pinon growth 60 lks. dist. E. of wash, 10 lks. wide, 6 ft. deep, that drains S. 170 lks. dist. E. of trail road that bears N. and S.

Remonumentation of Corners in T. 26 S., R. 2 W.

Township 26 South, Range 2 West, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by Breckon and McCarty in 1897.

At the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., marked with a sandstone 18x14x6 ins., firmly set and plainly mkd. with 5 notches on the S. and 1 on the N. edge.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T26S
R2W R1W
S1 | S6
S12 | S7

1969

Deposit the original stone alongside the corner.

The cor. is located on SW. slope of hill in scattered aspen growth at the cor. of old pole fence that bears W. and S. at SW. edge of grassy clearing.

At the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., marked with a trachyte stone 18x14x10 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T26S
R2W R1W
 $\frac{1}{4}$
S12 | S7

1969

From which I mark

Remonumentation of Corners in T. 26 S., R. 2 W.

CHAINS

A pine, 14 ins. in diam., bears S. 35° E., 41 lks. dist., mkd. 1/4 S7 BT.

A pine, 14 ins. in diam., bears N. 30° W., 81 lks. dist., mkd. 1/4 S12 BT.

Deposit the original stone alongside the corner.

The cor. is located on top of small spur that projects S., in scattered aspen and pine growth at the cor. of old pole fence that bears W. and N.

At the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., marked with a trachyte stone 16x12x7 ins., firmly set and plainly mkd. with 5 notches on the W. and 1 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3½ ft. base, 1½ ft. high, to W. Brass cap mkd.

T26S R2W

S35	S36
S2	S1

T27S R2W

1969

Deposit the original stone alongside the corner.

The cor. is located on steep SW. slope of hill in sage-brush clearing, surrounded by mahogany and cedar growth 2½ chs. dist. W. of top of hill that bears N. 45° W. and S. 45° E. approx. 12 chs. dist. E. of trail road in canyon that bears N. and S.

At the 1/4 sec. cor. of secs. 23 and 24, marked with a ironstone 18x12x4 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T26S R2W

½	
S23	S24

1969

Deposit the original stone alongside the corner.

The cor. is located on SW. slope of hill in scattered aspen growth, 2½ chs. dist. S. of top of hill that bears S. 45° E. and N. 45° W.

Remonumentation of Corners in T. 26 S., R. 2 W.

CHAINS

At the cor. of secs. 13, 14, 23 and 24, marked with a trachyte stone 18x12x8 ins., firmly set and plainly mkd. with 3 notches on the S. and 1 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T26S R2W

S14	S13
S23	S24

1969

From which I mark

An aspen, 8 ins. in diam., bears N. 41° E., 23 lks. dist., mkd. T26S R2W S13 BT.

An aspen, 7 ins. in diam., bears S. 25° E., 7 lks. dist., mkd. T26S R2W S24 BT.

An aspen, 5 ins. in diam., bears S. $41^{\circ} 30'$ W., 14 lks. dist., mkd. T26S R2W S23 BT.

An aspen, 9 ins. in diam., bears N. 55° W., 3 lks. dist., mkd. T26S R2W S14 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle E. slope $2\frac{1}{2}$ chs. dist. W. of draw that drains S.

At the cor. of secs. 11, 12, 13 and 14, marked with a trachyte stone 20x8x6 ins., firmly set and plainly mkd. with 4 notches on the S. and 1 on the E.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T26S R2W

S11	S12
S14	S13

1969

Deposit the original stone alongside the corner.

The cor. is located at S. edge of grassy flat in fence that bears N. and S. 35 lks. dist.; thence N. 74° W., 1 ch. N. of tree line that bears E. and W. approx. 6 chs. dist. W. of dirt road that bears N. 45° W. and S. 45° E.

Remonumentation of Corners in T. 26 S., R. 2 W.

CHAINS

At the 1/4 sec. cor. of secs. 11 and 12, marked with a trachyte stone 16x8x5 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T26S R2W

$\frac{1}{2}$
S11 | S12

1969

From which I mark

An aspen, 6 ins. in diam., bears N. $51^{\circ} 30'$ E., 52 lks. dist., mkd. 1/4 S12 BT.

An aspen, 5 ins. in diam., bears S. $17^{\circ} 30'$ W., 40 lks. dist., mkd. 1/4 S11 BT.

Deposit the original stone alongside the corner.

The cor. is located on S. slope of hill in scattered aspen growth approx. 20 chs. dist. N. of trail road that bears N. 45° E. and S.

At the 1/4 sec. cor. of secs. 14 and 23, marked with a trachyte stone 16x10x3 ins., firmly set and plainly mkd. 1/4 on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

T26S R2W

$\frac{1}{2}$ $\frac{S14}{S23}$

1969

Deposit the original stone alongside the corner.

The cor. is located in grassy flat 60 lks. dist. N. of trail road that bears N. 45° W. and S. 45° E. 175 lks. dist. N. of edge of aspens and pines that bear NW. and SE.

At the 1/4 sec. cor. of secs. 10 and 11, marked with a trachyte stone 20x14x8 ins., firmly set and plainly mkd. 1/4 on W. face.

There is no remaining evidence of the original bearing trees.

Remonumentation of Corners in T. 26 S., R. 2 W.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T26S R2W

$\frac{1}{4}$
S10|S11

1969

From which I mark

An aspen, 8 ins. in diam., bears N. 51° E., 48 lks. dist., mkd. $1/4$ S11 BT.

An aspen, 6 ins. in diam., bears N. 31° W., 49 lks. dist., mkd. $1/4$ S10 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle S. slope at the N. edge of draw that drains N. 70° W. and at edge of aspens that bears N. 70° W. and S. 70° E.

At the $1/4$ sec. cor. of secs. 21 and 28, marked with a trachyte stone $14 \times 8 \times 6$ ins., firmly set and plainly mkd. $1/4$ on N. face.

From which,

A spruce, 16 ins. in diam., bears N. 24° E., 16 lks. dist., mkd. $1/4$ S BT, (record N. $22^{\circ} 50'$ E., 14 lks. dist.).

A spruce, 12 ins. in diam., bears S. $87^{\circ} 40'$ E., 6 lks. dist., mkd. $1/4$ S BT, (same as record).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T26S R2W

$\frac{1}{4}$ $\frac{S21}{S28}$

1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land in thick pine and aspen growth at the cor. of old pole fence that bears N. and W. with trail road alongside.

At the cor. of secs. 20, 21, 28 and 29, marked with a trachyte stone $18 \times 10 \times 8$ ins., firmly set and plainly mkd. with 4 notches on the E. and 2 on the S. edge.

Remonumentation of Corners in T. 26 S., R. 2 W.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T26S R2W

<u>S20</u>	<u>S21</u>
S29	S28

1969

Deposit the original stone alongside the corner.

The cor. is located in grassy meadow land in old pole fence line that bears E. and W. 270 lks. dist. N. of trail road that bears N. 70° W. and S. 70° E.

At the cor. of secs. 29, 30, 31 and 32, marked with a trachyte stone $20 \times 12 \times 10$ ins., firmly set and plainly mkd. with 5 notches on the E. and 1 on the S. edge.

There is no remaining evidence of the four original bearing trees (aspen).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T26S R2W

<u>S30</u>	<u>S29</u>
S31	S32

1969

From which I mark

An aspen, 8 ins. in diam., bears N. 43° E., 35 lks. dist., mkd. T26S R2W S29 BT.

An aspen, 6 ins. in diam., bears S. 23° E., 61 lks. dist., mkd. T26S R2W S32 BT.

A pine, 12 ins. in diam., bears S. 60° W., 36 lks. dist., mkd. T26S R2W S31 BT.

A pine, 14 ins. in diam., bears N. $81^{\circ} 30'$ W., 60 lks. dist., mkd. T26S R2W S30 BT.

Deposit the original stone alongside the corner.

The cor. is located on S. slope and at head of small draw that drains S. 45° W. in thick aspen and pine growth at the cor. of pole fence that bears W. and S.

At the cor. of secs. 19, 20, 29 and 30, marked with a granite stone $16 \times 14 \times 8$ ins., firmly set and plainly mkd. with 5 notches on the E. and 2 on the S. edge.

From which,

Remonumentation of Corners in T. 26 S., R. 2 W.

CHAINS

A spruce, 7 ins. in diam., bears S. 55° E., 15 lks. dist., mkd. T26S R2W S29 BT, (same as record).

A spruce, 14 ins. in diam., bears N. 56° 40' W., 60 lks. dist., mkd. T26S R2W S19 BT, (same as record).

There is no remaining evidence of the other two original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and in a collar of stone to brass cap mkd.

T26S R2W

S19|S20

S30|S29

1969

From which I mark

A spruce, 10 ins. in diam., bears N. 79° E., 30 lks. dist., mkd. T26S R2W S20 BT.

A white pine, 6 ins. in diam., bears S. 76° W., 32 lks. dist., mkd. T26S R2W S30 BT.

Deposit the original stone alongside the corner.

The cor. is located on NE. slope of hill in thick pine growth.

At the cor. of secs. 17, 18, 19 and 20, marked with a trachyte stone 18x8x4 ins., firmly set and plainly mkd. with 5 notches on the E. and 3 on the S. edge.

From which,

A spruce, 10 ins. in diam., bears N. 77° 30' E., 66 lks. dist., mkd. T26S R2W S17 BT, (record N. 77° 30' E., 69 lks. dist.).

A spruce, 16 ins. in diam., bears S. 52° 45' W., 55 lks. dist., mkd. T26S R2W S19 BT, (same as record).

There is no remaining evidence of the other two original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a mound of stone to brass cap mkd.

T26S R2W

S18|S17

S19|S20

1969

Remonumentation of Corners in T. 26 S., R. 2 W.

CHAINS

Deposit the original stone alongside the corner.

The cor. is located on gentle NE. slope in scattered pine growth at the cor. of old pole fence that bears E., W. and S.

Remonumentation of Corners in T. 26 S., R. 4½ W.

Township 26 South, Range 4½ West, Salt Lake Meridian, is located within the Fishlake National Forest. The following corner was established by Page and Erwin in 1900.

At the 1/4 sec. cor. of secs. 7 and 18, marked with a trachyte stone 16x10x9 ins., firmly set and plainly mkd. 1/4 S7 on N. face and S18 on S. face, (same as record).

From which,

A cedar, 8 ins. in diam., bears S. 12° 30' E., 42 lks. dist., mkd. 1/4 S18 BT, (record pinon S. 10° W., 60 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to N. Brass cap mkd.

T26S R4½W

½ $\frac{S7}{S18}$

1969

Deposit the original stone alongside the corner.

The cor. is located on SW. slope of hill in railed and reseeded area approx. 5½ chs. dist. S. of five strand power line that bears S. 80° W. and N. 80° E.

Remonumentation of Corners in T. 26 S., R. 5 W.

Township 26 South, Range 5 West, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by Page and Erwin in 1900.

At the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., marked with a trachyte stone 14x8x6 ins., firmly and plainly mkd. with 3 notches on the N. and S. edges.

From which,

A cedar, 12 ins. in diam., bears S. 59° W., 22 lks. dist., mkd. T26S R5W S24 BT, (record S. 70° W., 25 lks. dist.).

Remonumentation of Corners in T. 26 S., R. 5 W.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T26S
R5W R4 $\frac{1}{2}$ W
S13|S18
S24|S19
1969

Deposit the original stone alongside the corner.

The cor. is located on N. slope of small rise and at head of small draw that drains N. 45° E. in railed and reseeded area.

At the $1/4$ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., marked with a trachyte stone 20x10x8 ins., firmly set and plainly mkd. $1/4$ S13 on W. face and S18 on E. face, (same as record).

From which,

A pinon pine, 6 ins. in diam., bears S. 70° W., 37 lks. dist., mkd. $1/4$ S13 BT, (record N. 75° W., 38 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T26S
R5W R4 $\frac{1}{2}$ W
 $\frac{1}{4}$
S13|S18
1969

From which I mark

A pinon pine, 8 ins. in diam., bears S. 88° E., 3 lks. dist., mkd. $1/4$ S18 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope of hill in scattered pinon growth $5\frac{1}{2}$ chs. dist. S. of trail road that bears E. and W.

At the $1/4$ sec. cor. of secs. 13 and 14, marked with a trachyte stone 18x12x6 ins., firmly set and plainly mkd. $1/4$ on W. face.

From which,

Remonumentation of Corners in T. 26 S., R. 5 W.

CHAINS

A pinon pine, 8 ins. in diam., bears S. 85° E.,
15 lks. dist., mkd. 1/4 S13 BT, (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24
ins. in the ground and raise a mound of stone 3 ft. base,
1½ ft. high, to W. with brass cap mkd.

T26S R5W

½
S14 | S13

1969

Deposit the original stone alongside the corner.

The cor. is located on S. slope of hill in cedar and
pinon growth 2 chs. dist. S. of top of spur projecting
W. approx. 9 chs. dist. N. of draw that drains E.

At the cor. of secs. 11, 12, 13 and 14, marked with a
trachyte stone 16x12x6 ins., firmly set and plainly mkd.
with 4 notches on the S. and 1 on the E. edge.

From which,

A pinon pine, 12 ins. in diam., bears S. 80° W.,
15 lks. dist., mkd. T26S R5W S14 BT, (record a
cedar S. 80° W., 25 lks. dist.).

A cedar, 12 ins. in diam., bears N. 45° W., 25 lks.
dist., mkd. T26S R5W S11 BT, (record a pinon tree
N. 45° W., 20 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20
ins. in the ground and in a collar of stone to brass
cap mkd.

T26S R5W

S11 | S12
S14 | S13

1969

Deposit the original stone alongside the corner.

The cor. is located on N. slope of hill in cedar and
pine growth 3 chs. dist. N. of top of spur projecting
W. 2 chs. dist. S. of small draw that drains W.

At the 1/4 sec. cor. of secs. 12 and 13, marked with a
trachyte stone 14x14x12 ins., firmly set and plainly mkd.
1/4 S12 on N. face and S13 on S. face.

There is no remaining evidence of the original bearing
trees.

At the cor. point

Remonumentation of Corners in T. 26 S., R. 5 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground and in a mound of stone to brass cap mkd.

T26S R5W

$\frac{1}{4}$ $\frac{S12}{S13}$
1969

From which I mark

A pine, 12 ins. in diam., bears S. 35° W., 59 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

A cedar, 6 ins. in diam., bears N. 45° E., 35 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle E. slope of hill in small grove of cedars and pines, surrounded by railed and re-seeded area about 4 chs. dist. W. of trail road that bears N. 45° W. and S. 45° E.

At the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, marked with a trachyte stone 16x12x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ S11 on W. face and S12 on E. face.

From which,

A pinon pine, 10 ins. diam., bears N. 71° E., 20 lks. dist., mkd. $\frac{1}{4}$ S12 BT (record N. 10° E., 20 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone to brass cap mkd.

T26S R5W

$\frac{1}{4}$
S11 | S12
1969

Deposit the original stone alongside the corner.

The cor. is located on steep SW. slope of hill in thick cedar and pinon growth approx. 7 chs. dist. S. of top of hill that bears N. 50° W. and S. 50° E.

Remonumentation of Corners in T. 27 S., R. 1 W.

Township 27 South, Range 1 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following cors. were established by Breckon and McCarty in 1896.

Remonumentation of Corners in T. 27 S., R. 1 W.

CHAINS

At the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, marked with a trachyte stone 18x12x8 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T27S R1W

$\frac{1}{4}$ $\frac{S5}{S8}$

1969

Deposit the original stone alongside the corner.

The cor. is located on broken, rocky E. slope of hill in scattered cedar and pinon growth at the corner of a four strand fence that bears S. and E.

At the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, marked with a sandstone 14x7x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T27S R1W

$\frac{1}{4}$ $\frac{S19}{S30}$

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope in scattered cedar and cotton wood growth at the mouth of draw that drains N. 2 cas. dist. into Box Creek that flows E.

Remonumentation of Corners in T. 27 S., R. 2 W.

Township 27 South, Range 2 West, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by Breckon and McCarty in 1897.

At the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., marked with a trachyte stone 14x8x6 ins., firmly set and plainly mkd. with 4 notches on the N. and 2 on the S. edges.

At the cor. point.

Remonumentation of Corners in T. 27 S., R. 2 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 6 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T27S
R2W R1W
S24|S19
S25|S30

1969

The original stone in mound alongside the corner.

The cor. is located on top of steep, broken spur projecting N. 80° E. in scattered pine and cedar growth approx. 14 chs. dist. S. of Box Creek that flows E.

At the cor. of secs. 1, 2, 11 and 12, marked with a trachyte stone $20 \times 14 \times 12$ ins., firmly set and plainly mkd. with 5 notches on the S. and 1 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 16 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T27S R2W
S2|S1
S11|S12

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle NW. slope of small rise in sagebrush growth 150 lks. dist. E. of draw that drains S. 126 lks. dist. W. of four strand fence that bears N. and S. approx. 8 chs. dist. S. of dirt road that bears E. and W.

At the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, marked with a trachyte stone $16 \times 10 \times 6$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

T27S R2W
 $\frac{1}{4}$ S2
S11
1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 27 S., R. 2 W.

CHAINS

The cor. is located on S. slope of hill in sagebrush growth approx. 20 chs. dist. N. of Lower Box Creek Reservoir.

At the 1/4 sec. cor. of secs. 2 and 3, marked with a trachyte stone 16x12x8 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T27S R2W

S3|S2

1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land in sagebrush growth approx. 10 chs. dist. S. of Monroe Mountain Road, that bears S. 65° E. and N. 65° W.

Remonumentation of Corners in T. 27 S., R. 3 W.

Township 27 South, Range 3 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following corners were established by John T. Breckon in 1896.

At the cor. of secs. 13, 17, 20 and 24, on the E. bdy. of the Tp., marked with a quartzite stone 18x8x6 ins., firmly set and plainly mkd. with 3 notches on the N. and S. edges.

From which,

A cedar, 7 ins. in diam., bears N. 36° 45' E., 42 lks. dist., mkd. T27S R2½W S17 BT, (same as record).

A cedar, 18 ins. in diam., bears S. 51° 35' W., 59 lks. dist., mkd. T27S R3W S24 BT, (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T27S
R3W R2½W

S13|S17
S24|S20

1969

Remonumentation of Corners in T. 27 S., R. 3 W.

CHAINS

Deposit the original stone alongside the corner.

The cor. is located on gentle SW. slope of hill in scattered cedar and pine growth in net wire fence line that bears N. and S. 10 lks. dist. N. of trail road that bears N. 70° W. and S. 70° E.

At the cor. of secs. 8, 12, 13 and 17, on the E. bdy. of the Tp., marked with a sandstone 20x8x8 ins., firmly set and plainly mkd. with 4 notches on the S. and 2 notches on the N. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 8 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T27S
R3W R2½W

S12|S8
S13|S17

1969

Deposit the original stone alongside the corner.

The cor. is located on SW. slope of hill in scattered pine and cedar growth in netwire fence line that bears N. and S. approx. 4 chs. dist. N. of small draw that drains W. into Durkee Springs.

At the 1/4 sec. cor. of secs. 8 and 12 on the E. bdy. of the Tp., marked with a sandstone 18x7s6 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 12 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T27S
R3W R2½W

½
S12|S8

1969

Deposit the original stone alongside the corner.

The cor. is located on W. slope of hill in sagebrush growth in netwire fence line that bears N. and S. approx. 5 chs. dist. S. of trail road that bears S. 45° W. and N. 45° E.

At the cor. of secs. 1, 5, 8 and 12 on the E. bdy. of the Tp., marked with a quartzite stone 16x12x6 ins., firmly set and plainly mkd. with 5 notches on the S. and 1 notch on the N.

Remonumentation of Corners in T. 27 S., R. 3 W.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 15 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T27S
R3W R2 $\frac{1}{2}$ W
S1|S5
S12|S8
1969

Deposit the original stone alongside the corner.

The cor. is located on S. slope of hill in scattered pine and cedar growth $2\frac{1}{2}$ chs. dist. N. of ravine that drains S. 75° W. in netwire fence line that bears N. and S.

At the cor. of Tps. 27 and 28 S., Rs. 3 and 4 W., mkd. with a quartzite boulder 30x20x16 ins., firmly set and plainly mkd. with 6 notches on the N., S., E. and W. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 12 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T27S
R4W R3W
S36|S31
S1|S6
T28S
1969

The original stone in mound alongside the corner.

The cor. is located on E. slope of gentle rolling foothills, in sagebrush growth 3 chs. dist. N. of old trail road that bears E. and W.

Remonumentation of Corners in T. 29 S., R. 3 W.

Township 29 South, Range 3 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following corners were established by Page and Erwin in 1900.

At the cor. of secs. 19 and 30 on the W. bdy. of the Tp., marked with an iron stone 20x18x16 ins., firmly set and plainly mkd. with 4 notches on the N. and 2 on the S. edge.

At the cor. point

Remonumentation of Corners in T. 29 S., R. 3 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone. Raise a mound of stone 4 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T29S
R4W R3W
S24 | $\frac{S19}{S30}$

1969

The original stone in mound alongside the corner.

The cor. is located on rocky SE. slope of small hill, 50 lks. dist. S. of top and $3\frac{1}{2}$ chs. dist. N. of wash, 40 lks. wide, 10 ft. deep, that drains E. In very scattered pine growth.

Remonumentation of Corners in T. 29 S., R. 4 W.

Township 29 South, Range 4 West, Salt Lake Meridian, is located almost entirely within the Fishlake National Forest. The following cor. was established by Page and Erwin in 1900.

At the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, marked with a trachyte stone 18x10x8 ins., firmly set and plainly mkd. $\frac{1}{4}$ S27 on W. face and S26 on E. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 14 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T29S R4W
 $\frac{1}{4}$
S27 | S26

1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land in City Creek Canyon that bears S. 65° E. and N. 65° W. 124 lks. dist. S. of improved dirt road that bears S. 58° E. and N. 58° W. in oak and sagebrush growth.

CHAINS

Blank

Page

CERTIFICATE OF SURVEY

(I) ~~(ME)~~, **Ferrel D. Reynolds**, **HEREBY**

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of February, 1961, (I) ~~(WE)~~ have remonumented corners in T. 24 S., R. 2 E., Tps. 24 S., Rs. 4 and 5 W., T. 25 S., R. 2 E., T. 25 S., R. 6 W., Tps. 26 S., Rs. 1, 2, 4½ and 5 W., Tps. 27 S., Rs. 1, 2 and 3 W., Tps. 29 S., Rs. 3 and

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(WE)~~ and under (my) ~~(OUR)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 19, 1970
(Date)

Ferrel D. Reynolds
~~(Cadastral Surveyor)~~
Surveying Technician

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JUN 2 1970

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of corners in T. 24 S., R. 2 E., Tps. 24 S., Rs. 4 and 5 W., T. 25 S., R. 2 E., T. 25 S., R. 6 W., Tps. 26 S., Rs. 1, 2, 4½ and 5 W., Tps. 27 S., Rs. 1, 2 and 3 W., and Tps. 29 S., Rs. 3 and Salt Lake Meridian, Utah

executed by Ferrel D. Reynolds, Surveying Technician
having been critically examined and found correct, are hereby approved.

DEC 1 1971
(Date)

Clark F. Summ
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief, Division of Cadastral Survey)~~

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

117

ORIGINAL
FIELD NOTES
OF THE

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 28 SOUTH, RANGE 21 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

H. Dennis Badger Supervisory Cadastral Surveyor

Under special instructions dated January 12, 19 71, which provided for the surveys
included under Group Number 524, approved February 25, 1971,
and assignment instructions dated May 26, 19 71.

Survey commenced June 14, 19 72

Survey completed June 30, 19 72

The following field notes are those of the survey of a portion of the subdivisional lines of T. 28 S., R. 21 E.

The north boundary was surveyed by R. C. Yundt, in 1926. The east boundary was surveyed by Willis W. Bandy in 1924. The south boundary was surveyed by Ernst Buettner in 1884, and resurveyed by Leland P. Lewis in 1954. The west boundary was surveyed by C. F. Moore in 1926. A portion of the subdivisional lines were surveyed by Leland P. Lewis in 1954.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated January 12, 1971.

The directions of the lines of survey were determined by observations on Polaris. The lines were carried forward by sustained angulation being supplemented by numerous observations on Polaris taken throughout the progress of the survey.

The lengths of all lines were determined by chaining where possible; otherwise by triangulation. The details of such triangulations have been thoroughly verified and in order to simplify the record the diagrams and reductions are omitted from these field notes.

The geographic position of the southeast corner of the township is at Latitude $38^{\circ} 18' 56''$ N. and Longitude $109^{\circ} 33' 02''$ W. as determined by Leland P. Lewis in 1954.

The magnetic declination was read at a number of stations throughout the progress of the survey and the average of these readings was found to be $15^{\circ} 15'$ E.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

Beginning at the cor. of secs. 25, 26, 35 and 36, monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 18 ins. above ground and in a mound of stone, with brass cap mkd.

T28S R21E
 $\frac{S26|S25}{S35|S36}$
 1954

N. $0^{\circ} 11'$ W., bet. secs. 25 and 26.

Over broken desert land, through scattered timber, by triangulation.

- 3.00 Trail road, bears E. and W.
- 5.00 Draw, drains irregularly E.
- 7.00 Same trail road, bears E. and W.
- 30.00 Top of exposed sandstone spur, slopes E.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
62.75	Sandstone spur, slopes S.; end triangulation.
80.26	The cor. of secs. 23, 24, 25 and 26.
	Land, broken desert. Soil, sandy. Timber, scattered juniper and pinon.
	N. 0° 11' W., bet. secs. 23 and 24.
	Over gently rolling desert land, through scattered timber.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28S R21E $\frac{1}{4}$ S23 S24 1972
45.00	Base of escarpment, bears E. and W.
45.80	Top of escarpment, bears E. and W.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.
	T28S R21E S14 S13 S23 S24 1972
	Land, gently rolling. Soil, sandy. Timber, scattered juniper and pinon.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 12 ins. above ground, with brass cap mkd.
	T28S R21E R22E S13 S18 S24 S19 1924
	N. 89° 49' W., bet. secs. 13 and 24.
	Over nearly level land, through scattered timber.
30.00	Trail road, bears N. 35° E. and S. 35° W.
40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS		<div>T28S R21E S13 $\frac{1}{4}$ S24 1972</div>
		Cor. is located 55 lks. west of base of sloping sandstone ledge.
80.18	The cor. of secs. 13, 14, 23 and 24.	
	Land, nearly level.	
	Soil, sandy.	
	Timber, scattered juniper and pinon.	
	<hr/>	
	N. 0° 11' W., bet. secs. 13 and 14.	
	Over rolling desert land, through dense timber.	
36.90	Begin triangulation.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, falls in the bottom of a small draw, draining W., and impractical to monument.	
40.68	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 13 and 14.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<div>T28S R21E $\frac{1}{4}$ S14 S13 W↓C 1972</div>	
63.00	Bottom of canyon, drains N. 45° E.	
80.00	Point for the cor. of secs. 11, 12, 13 and 14. End triangulation.	
	Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled in solid sandstone and in a mound of stone, 4½ ft. base to top, with brass cap mkd.	
	<div>T28S R21E S11 S12 S14 S13 1972</div>	
	Land, gently rolling.	
	Soil, sandy and sandstone.	
	Timber, dense juniper and pinon.	
	<hr/>	
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 30 ins. above ground and in a mound of stone, with brass cap mkd.	
	<div>T28S R21E R22E S12 S7 S13 S18 1924</div>	

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 89° 49' W., bet. secs. 12 and 13.</p>
	<p>Over broken canyon land, through scattered timber, by triangulation.</p>
38.85	<p>Top of high ledges, bears N. and S.</p>
40.08	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.</p>
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) chiseled in solid sandstone, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T28S R21E $\frac{1}{4}$ $\frac{S12}{S13}$ 1972</p>
68.00	<p>Draw, drains N. 35° E.</p>
80.16	<p>End triangulation.</p>
	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, broken canyon. Soil, sandy and sandstone. Timber, scattered juniper and pinon.</p>
	<p>N. 0° 07' W., bet. secs. 11 and 12.</p>
	<p>Over broken land, through scattered timber.</p>
39.92	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.</p>
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) chiseled in solid sandstone and in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T28S R21E $\frac{1}{4}$ S11 S12 1972</p>
79.84	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 10 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28S R21E $\frac{S2 S1}{S11 S12}$ 1954</p>
	<p>Land, broken. Soil, sandy and sandstone. Timber, scattered juniper and pinon.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy of the Tp., monumented with an iron post, 2 ins. diam., protruding 30 ins. above ground and in a mound of stone, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

T28S
R21E R22E
S1|S6
S12|S7
1924

S. 89° 58' W., bet. secs. 1 and 12.

Over broken land, through scattered juniper and pinon.

14.00 Draw, drains N. 35° E.

40.15 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.

T28S R21E
 $\frac{1}{4}$ S1
S12
1972

80.30 The cor. of secs. 1, 2, 11 and 12.

Land, broken.

Soil, sandy.

Timber, scattered juniper and pinon.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 10 ins. above ground, with brass cap mkd.

T28S R21E
S34|S35
S3|S2
1954

N. 0° 11' W., bet. secs. 34 and 35.

Over gently rolling land, through scattered timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R21E
 $\frac{1}{4}$
S34|S35
1972

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R21E
S27|S26
S34|S35
1972

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Land, gently rolling. Soil, sandy. Timber, scattered juniper.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36. S. 89° 53' W., bet. secs. 26 and 35. Over rolling land, through scattered timber.</p>
11.05	Draw, drains N. 80° E.
24.90	Top of sandstone spur, slopes S.
28.60	Draw, drains irregularly SE.
37.00	Draw, drains irregularly NE.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) chiseled in solid sandstone and in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> $\begin{array}{r} \text{T28S R21E} \\ \frac{1}{4} \frac{\text{S26}}{\text{S35}} \\ 1972 \end{array}$
72.80	Leave timber.
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling. Soil, sandy. Timber, scattered juniper and pinon.</p>
	<p>S. 89° 58' W., bet. secs. 27 and 34. Over rolling desert land.</p>
36.00	Trail road, bears N. 13° W. and S. 13° E.
40.01	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T28S R21E} \\ \frac{1}{4} \frac{\text{S27}}{\text{S34}} \\ 1972 \end{array}$ <p>Set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p>
60.25	Hatch Point Road, an improved gravel road, bears N. 2° 32' W and S. 2° 32' E.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

62.00 Enter scattered timber.

80.02 The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 1 ins. diam. protruding 18 ins. above ground, with brass cap mkd.

T28S R21E
S28|S27
S33|S34
1954

Land, rolling.

Soil, sandy.

Timber, scattered juniper and pinon W. 18.00 chs.

From the cor. of secs. 26, 27, 34 and 35.

N. 0° 11' W., bet. secs. 26 and 27.

Over rolling desert land.

10.15 Trail road, bears N. 85° W. and S. 85° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R21E
 $\frac{1}{4}$
S27|S26
1972

80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam. 24 ins. in the ground, with brass cap mkd.

T28S R21E
S22|S23
S27|S26
1972

Land, rolling.

Soil, sandy.

Timber, none.

From the cor. of secs. 23, 24, 25 and 26.

S. 89° 54' W., bet. secs. 23 and 26.

Over rolling desert land, through scattered timber.

16.10 E. rim of plateau, bears N. and S.; thence over nearly level land. Leave timber.

23.80 Trail road, bears N. 10° E. and S. 10° W.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T28S R21E $\frac{1}{4} \frac{S23}{S26}$ 1972</p>	
80.02	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling to nearly level. Soil, sandy. Timber, scattered juniper and pinon E. 16.00 chs.</p>	
	<p>S. 89° 58' W., bet. secs. 22 and 27.</p> <p>Over nearly level desert land.</p>	
24.70	Trail road, bears N. 30° E. and S. 30° W.	
32.10	Small rocky rim, bears NE. and SW.	
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T28S R21E $\frac{1}{4} \frac{S22}{S27}$ 1972</p>	
	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor.</p>	
51.20	Trail road, bears N. and S.	
68.60	Hatch Point Road, an improved gravel road, bears N. 20° W. and S. 20° E.	
70.50	Base of low ridge, bears N. and S.	
78.00	Top of ridge, bears N. and S.	
79.98	The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2½ ins. diam. protruding 10 ins. above ground and in a mound of stone, with brass cap mkd.	
	<p style="text-align: center;">T28S R21E $\frac{S21}{S28} \frac{S22}{S27}$ 1954</p>	
	<p>Land, nearly level. Soil, sandy. Timber, none.</p>	
	From the cor. of secs. 22, 23, 26 and 27.	
	N. 0° 11' W., bet. secs. 22 and 23.	
	Over gently rolling land.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<div>T28S R21E</div> <div>$\frac{1}{4}$</div> <div>S22 S23</div> <div>1972</div>
80.00	<div>Point for the cor. of secs. 14, 15, 22 and 23.</div> <div>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</div> <div><div>T28S R21E</div><div>S15 S14</div><div>S22 S23</div><div>1972</div></div> <div>Land, gently rolling.</div> <div>Soil, sandy.</div> <div>Timber, none.</div>
	<div>From the cor. of secs. 13, 14, 23 and 24.</div> <div>S. 89° 53' W., bet. secs. 14 and 23.</div> <div>Over gently rolling land, through scattered timber.</div>
9.55	Draw, drains N. 10° E.
22.00	Leave timber.
26.30	Trail road, bears N. 40° W. and S. 40° E.
40.02	<div>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.</div> <div>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</div> <div><div>T28S R21E</div><div>$\frac{1}{4}$ $\frac{S14}{S23}$</div><div>1972</div></div>
80.04	<div>The cor. of secs. 14, 15, 22 and 23.</div> <div>Land, gently rolling.</div> <div>Soil, sandy.</div> <div>Timber, scattered juniper and pinon E. 22.00 chs.</div>
	<div>S. 89° 56' W., bet. secs. 15 and 22.</div> <div>Over gently rolling land.</div>
40.00	<div>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.</div> <div>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</div>

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<p>T28S R21E $\frac{1}{4} \frac{S15}{S22}$ 1972</p>
44.00	Trail road, bears N. 40° W. and S. 40° E.
80.00	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2½ ins. diam., protruding 8 ins. above ground and in a collar of stone, with brass cap mkd.</p> <p>T28S R21E $\frac{S16 S15}{S21 S22}$ 1954</p> <p>Land, gently rolling. Soil, sandy. Timber, none.</p>
40.00	<p>From the cor. of secs. 14, 15, 22 and 23. N. 0° 11' W., bet. secs. 14 and 15. Over gently rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 15. Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled in solid sandstone and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p>T28S R21E $\frac{1}{4} \frac{S15 S14}{1972}$</p>
72.90	Enter scattered timber.
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p>T28S R21E $\frac{S10 S11}{S15 S14}$ 1972</p> <p>Land, gently rolling. Soil, sandy. Timber, scattered juniper and pinon N. 8.00 chs.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14. S. 89° 54' W., bet. secs. 11 and 14. Over gently rolling land, through scattered timber.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
40.07	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T28S R21E <u>S11</u> S14 1972 </div>
66.65	Draw, drains N.
80.14	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, gently rolling. Soil, sandy. Timber, scattered juniper and pinon.</p>
40.02	<hr/> <p>S. $89^{\circ} 54'$ W., bet. secs. 10 and 15.</p> <p>Over rolling land, through scattered timber.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T28S R21E <u>S10</u> $\frac{1}{4}$ <u>S15</u> 1972 </div>
80.04	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 6 ins. above ground and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T28S R21E <u>S9 S10</u> <u>S16 S15</u> 1954 </div> <p>Land, rolling. Soil, sandy. Timber, scattered juniper and pinon.</p>
39.95	<hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. $0^{\circ} 07'$ W., bet. secs. 10 and 11.</p> <p>Over rolling land, through scattered timber.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T28S R21E $\frac{1}{4}$ S10 S11 1972</p>	
59.75	Wash, 15 lks. wide, 4 ft. deep, drains N. 75° W.	
63.45	Wash, 25 lks. wide, 7 ft. deep, drains N. 60° W.	
70.40	Wash, 40 lks. wide, 6 ft. deep, drains N. 20° E.	
79.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 80° E.	
79.90	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2½ ins. diam. protruding 10 ins. above ground and in a mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T28S R21E S3 S2 S10 S11 1954</p> <p>Land, rolling. Soil, sandy. Timber, scattered juniper and pinon.</p>	
40.05	<p>S. 89° 56' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through scattered timber.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
-	<p style="text-align: center;">T28S R21E $\frac{1}{4}$ $\frac{S3}{S10}$ 1972</p>	
65.00	Leave timber.	
80.10	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2½ ins. diam., protruding 6 ins. above ground and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T28S R21E S4 S3 S9 S10 1954</p> <p>Land, rolling. Soil, sandy. Timber, scattered juniper and pinon, E. 65.00 chs.</p>	
22.00	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89° 57' W., bet. secs. 28 and 33.</p> <p>Over rolling land, through scattered timber.</p> <p>Draw, drains irregularly N. 45° W.</p>	

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T28S R21E} \\ \frac{1}{4} \frac{\text{S28}}{\text{S33}} \\ 1972 \end{array}$ <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p>
63.75	Trail road, bears N. 33° . E. and S. 33° W.
80.00	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 30 ins. above ground, and in a mound of stone, with brass cap mkd.</p> $\begin{array}{r} \text{T28S R21E} \\ \frac{\text{S29} \text{S28}}{\text{S32} \text{S33}} \\ 1954 \end{array}$ <p>Land, rolling. Soil, sandy. Timber, scattered juniper and pinon.</p>
	<p>N. 0° 13' W., bet. secs. 28 and 29.</p> <p>Over broken canyon land, through scattered timber, by triangulation.</p>
16.00	S. edge of ledgy gulch.
26.00	Bottom of ledgy gulch, 720 ft. deep, drains irregularly S. 55° W.
34.00	N. edge of gulch.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> $\begin{array}{r} \text{T28S R21E} \\ \frac{1}{4} \frac{\text{S29} \text{S28}}{\text{S29} \text{S28}} \\ 1972 \end{array}$
80.00	<p>End triangulation.</p> <p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T28S R21E} \\ \frac{\text{S20} \text{S21}}{\text{S29} \text{S28}} \\ 1972 \end{array}$ <p>Land, broken. Soil, sandy and sandstone.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS		
	Timber, scattered juniper and pinon.	
	From the cor. of secs. 21, 22, 27 and 28.	
	S. 89° 58' W., bet. secs. 21 and 28.	
	Over broken land, through scattered timber.	
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.	
	<div style="text-align: center;"> T28S R21E $\frac{1}{4}$ S21 <u>S28</u> 1972 </div>	
80.16	The cor. of secs. 20, 21, 28 and 29.	
	Land, broken.	
	Soil, sandy and sandstone.	
	Timber, scattered juniper and pinon.	
	N. 0° 08' W., bet. secs. 20 and 21.	
	Over broken sandstone ledges, through scattered timber.	
8.60	Sandstone spur, slopes S. 75° W.; thence by triangulation.	
35.00	Draw, drains irregularly W.	
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground to solid sandstone and in a mound of stone, 4 ft. base to top, with brass cap mkd.	
	<div style="text-align: center;"> T28S R21E $\frac{1}{4}$ S20 S21 1972 </div>	
57.00	Draw, drains irregularly S. 45° W.	
68.80	Top of small sandstone knoll, end triangulation.	
79.94	The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 1 in. diam., protruding 15 ins. above ground, with brass cap mkd.	
	<div style="text-align: center;"> T28S R21E S17 S16 <u>S20 S21</u> 1954 </div>	
	Land, broken.	
	Soil, sandstone.	
	Timber, scattered juniper and pinon.	

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 8, 9, 16 and 17, monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 6 ins. above ground, with brass cap mkd.

T28S R21E
S8|S9
S17|S16
1954

N. $0^{\circ} 13'$ W., bet. secs. 8 and 9.

Over rolling land, through scattered timber.

8.15 Hatch Point Road, an improved gravel road, bears N. $52^{\circ} 10'$ W. and S. $52^{\circ} 10'$ E.

24.75 Leave timber and enter nearly level land.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R21E
 $\frac{1}{4}$
S8|S9
1972

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R21E
S5|S4
S8|S9
1972

Land, rolling to nearly level.

Soil, sandy.

Timber, scattered juniper and pinon S. 25.00 chs.

From the cor. of secs. 3, 4, 9 and 10.

N. $89^{\circ} 59'$ W., bet. secs. 4 and 9.

Over nearly level land.

12.90 Trail road, bears N. and S.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R21E
S4
 $\frac{1}{4}$ S9
1972

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
63.60	Wash, 20 lks. wide, 4 ft. deep, drains irregularly N.
80.00	The cor. of secs. 4, 5, 8 and 9.
	Land, nearly level. Soil, sandy. Timber, none.
	N. 0° 01' W., bet. secs. 4 and 5. Over gently rolling land.
31.00	Draw, drains N. 34° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28S R21E $\frac{1}{4}$ S5 S4 1972
	Set steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.
74.05	Hatch Point Road, an improved gravel road, bears generally N. 40° E. and S. 41° W. on a curve.
84.74	The cor. of secs. 4, 5, 32 and 33, on the N. bdy of the Tp., monumented with an iron post, 2 ins. diam., protruding 10 ins. above ground and in a collar of stone, with brass cap mkd.
	T27S R21E S32 S33 S5 S4 T28S 1926
	Land, gently rolling. Soil, sandy. Timber, none.
	From the cor. of secs. 29, 30, 31 and 32, monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 10 ins. above ground, with brass cap mkd.
	T28S R21E S30 S29 S31 S32 1954
	N. 0° 13' W., bet. secs. 29 and 30.
	Over rolling and broken desert land.
5.50	Draw, drains W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) chiseled in solid sandstone and in a mound of stone, $5\frac{1}{2}$ ft. base to top, with brass cap mkd.

T28S R21E

 $\frac{1}{4}$

S30|S29

1972

42.50 Top of rocky spur, slopes W.

57.80 Spur, slopes W.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T28S R21E

S19|S20

S30|S29

1972

Set a steel fence post, 6 ft. long, in mound alongside the iron post.

Land, rolling and broken.
Soil, sandy and sandstone.
Timber, none.

From the cor. of secs. 20, 21, 28 and 29.

S. $89^{\circ} 50'$ W., bet. secs. 20 and 29.

Over rolling land, through scattered timber.

40.05 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T28S R21E

 $\frac{1}{4}$ S20 $\frac{1}{4}$ S29

1972

46.50 Leave timber and begin steep descent into Lockhart Basin.
Desc. about 1120 ft. over steep NW. slope by triangulation.

80.10 End triangulation.

The cor. of secs. 19, 20, 29 and 30.

Land, rolling E. $\frac{1}{2}$; broken W. $\frac{1}{2}$.
Soil, sandy and sandstone.
Timber, scattered juniper and pinon E. $\frac{1}{2}$.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<p>S. 89° 52' W., bet. secs. 19 and 30.</p> <p>Over rolling and broken desert land.</p> <p>4.00 Bottom of deep wash, drains irregularly SW.</p> <p>7.40 Bottom of main wash, drains S. 30° W.</p> <p>19.50 Trail road, bears NE. and SW.</p> <p>26.00 Trail road, bears NE. and SW.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28S R21E</p> <p>$\frac{1}{4} \frac{S19}{S30}$</p> <p>1972</p> </div> <p>Set steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.</p> <p>58.00 Trail road, bears N. and S.</p> <p>66.30 Wash, 15 lks. wide, 6 ft. deep, drains S.</p> <p>77.10 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 30 ins. above ground and in a mound of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28S</p> <p>R20E R21E</p> <p>$\frac{S24}{S25} \frac{S19}{S30}$</p> <p>1926</p> </div> <p>Land, rolling and broken.</p> <p>Soil, sandy and sandstone.</p> <p>Timber, none.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 13' W., bet. secs. 19 and 20.</p> <p>Over rolling and broken desert land by triangulation.</p> <p>10.00 Draw, drains S. 60° W.</p> <p>21.00 Trail road, bears E. and W. Begin steep ascend out of Lockhart Basin. Ascend about 1,200 ft. over steep S. slope.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, falls on inaccessible ledges where a corner cannot be perpetuated.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 S. R. 2 E. Salt Lake Meridian Utah

CHAINS

scattered timber.

41.64 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs.
19 and 20

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a
cross (X) chiseled in solid rock and in a mound of
stone, 5 ft. base to top, with brass cap mkd.

T28S R21E

$\frac{1}{4}$
S19 S20

W.C.

1972

54.25 Draw, drains irregularly SE.

60.00 Spur, slopes SE.

72.00 Draw, drains irregularly SE.

80.00 End triangulation.

Point for the cor. of secs. 17, 18, 19 and 20.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins.
in the ground to solid rock and in a mound of stone,
3 ft. base to top, with brass cap mkd.

T28S R21E

S18 S17
S19 S20

1972

Set a steel fence post, 6 ft. long, in mound
alongside the iron post.

Land, rolling and broken.

Soil, sandy and sandstone.

Timber, scattered juniper and pinon, N. $\frac{1}{2}$ mile.

From the cor. of secs. 16, 17, 20 and 21.

S. $89^{\circ} 55'$ W., bet. secs. 17 and 20.

Over rolling and broken land, through scattered timber.

4.75 Ledgy canyon, drains S. 56° W.

19.50 Ledgy spur, projects S.

35.50 Ledgy draw, drains S. 39° E. Ascend abruptly over
sandstone ledges facing NE.

40.07 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, falls on
inaccessible ledges where a corner cannot be perpetuated.

47.20 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs.
17 and 20.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam. 2 ins.
in the ground to solid rock and in a mound of stone,
4 ft. base to top, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	$\begin{array}{c} \text{T28S R21E} \\ \frac{1}{4} \quad \frac{\text{S17 W}}{\text{S20 C}} \rightarrow \\ 1972 \end{array}$
60.35	Rim of butte.
80.14	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rolling and broken. Soil, sandy and sandstone. Timber, scattered juniper and pinon.</p>
	<p>S. 89° 45' W., bet. secs. 18 and 19.</p> <p>Over rolling and broken land, through scattered timber.</p>
4.00	Small draw, drains irregularly SE.
14.00	Trail road, bears N. 10° W. and S. 10° E.
17.50	Trail road, bears N. 20° E. and curves S.
24.70	Trail road, bears N. 5° E. and S. 5° W.
38.31	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> $\begin{array}{c} \text{T28S R21E} \\ \frac{1}{4} \quad \frac{\text{W S18}}{\text{C S19}} \leftarrow \\ 1972 \end{array}$ <p>Set a steel fence post, 6 ft. long, 18 ins. in the ground alongside the iron post.</p> <p>Cor. is located at the base of sandstone ledges facing SE.</p> <p>Begin triangulation.</p>
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, falls on inaccessible ledges where a corner cannot be perpetuated.
50.00	Rim of broken bench, bears NE. and SW. End triangulation
76.85	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 16 ins. above ground and in a mound of stone, with brass cap mkd.</p> $\begin{array}{c} \text{T28S} \\ \text{R20E R21E} \\ \frac{\text{S13 S18}}{\text{S24 S19}} \\ 1926 \end{array}$

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHASER

Land, rolling and broken.
Soil, sandy and sandstone.
Timber, scattered juniper and pinon.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 13' W., bet. secs. 17 and 18.

Over rolling land, through scattered timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R21E

$\frac{1}{4}$

S18|S17

1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) chiseled in solid sandstone and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T28S R21E

S7|S8

S18|S17

1972

Land, rolling.
Soil, sandy and sandstone.
Timber, scattered juniper and pinon.

From the cor. of secs. 8, 9, 16 and 17.

S. 89° 50' W., bet. secs. 8 and 17.

Over rolling land, through scattered timber.

9.00 Draw, drains irregularly N.

24.55 Draw, drains irregularly N.

40.07 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T28S R21E

$\frac{1}{4}$ S8

S17

1972

54.00 Draw, drains N.

80.14 The cor. of secs. 7, 8, 17 and 18.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	<p>Land, rolling. Soil, sandy and sandstone. Timber, scattered juniper and pinon.</p>
16.20	<p>S. 89° 43' W., bet. secs. 7 and 18. Over rolling land, through scattered timber. Draw, drains N. 37° E.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> $\begin{array}{r} \text{T28S R21E} \\ \frac{1}{4} \quad \frac{\text{S7}}{\text{S18}} \\ 1972 \end{array}$
46.10	Trail road, bears N. 30° W. and S. 30° E..
76.47	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 20 ins. above ground and in a mound of stone, with brass cap mkd.</p> $\begin{array}{r} \text{T28S} \\ \text{R20E R21E} \\ \text{S12 S7} \\ \hline \text{S13 S18} \\ 1926 \end{array}$
35.00	<p>Land, rolling. Soil, sandy. Timber, scattered juniper and pinon.</p> <p>From the cor. of secs. 7, 8, 17 and 18. N. 0° 13' W., bet. secs. 7 and 8. Over rolling land, through scattered timber. Draw, drains N. 31° E.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T28S R21E} \\ \frac{1}{4} \\ \text{S7 S8} \\ 1972 \end{array}$
54.80	<p>Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post. Cor. is located in bottom of small draw, drains irregularly NE. Top of low ridge, projects E.</p>

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

56.00 Trail road, bears E. and W.

80.00 Point for the cor. of secs. 5, 6, 7 and 8.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T28S R21E} \\ \text{S6|S5} \\ \hline \text{S7|S8} \\ 1972 \end{array}$$

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Land, rolling.

Soil, sandy.

Timber, scattered juniper and pinon.

From the cor. of secs. 4, 5, 8 and 9.

S. $89^{\circ} 56'$ W., bet. secs. 5 and 8.

Over rolling land.

7.50 Draw, drains irregularly N.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T28S R21E} \\ \text{S5} \\ \hline \frac{1}{4} \text{ S8} \\ 1972 \end{array}$$

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

47.20 Hatch Point Road, an improved gravel road, bears general N. and S. on a curve.

47.65 Begin triangulation.

58.00 Enter scattered timber.

64.00 Draw, drains irregularly N.

80.04 End triangulation.

The cor. of secs. 5, 6, 7 and 8.

Land, rolling.

Soil, sandy.

Timber, scattered juniper and pinon, W. 22.00 chs.

S. $89^{\circ} 44'$ W., bet. secs. 6 and 7.

Over rolling land, through scattered timber.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
26.50	Draw, drains N. 36° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T28S R21E $\frac{1}{4}$ $\frac{S6}{S7}$ 1972 </div>
51.00	Draw, drains N. 40° E.
64.00	Draw, drains N. 50° E.
76.22	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 18 ins. above ground and in a mound of stone, with brass cap mkd. <div style="text-align: center;"> T28S R20E R21E $\frac{S1}{S12} \frac{S6}{S7}$ 1926 </div> <p>Land, rolling. Soil, sandy. Timber, scattered juniper and pinon.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8. N. 0° 01' W., bet. secs. 5 and 6. Over rolling land, through scattered timber.</p>
37.00	Draw, drains irregularly W.
40.00	point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, falls on vertical face of ledge where a corner cannot be perpetuated.
40.98	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 5 and 6. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T28S R21E $\frac{1}{4}$ S6 S5 W C ↓ 1972 </div>
42.35	Rim of canyon, bears NE. and SW. Descend about 800 ft. over steep N. slope by triangulation.
84.85	End triangulation.

Survey of a Portion of the Subdivisional Lines,
T. 28 S., R. 21 E., Co. 2, Ariz.

CHAINS

The cor. of secs. 5, 6, 31 and 32, on the N. bdy of the Tp., monumented with an iron post, 2 ins. diam., protruding 20 ins. above ground and in a mound of stone, with brass cap mkd.

T27S R21E

S31|S32

S6|S5

T28S

1926

Land, rolling S. $\frac{1}{2}$; broken canyon N. $\frac{1}{2}$.

Soil, sandy and sandstone.

Timber, scattered juniper and pinon.

General Description

Township 28 South, Range 21 East, is mostly rolling and broken except in the southwest corner which is very rough canyons and steep sandstone ledges where it drops off into Lockhart Basin. The elevation varies from about 6,000 ft. above sea level on the high mesas to about 4,300 ft. above sea level in the bottom of Lockhart Basin. The soil is sandy with exposed sandstone. There is a growth of scattered juniper and pinon throughout the township. The township is accessible with very few trail roads. The drainage of the eastern $\frac{1}{2}$ of the township is in a northeasterly direction. The drainage of the northwest $\frac{1}{4}$ is in a northerly direction. The drainage of the southwest $\frac{1}{4}$ is in a southwesterly direction. There is no clear water and no permanent habitations noted.

The magnetic declination was read at a number of stations throughout the progress of the survey and the average of these readings was found to be $15^{\circ} 15'$ E.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Stewart Burt	Surveying Technician
Gregory Landheim	Surveying Aid
Keith Luke	Surveying Aid
Gregory Darlington	Surveying Aid

(1) ~~(X)~~, H. Dennis Badger

HERREBY

of the **Salt Lake** Meridian, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by (me), ~~XXX~~ and under (my) ~~XXX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

H. Dennis Badger
(Cadastral Surveyor)

Supervisory Cadastral Surveyor

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date JUN 14 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the survey of a portion of the subdivisional lines of T. 28 S., R. 21 E., Salt Lake Meridian, Utah

executed by H. Dennis Badger, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

APR 29 1975

(Date)

Bernard M. DeLoe
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~_____~~, is a true copy of the original field notes.

~~(Date)~~

~~(Chief, Division of Cadastral Survey) and the~~

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

147

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY AND

A PORTION OF THE NORTH BOUNDARY AND

THE SURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 4 SOUTH, RANGE 23 EAST

Of the SALT LAKE Meridian,

In the State of UTAH

EXECUTED BY

Glen B. Hatch

Supervisory Cadastral Surveyor

Under special instructions dated May 17, 19 72, which provided for the surveys
included under Group Number 540, approved May 18, 1972,
and assignment instructions dated June 14, 19 72.

Survey commenced July 6, 19 72

Survey completed July 13, 19 72

INDEX DIAGRAM

Township 4 South, Range 23 East,

6					
11					
9					
11					
11					
14					
23					
26					
35					
36					

Township 4 South, Range 23 East

CHAINS

were remonumented in their original positions. The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., was the only lost corner, and was reestablished by proportionate method.

The geographic position of the southeast corner of section 1 is at Latitude $40^{\circ} 29' 40''$ N. and Longitude $109^{\circ} 16' 12''$ W., as computed from section line ties to U.S.G.S. triangulation station "Divide", at Latitude $40^{\circ} 30' 21.998''$ N. and Longitude $109^{\circ} 18' 16.417''$ W., located S. $52^{\circ} 26' 30''$ E., 17.78 chs. dist. from the closing corner of sections 2 and 3, T. 4 S., R. 23 E.

The mean magnetic declination is $15^{\circ} 30'$ East, as shown on U.S.G.S. quadrangle sheet "Jensen Ridge, Utah", 1966.

Dependent Resurvey of a Portion
of the East Boundary
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by Adolph Jessen and Edgar F. Harmston, Deputy Surveyors, in 1900, and the Retracement Executed by Ralph Gentry, Cadastral Surveyor, in 1916.

Beginning at the cor. of secs. 1 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 1 in. above a concrete collar at cor. of fences extending S. and W. Brass cap mkd.

T4S T4S

$\frac{S1}{S12} \mid \frac{R24E}{S6}$

R23E
DNM
1939

from which the original bearing tree:

A juniper, 7 ins. diam., bears N. $35^{\circ} 30'$ W.,
4 lks. dist., mkd. T4S R23E S1 BT.

Thence,

N. $0^{\circ} 02'$ E., along the E. bdy. of secs. 1.

Over rolling mountain land, through scattered timber Asc. 40 ft. over general SE. slope. Measurement by DI-10, Distomat electronic measuring device, and topography scaled from U.S.G.S. quadrangle "Jensen Ridge, Utah".

3.11

The original cor. of secs. 1, 6, 7 and 12, and remarked as an angle point in the 1939 survey monumented with a sandstone, 16x8x3 ins., firmly set 6 ins. in the ground, and in a collar of stone, mkd. 5 notches on S. and 1 notch on N. edges, and AP on W. face.

Township 4 South, Range 23 East

CHAINS

T. 4 S., R. 23 E.History of SurveysSurveyed by Retr. or Resurveyed byNORTH BOUNDARYAll Jessen & Harmston
1900SOUTH BOUNDARYAll A. D. Ferron 1878
Jessen & Harmston 1900
Elliot Bird 1949EAST BOUNDARYAll Jessen & Harmston
1900
S. 2 miles Ralph Gentry 1916WEST BOUNDARY (Ashley Guide Meridian)All A. D. Ferron 1878
Jessen & Harmston 1900SUBDIVISIONAL LINESPortion Jessen & Harmston
1900
J. C. Clark &
Elliot Bird 1939-
1942BOUNDARIES OF DINOSAUR NATIONAL MONUMENTJ. C. Clark & Elliot Bird
1939 - 42

The following field notes are those of the dependent resurvey of a portion of the east boundary and a portion of the north boundary and the survey of a portion of the subdivisional lines of T. 4 S., R. 23 E., Salt Lake Meridian, Utah.

The dependent resurvey and survey were conducted in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions for Group 540, Utah, dated May 17, 1972.

The direction of the lines of this dependent resurvey and survey were determined from reference to true meridians established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other hour angle observations on Polaris. The lines were run by direct method and the distances determined by DI-10 Distomat, electronic measuring device. Topography is scaled from U.S.G.S. quadrangle sheets "Jensen Ridge" and "Dinosaur Quarry Utah", 1966, unless otherwise noted.

Before restoring the corners the lines of the original survey were retraced and diligent search made for any evidence of the original corners. Identified corners

Dependent Resurvey of a Portion
of the East Boundary,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS

From which the remaining original bearing trees as found and remarked in 1939:

A juniper, 10 ins. diam., bears N. 83° 45' E., 51 lks. dist., mkd. T4S R24E S6 BT AP.

A juniper, 6 ins. diam., bears S. 36° 08' E., 67 lks. dist., mkd. T4S R24E S6 BT AP.

A juniper, 12 ins. diam., bears N. 63° 15' W., 28 lks. dist., mkd. T4S R23E S1 BT AP.

At the angle point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd.

T4S
R23E R24E
AP
|
S1|S6
1972

Bury original cor. stone alongside the iron post.

N. 0° 02' E., beginning new measurement.

Desc. 10 ft. over gentle NW. slope.

2.50 Small draw, drains N. 65° E.; asc. 15 ft. over SE. slope. Leave timber.

6.00 Spur, slopes N. 60° E.; desc. 120 ft. over NW. slope.

18.90 Draw, drains irregularly N. 60° E.; asc. 50 ft. over general SE. slope. Enter timber.

24.90 Small draw, 20 ft. deep, drains S. 35° E.

27.45 Spur, slopes N. 80° E.; desc. 75 ft. over N. slope.

36.89 Point for the E. ¼ sec. cor. of sec. 1, at 40.00 chs. of northing from the cor. of secs. 1 and 12.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S
R23E R24E
¼
|
S1|
1972

Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Desc. 40 ft. over NW. slope.

39.80 Small draw, drains N. 60° E.; asc. 15 ft. over SE. slope.

40.35 The ¼ sec. cor. of secs. 1 and 6, on point of spur,

Dependent Resurvey of a Portion
of the East Boundary,
T. 4 S., R. 23 E. Salt Lake Meridian, Utah

CHAINS

monumented with a sandstone, 10x5x3 ins., set 3 ins. in the ground, and mkd. $\frac{1}{4}$ on W. face. (Record 18x8x8 ins.) This cor. will now function as an angle point only.

from which the original bearing trees:

A juniper, 8 ins. diam., bears S. 25° E., 72 lks. dist., mkd. $\frac{1}{4}$ S6 BT. (Record, S. 27° 10' E., 74 lks.)

A juniper, 6 ins. diam., bears N. 30° W., 16 lks. dist., mkd. $\frac{1}{4}$ S1 BT. (Record, N. 29° 20' W., 13 lks.).

I add the marks "AP" to original bearing trees.

At the angle point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T4S
R23E R24E
AP
|
S1|S6
1972

Bury original cor. stone alongside the iron post.

N. 2° 06' W., beginning new measurement.

Desc. 15 ft. over NE. slope.

- 1.50 Draw, drains N. 65° E.; asc. 50 ft. over SE. slope. Leave timber.
- 4.00 Low spur, slopes N. 60° E.; desc. 60 ft. over N. slope.
- 12.00 Stone Bridge Draw, 30 lks. wide, 12 ft. deep, drains irregularly E.; asc. 100 ft. over S. slope.
- 14.00 Improved dirt road, bears E. to Island Park and W. to Vernal.
- 20.65 The Reef Ridge, bears E. and W.; desc. 200 ft. over NW. slope. Coal Bed Spring, (nearly dry) bears N. 85° W., 6.75 chs. dist.
- 30.85 Draw, 40 lks. wide, 10 ft. deep, drains irregularly E.
- 32.99 The cor. of Tps. 3 and 4 S., Rs. 23 and 24 E., monumented with a sandstone, 18x6x3 ins., firmly set 8 ins. in the ground and in a collar of stone, mkd. 6 notches on N., E., S. and W. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey, of a Portion
of the East Boundary
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS

T3S
R23E R24E

S36|S31
S1|S6
T4S
1972

Bury original cor. stone alongside the iron post.

Land, rolling mountain.

Soil, rocky clay.

Timber, juniper and pinon on S. portion.

Undergrowth, sagebrush and shadscale.

Dependent Resurvey of a Portion of
the North Boundary,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by Adolphe Jessen
and Edgar F. Harmston, Deputy Surveyors, in 1900.

From the cor. of Tps. 3 and 4 S., Rs. 23 and 24 E.

N. 89° 59' W., along the S. bdy. of sec. 36, T. 3 S.,
R. 23 E.

Over gently rolling desert land, through shadscale under-
growth. Measurement by DI-10, Distomat electronic
measuring device and topography scaled from U.S.G.S.
quadrangle Jensen Ridge. Utah.

- 0.75 Wash, 40 lks. wide, 10 ft. deep, drains S. 10° E. about
4.00 chs. to main wash draining E.; asc. 20 ft. along
S. slope.
- 20.75 Bend in wash, 40 lks. wide, 12 ft. deep, drains irregular-
ly S. 80° E. from S. 80° W.; thence along side of wash.
- 30.55 Junction of wash, 30 lks. wide, 8 ft. deep, from N. 60° W.
and wash, 50 lks. wide, 10 ft. deep, from irregularly W.
drains S. 85° E.; asc. along wash.
- 38.64 Point for the N. $\frac{1}{4}$ sec. cor. of sec. 1, hereinafter
described.
- 39.60 Leave wash, drains irregularly E. from N. 85° W.
- 40.27 The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a
limestone, 14x12x4 ins., firmly set, 6' ins. in the ground
and plainly mkd. $\frac{1}{4}$ on N. face. This cor. will now
function as the S. $\frac{1}{4}$ sec. cor. of sec. 36, T. 3 S.,
R. 23 E. only.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

Dependent Resurvey of a Portion of
the North Boundary,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS

T3S R23E

$\frac{1}{4}$ S36
T4S R23E
1972

Bury original cor. stone alongside the iron post.

S. 89° 53' W., beginning new measruement.

Continue over gently rolling land.

- 5.25 Enter same wash, thence asc. along wash.
- 17.25 Leave wash, drains from N. 80° W.; asc. 40 ft. over gentle NE. slope.
- 38.37 Point for the closing cor. of secs. 1 and 2, hereinafter described.
- 40.26 The cor. of secs. 1, 2, 35 and 36, monumented with a sandstone, 14x12x4 ins., set, 10 ins. in the ground, and in a collar of stone, mkd. 1 notch on E. and 5 on W. edges. This cor. will now function as the cor. of secs. 35 and 36, T. 3 S., R. 23 E., only.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T3S R23E

S35|S36
S2
T4S R23E
1972

Bury original cor. stone alongside the iron post.

Land, gently rolling desert.
Soil, clay.
Undergrowth, shadscale.

S. 89° 35' W., along the S. bdy. of sec. 35, T. 3 S., R. 23 E.

Over rolling desert land through shadscale undergrowth. Measurement by DI-10 Distomat electronic measuring device. Topography scaled. Asc. 20 ft. over gentle NE. slope.

- 15.75 Wash, drains N. 85° E.; asc. 50 ft. over SE. slope.
- 33.15 Low ridge, bears N. and S.; desc. 15 ft. over gentle W. slope.
- 38.50 Point for the N. ¼ sec. cor. of sec. 2, hereinafter described.
- 40.38 Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance falls on E. bank of small wash, 10

Dependent Resurvey of a Portion of
the North Boundary,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	<p>lks. wide, 2 ft. deep, drains N. 15° E.; there is no remaining evidence of the original cor. This point will now function as the S. ¼ sec. cor. of sec. 35, T. 3 S., R. 23 E. only.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T3S R23E</p> <p style="text-align: center;"> $\frac{\frac{1}{4} S35}{T4S R23E}$ 1972 </p> <p>Asc. 50 ft. over rolling desert land.</p>
63.75	Wash, 15 lks. wide, 4 ft. deep, drains N. 45° E.
69.75	Trail road, bears N. 70° E. and S. 70° W.
78.13	Point for the closing cor. of secs. 2 and 3, hereinafter described.
78.75	Low ridge, bears N. and S.; desc. 40 ft. over SW. slope. Enter scattered timber.
80.76	<p>The cor. of secs. 2, 3, 34 and 35, monumented with a limestone, 16x14x12 ins., firmly set 5 ins. in the ground, plainly mkd. 4 notches on W. edge. This cor. will now function as the cor. of secs. 34 and 35, T. 3 S., R. 23 E. only.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T3S R23E</p> <p style="text-align: center;"> $\frac{S34 S35}{S3}$ </p> <p style="text-align: center;">T4S R23E 1972</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 35° W., 15 lks. dist., mkd. T3S R23E S34 BT.</p> <p style="padding-left: 40px;">Bury original cor. stone alongside the iron post.</p> <p>Land, gently rolling desert. Soil, clay. Timber, scattered juniper extreme W. portion. Undergrowth, shadscale.</p>
	<p>Survey of a Portion of the Subdivision, T. 4 S., R. 23 E., Salt Lake Meridian, Utah</p>
	<p>From the cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., extending 8 ins. above</p>

Survey of a Portion of the
Subdivision, T. 4 S., R. 23 E.,
Salt Lake Meridian, Utah

CHAINS	
	ground, set in fence line extending E. and W., with brass cap mkd.
	T4S R23E <u>S2 S1</u> S11 S12 DNM 1939
	North, bet. secs. 1 and 2.
	Over rolling land through sagebrush undergrowth, and widely scattered timber. Measurement by DI-10, Distomat electronic measuring device. Topography scaled. Desc. 100 ft. over N. slope.
14.00	Draw, drains E.; asc. 50 ft. over S. slope. Enter dense timber.
18.50	Spur, slopes E.; desc. 120 ft. over N. slope.
37.50	Leave timber, bears N. 30° E. and S. 30° W.; enter sagebrush.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cedar post, 3 ins. diam., 4 ft. long, alongside, brass cap mkd.
	T4S R23E $\frac{1}{4}$ <u>S2 S1</u> 1972
	Desc. 80 ft. over NW. slope.
44.00	Enter timber, bears N. 30° E. and S. 30° W.
48.00	Draw, 20 ft. deep, drains N. 40° E.; leave timber.
57.50	Stone Bridge Draw, 50 lks. wide, 10 ft. deep, drains E.; asc. 125 ft. over S. slope.
59.50	Improved dirt road, bears E. to Island Park and S. 60° W. to Vernal; enter scattered timber.
64.70	The Reef Ridge, bears E. and W.; desc. 150 ft. over steep and ledgy N. slope.
70.00	Base of steep descent; desc. gentle N. slope, leave timber.
76.40	Intersect the N. bdy. of the Tp.
	Point for the closing cor. of secs. 1 and 2.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T3S R23E <u>S36</u> <u>S2 S1</u> C C T4S R23E 1972

Survey of a Portion of the
Subdivision, T. 4 S., R. 23 E.,
Salt Lake Meridian, Utah

CHAINS

from which

The cor. of secs. 35 and 36, T. 3 S., R. 23 E.,
bears S. 89° 53' W., 1.89 chs. dist., hereinbefore
described.

Land, rolling and mountainous.

Soil, rocky clay.

Timber, patches of juniper and pinon.

Undergrowth, sagebrush and shadscale.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 1, on the N.
bdy. of the Tp., and at 40.00 chs. of easting from the
closing cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T3S R23E

$\frac{1}{4}$ S1

T4S R23E

1972

from which

The S. $\frac{1}{4}$ sec. cor. of sec. 36, T. 3 S., R. 23 E., bears
N. 89° 59' W., 1.63 chs. dist., hereinbefore
described.

From the cor. of secs. 2, 3, 10 and 11, monumented with
an iron post, 2 ins. diam., extending 8 ins. above ground,
set in fence line extending E. and W., with brass cap mkd.

T4S R23E

S3|S2

S10|S11

DNM

1939

N. 0° 01' W., bet. secs. 2 and 3.

Over rolling land through scattered timber and sagebrush
undergrowth. Measurement by DI-10, Distomat electronic
measuring device. Topography scaled. Asc. 50 ft. over
SW. slope.

8.00 Rocky outcrop, on point of spur, slopes W.; desc. 25 ft.
over gentle NW. slope.

22.00 Trail road, bears N. 70° E. and curves S. 38° W., in draw,
drains S. 38° W.; asc. 40 ft. over S. slope.

35.00 Top of ascent, bears E. and W.; desc. 10 ft. over gentle
N. slope. Enter dense timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins.
in the ground, with brass cap mkd.

Survey of a Portion of the
Subdivision, T. 4 S., R. 23 E.,
Salt Lake Meridian, Utah

CHAINS

T4S R23E

 $\frac{1}{4}$

S3|S2

1972

from which

A juniper, 4 ins. diam., bears S. 41° W., 23 lks.
dist., mkd. $\frac{1}{4}$ S3 BT.

Desc. 100 ft. over steep N. slope.

- 48.00 Draw, drains N. 45° W.; asc. 100 ft. over SW.slope.
- 52.00 Point of spur, slopes W.; desc. 100 ft. over N. slope.
- 56.50 Improved dirt road, bears S. 85° E. to Island Park and
N. 65° W. to Vernal. Leave timber.
- 57.50 Bear Wallow Draw, 20 lks. wide, 5 ft. deep, drains N. 80°
W.; asc. 100 ft. over S. slope.
- 63.00 Enter scattered timber.
- 65.50 The Reef Ridge, bears E. and W.; desc. 80 ft. over N.
slope.
- 67.00 Leave timber.
- 71.00 Trail road, bears N. 60° E. and S. 60° W.; in saddle,
bears N. 30° W. and S. 30° E.; asc. 10 ft. over gentle
SE. slope.
- 75.86 Intersect the N. bdy. of the Tp.

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T3S R23E

S35

 $\frac{S35}{S3|S2}$

|

C C

T4S R23E

1972

from which

U.S.G.S. triangulation station "Divide", bears
S. $52^{\circ} 26' 30''$ E., 17.78 chs. dist.

The cor. of secs. 34 and 35, T. 3 S., R. 23 E.,
bears S. $89^{\circ} 35'$ W., 2.63 chs. dist., hereinbefore
described.

Land, rolling and mountainous.

Soil, rocky clay.

Timber, patches of juniper and pinon.

Undergrowth, sagebrush and shadscale.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 2 on the N. bdy.
of the Tp., and midpoint bet. the closing cor. of secs.

Survey of a Portion of the
Subdivision, T. 4 S., R. 23 E.,
Salt Lake Meridian, Utah

CHAINS

1 and 2, and the closing cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T3S R23E

$\frac{1}{4}$ S2
T4S R23E
1972

from which

The S. $\frac{1}{4}$ sec. cor. of sec. 35, T. 3 S., R. 23 E., bears S. $89^{\circ} 35'$ W., 2.26 chs. dist., hereinbefore described.

General Description

The portion of T. 4 S., R. 23 E., surveyed at this time is adjacent to the Dinosaur National Monument and about 15 miles northeast of Vernal, Utah.

It is rolling desert and mountain land, with rocky clay to clay soil. The area is covered with patches of juniper and pinon timber, with sagebrush and shadscale undergrowth. The elevation varies from 5,500 ft. to 5,880 ft. above sea level. The area is drained in an easterly direction by washes and draws draining into Stone Bridge Draw, thence into the Green River, except the western portion of section 2, which drains in a westerly direction. The Reef Ridge, a sharp narrow ridge, divides the area in an east-west direction. The road from Vernal to Island Park passes through the north portion in an east-west direction. Several trail roads are located in the western portion of sec. 2. Coal Bed Spring, (nearly dry) is located in the northeast $\frac{1}{4}$ of sec. 1. No other water was noted.

Blank

Page

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

[illegible]

CERTIFICATE OF SURVEY

(I ~~xxx~~), Glen B. Hatch

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 17th day of May, 1972, (I) ~~Wes~~ have dependently resurveyed a portion of the east boundary and a portion of the north boundary, and surveyed a portion of the subdivisional lines of Township 4 South Range 23 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(XX)~~ and under (my) ~~(XXX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 5, 1972

(Date)

Glen B Hatch

(Cadastral Surveyor)

Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date OCT 29 1973

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the east boundary and a portion of the north boundary, and the survey of a portion of the subdivisional lines of Township 4 South, Range 23 East, Salt Lake Meridian, Utah

executed by Glen B. Hatch Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

DEC 17 1973

(Date)

Clark F. Lumm,

(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~

, is a true copy of the original field notes.

~~(Chief, Division of Cadastral Survey) cno 311-222~~

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF THE
REMONUMENTATION OF CORNERS

IN

TOWNSHIP 15 SOUTH, RANGE 3 WEST

TOWNSHIP 16 SOUTH, RANGE 3 WEST

TOWNSHIP 18 SOUTH, RANGE 3 WEST

TOWNSHIP 19 SOUTH, RANGE 3 WEST

TOWNSHIP 20 SOUTH, RANGE 2 WEST

TOWNSHIP 21 SOUTH, RANGE 2 WEST

TOWNSHIP 21 SOUTH, RANGE 4 WEST

TOWNSHIP 22 SOUTH, RANGE 1 EAST

TOWNSHIP 22 SOUTH, RANGE 2 EAST

TOWNSHIP 22 SOUTH, RANGE 4 EAST

TOWNSHIP 22 SOUTH, RANGE 4 WEST

TOWNSHIP 23 SOUTH, RANGE 1 EAST

TOWNSHIP 23 SOUTH, RANGE 2 EAST

TOWNSHIP 23 SOUTH, RANGE 3 WEST

TOWNSHIP 23 SOUTH, RANGE 5 WEST

Of the SALT LAKE

In the State of UTAH

EXECUTED BY

Ferrel D. Reynolds

Surveying Technician

Under special instructions dated February 15, 19 61, which provided for the surveys
included under Group Number 447, approved February 16, 1961,
and assignment instructions dated May 26, 19 69.

Survey commenced June 30, 19 69

Survey completed August 21, 19 69

RECEIVED
BUREAU OF LAND MANAGEMENT
OFFICE
Meridian
71 DEC 23 PM 1:55

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 15 S. R. 3 W. Mer Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23 2	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 16 S. R. 3 W. Mer Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12 3
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 18 S. R. 3 W. Mer Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

**Blank
Page**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 19 S. R. 3 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
			4	4	
19	20	21	22	23	24
		5	5		
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 20 S. R. 2 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
		6			
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 21 S. R. 2 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
			6		

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 21 S. R. 4 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Monument locations: 8 (between 14 and 23), 8 (between 23 and 24), 8 (between 26 and 25), 7 (between 33 and 34)

Tp. 22 S. R. 1 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Monument location: 9 (between 20 and 21)

Tp. 22 S. R. 2 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Monument locations: 10 (between 19 and 20), 11 (between 30 and 31), 9 (between 29 and 30)

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 22 S. R. 4 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 22 S. R. 4 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 23 S. R. 1 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 23 S. R. 2 E. Mer. Salt Lake

6	5	4	3	2	1
17	17				
7	16	15	10	11	12
	16				
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 23 S. R. 3 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
					19
18	17	16	15	14	13
				19	
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 23 S. R. 5 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	22
			23	22	21
19	20	21	22	23	24
30	29	28	27	26	25
21	21	32	23	34	36
	20	20	19		

Blank

Page

Remonumentation of Corners

CHAINS

The following field notes are those of the remonumentation of certain identified corners selected by the U. S. Forest Service as being located in or controlling the boundaries of Forest Service lands, situated in the Fishlake National Forest. A Forester's Compass was used to determine the bearings of new corner accessories. The mean magnetic declinations were found to be as follows:

T. 15 S., R. 3 W., Salt Lake Meridian,	15° 50' E.
T. 16 S., R. 3 W., " " "	15° 50' E.
T. 18 S., R. 3 W., " " "	15° 45' E.
T. 19 S., R. 3 W., " " "	15° 45' E.
T. 20 S., R. 2 W., " " "	15° 40' E.
T. 21 S., R. 2 W., " " "	15° 40' E.
T. 21 S., R. 4 W., " " "	15° 45' E.
T. 22 S., R. 1 E., " " "	15° 20' E.
T. 22 S., R. 2 E., " " "	15° 20' E.
T. 22 S., R. 4 E., " " "	15° 20' E.
T. 22 S., R. 4 W., " " "	15° 20' E.
T. 23 S., R. 1 E., " " "	15° 40' E.
T. 23 S., R. 2 E., " " "	15° 20' E.
T. 23 S., R. 3 W., " " "	15° 35' E.
T. 23 S., R. 5 W., " " "	15° 40' E.

The position of each corner was marked by the original monument or determined from corner accessories recorded in the survey record. The monumentation was requested by and accomplished in cooperation with the Forest Service.

Remonumentation of Corners in T. 15 S., R. 3 W.

Township 15 South, Range 3 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following cor. was established by A. J. Stewart Jr. in 1884.

At the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., (Third Standard Parallel South), marked with a gray sandstone, 18x8x5 ins., firmly set and plainly mkd. with 5 notches on the W. and 1 on the E., SC on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T15S R3W

SC

S35|S36

1969

Deposit the original stone alongside the corner.

This cor. is located on steep rocky E. slope of hill at the cor. of four strand fence line that bears N. and E. 150 lks. dist. W. of small draw that drains N. 30° E.

Remonumentation of Corners in T. 15 S. R. 3 W.

CHAINS

At the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, marked with a limestone, 12x8x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T15S R3W

$\frac{1}{4}$
S26 | S25

1969

Deposit the original stone alongside the corner.

From which I mark

A cedar, 6 ins. in diam., bears S. 39° E., 54 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

A cedar, 7 ins. in diam., bears N. $43^\circ 30'$ W., 24 lks. dist., mkd. $\frac{1}{4}$ S26 BT.

This cor. is located on gentle NE. slope at the cor. of fence that bears S. and W. in thick cedar growth.

At the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, marked with a quartzite stone, 14x6x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Brass cap mkd.

T15S R3W

$\frac{1}{4}$ $\frac{S23}{S26}$

1969

From which I mark

A cedar, 5 ins. in diam., bears S. 45° W., $28\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S26 BT.

Deposit the original stone alongside the corner.

This cor. is located on nearly level land 250 lks. dist. N. of trail road that bears E. and W. in lightly scattered cedar growth.

Remonumentation of Corners in T. 16 S., R. 3 W.

Remonumentation of Corners in T. 16 S., R. 3 W.

CHAINS

Township 16 South, Range 3 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. This corner was established by Ferdinand Dickert in 1871.

At the 1/4 sec. cor. of secs. 12 and 13, marked with a sandstone, 14x12x5 ins., (same as record) firmly set, but not mkd. (The corners in this Tp. were not mkd.) This rock fits the topographic features of the original notes and appears to have been used by local surveyors.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and in a collar of stone. Brass cap mkd.

T16S R3W

¼ $\frac{S12}{S13}$

1969

From which I mark

A cedar, 8 ins. in diam., bears N. 69° E., 60 lks. dist., mkd. 1/4 S12 BT.

A cedar, 5 ins. in diam., bears S. 74° 30' W., 50 lks. dist., mkd. 1/4 S13 BT.

Deposit the original stone alongside the corner.

This corner is located on nearly level land 350 lks. dist. N. of trail road that bears E. and W., 200 lks. dist. W. of small draw that drains S. 20° E. in scattered cedar growth.

Remonumentation of Corners in T. 18 S., R. 3 W.

Township 18 South, Range 3 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following cor. was established by Shadrach M. Richardson in 1883 and retraced by Joseph C. Thoma in 1919.

At the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., marked with a quartzite stone, 12x8x6 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T18S
R3W R2W

¼ $\frac{S25}{S30}$

1969

Remonumentation of Corners in T. 18 S., R. 3 W.

CHAINS

From which I mark

A cedar, 8 ins. in diam., bears S. 33° E., 33 lks. dist., mkd. 1/4 S30 BT.

A cedar, 12 ins. in diam., bears S. 65° W., 63 lks. dist., mkd. 1/4 S25 BT.

Deposit the original stone alongside the corner.

This cor. is located on N. slope of hill 130 lks. dist. W. of cor. of old fence that bears N., S. and E. in scattered cedar growth.

Remonumentation of Corners in T. 19 S., R. 3 W.

Township 19 South, Range 3 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following corners were established by Shadrach M. Richardson in 1883.

At the cor. of secs. 15, 16, 21 and 22, marked with a sandstone, 15x13x6 ins., firmly set and plainly mkd. with 3 notches on the S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor. Brass cap mkd.

T19S R3W

S16	S15
S21	S22

1969

Deposit the original stone alongside the corner.

This cor. is located on top of low ridge that bears N. 70° W. and S. 70° E. at the corner of four strand fence that bears N., S. and W., 200 lks. dist. S. of wash in draw that drains N. 70° W. in sage, oak and scattered cedar growth.

At the 1/4 sec. cor. of secs. 15 and 22, marked with a limestone, 14x10x4 ins., firmly set and plainly mkd. 1/4 on N. face, witnessed by a small mound of stones to N.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 16 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T19S R3W

$\frac{1}{4}$	S15
	S22

1969

Remonumentation of Corners in T. 19 S., R. 3 W.

CHAINS

From which I mark

A cedar limb, 5 ins. in diam., bears N. 3° E.,
32 lks. dist., mkd. 1/4 S15 BT.

A cedar limb, 5 ins. in diam., bears S. 26° 30' W.,
43 lks. dist., mkd. 1/4 S22 BT.

Deposit the original stone alongside the corner.

This cor. is located on nearly level land approx. 9 chs.
dist. S. of trail road that bears E. and W. in scattered
cedar growth.

At the cor. of secs. 21, 22, 27 and 28, marked with a
limestone, 16x10x7 ins., firmly set and plainly mkd.
with 3 notches on the E. and 2 on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 16
ins. in the ground and in a mound of stone 3 ft. base
to brass cap mkd.

T19S R3W

S21 | S22

S28 | S27

1969

Deposit the original stone alongside the corner.

This cor. is located on gentle N. slope 13 lks. dist. W.
of fence line that bears N. and S., approx. 6½ chs. dist.
S. of wash in draw that drains W. in scattered cedar and
mahogany growth.

At the cor. of secs. 20, 21, 28 and 29, marked with a
sandstone 18x10x6 ins., firmly set and plainly mkd. with
4 notches on the E. and 2 on S. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18
ins. in the ground and in a mound of stone to brass cap
mkd.

T19S R3W

S20 | S21

S29 | S28

1969

From which I mark

A cedar, 6 ins. in diam., bears S. 18° W., 43 lks.
dist., mkd. T19S R3W S29 BT.

A cedar, 6 ins. in diam., bears N. 29° W., 39 lks.
dist., mkd. T19S R3W S20 BT.

Remonumentation of Corners in T. 19 S., R. 3 W.

CHAINS

Deposit the original stone alongside the corner.

This cor. is located on nearly level land in old fence that bears E. and W., 25 lks. dist. W. of fence cor. bearing E., W. and S., 6 lks. dist. S. of new fence line that bears E. and W., 86 lks. dist. N. of creek, 5 lks. wide, 6 ins. deep, that flows W. in scattered cedar growth.

Remonumentation of Corners in T. 20 S., R. 2 W.

Township 20 South, Range 2 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. This cor. was established by Henry Fitzhugh in 1882 and retraced by H. D. Heist and E. V. Woolley in 1906.

At the cor. of secs. 8, 9, 16 and 17, marked with a sandstone 16x8x6 ins., firmly set and plainly mkd. with four notches on the S. and E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T20S R2W

S8	S9
S17	S16

1969

From which I mark

A cedar, 8 ins. in diam., bears S. 28° W., 46 lks. dist., mkd. T20S R2W S17 BT.

Deposit the original stone alongside the corner.

This cor. is located at base of rocky E. slope 2 lks. dist. W. of fence that bears N. and S. 15 lks. dist. W. of trail road that bears N. and S. alongside fence in oak, mahogany, pine and cedar growth.

Remonumentation of Corners in T. 21 S., R. 2 W.

Township 21 South, Range 2 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. This cor. was established by Henry Fitzhugh in 1882.

At the cor. of secs. 33 and 34, on the S. bdy. of the Tp., marked with a sandstone 30x16x10 ins. (record 40x30x10 ins.), firmly set in a mound of stone and plainly mkd. with 3 notches on the E. and W. edge.

Remonumentation of Corners in T. 21 S., R. 2 W.

CHAINS

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Brass cap mkd.

T21S R2W

S33|S34

S4

T22S R2W

1969

From which I mark

A cedar, 7 ins. in diam., bears N. 77° E., 33 lks. dist., mkd. T21S R2W S34 BT.

The original stone in mound N. of corner.

This cor. is located on gentle N. slope 170 lks. dist. E. of small draw that drains N., 5 chs. dist., into Frog Flat in pinon and cedar growth.

Remonumentation of Corners in T. 21 S., R. 4 W.

Township 21 South, Range 4 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The S. bdy. was surveyed by Adolphe Jessen in 1879 and the interior lines by A. J. Stewart Jr. and Shadrach M. Richardson in 1874 and 1883.

At the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., marked with a conglomerate stone 30x24x18 ins., firmly set and plainly mkd. with 3 notches on the E. and W. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T21S R4W

S33|S34

S4|S3

T22S R4W

1969

Deposit the original stone alongside the corner.

This cor. is located on top of ridge that bears N. 45° W. and S. 45° E., 50 lks. dist. W. of fence cor. that bears E., S. $44^{\circ} 30'$ W. and N. 21° W., 50 lks. dist. N. of fence cor. that bears E., S. and N. $44^{\circ} 30'$ E. approx. 6 chs. dist. E. of dirt road that bears N. 30° W. and S. 30° E. in oak and sagebrush growth.

Remonumentation of Corners in T. 21 S., R. 4 W.

CHAINS

At the cor. of secs. 25, 26, 35 and 36, marked with a brown flintstone 20x8x6 ins., firmly set and plainly mkd. with 1 notch on the S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 4 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor. Brass cap mkd.

T21S R4W

S26	S25
S35	S36

1969

From which I mark

A cedar, 4 ins. in diam., bears S. 30° W., 8 lks. dist., mkd. BT.

Deposit the original stone alongside the corner.

The cor. is located on steep N. slope of hill approx. 14 chs. dist. S. of the left hand fork of Chalk Creek in thick oakbrush.

At the cor. of secs. 23, 24, 25 and 26, marked with a sandstone 18x16x10 ins., firmly set and plainly mkd. with 2 notches on the S. and 1 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T21S R4W

S23	S24
S26	S25

1969

From which I mark

A cedar, 6 ins. in diam., bears N. 35° E., 56 lks. dist., mkd. T21S R4W S24 BT.

A cedar, 5 ins. in diam., bears S. 26° E., 12 lks. dist., mkd. T21S R4W S25 BT.

Deposit the original stone alongside the corner.

The cor. is located on top of low spur projecting W. 2 chs. dist. N. of small draw that drains W. and $7\frac{1}{2}$ chs. dist. S. of draw that drains W. on fence line that bears N. and S. in thick oak and cedar growth.

At the cor. of secs. 13, 14, 23 and 24, marked with a gray granite stone 18x12x6 ins., firmly set and plainly mkd. with 3 notches on the S. and 1 on the E. edge.

At the cor. point

Remonumentation of Corners in T. 21 S., R. 4 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T21S R4W

$\frac{S14}{S23} | \frac{S13}{S24}$

1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land on four strand fence line that bears E. and W. 50 lks. dist. N. of trail road that bears E. and W. alongside the fence in sagebrush growth; no timber.

Remonumentation of Corners in T. 22 S., R. 1 E.

Township 22 South, Range 1 East, Salt Lake Meridian, is located within the Fishlake National Forest. The following cor. was established by R. C. Yundt in 1940.

At the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, marked with a 1 inch iron post, with brass cap sheared off and lying on ground.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18 ins. in the ground and in a mound of stone to brass cap mkd.

T22S R1E

$\frac{1}{4}$
 $\frac{S20}{S21} | \frac{S21}{S21}$

1969

The 1 inch iron post standing alongside the cor.

The cor. is located on nearly level sagebrush flat 40 lks. dist. S. of dirt road that bears N. 30° E. and S. 30° W. at the cor. of old fence that bears S. and W.

Remonumentation of Corners in T. 22 S., R. 2 E.

Township 22 South, Range 2 East, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by A. D. Ferron in 1877.

At the cor. of secs. 29, 30, 31 and 32, marked with a trachyte stone $18 \times 16 \times 12$ ins., firmly set and plainly mkd. with 5 notches on the E. and 1 on the S. edge.

From which,

Remonumentation of Corners in T. 22 S., R. 2 E.

CHAINS

A cedar, 10 ins. in diam., bears N. $32^{\circ} 30'$ E.,
10 lks. dist., mkd. T22S R2E S29 BT, (record N.
 15° E., 10 lks. dist.).

A cedar, 6 ins. in diam., bears S. 10° E., 16 lks.
dist., mkd. T22S R2E S32 BT, (same as record).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24
ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft.
base, $1\frac{1}{2}$ ft. high, to W. of cor. Brass cap mkd.

T22S R2E

S30	S29
S31	S32

1969

Deposit the original stone alongside the corner.

The cor. is located on N. slope of hill $2\frac{1}{2}$ chs. dist.
S. of steep descent into canyon that drains N. 70° W.
in cedar and pine growth.

At the cor. of secs. 19, 20, 29 and 30, marked with a
trachyte stone $20 \times 10 \times 10$ ins., firmly set and plainly
mkd. with 5 notches on E. and 2 on S. edge.

From which,

A pinon pine, 12 ins. in diam., bears N. 59° E.,
26 lks. dist., mkd. T22S R2E S20 BT, (record N.
 80° E., 29 lks. dist.).

A pinon pine, 14 ins. in diam., bears S. 60° E.,
22 lks. dist., mkd. T22S R2E S29 BT, (record S.
 40° E., 33 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24
ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft.
base, $1\frac{1}{2}$ ft. high, W. of corner. Brass cap mkd.

T22S R2E

S19	S20
S30	S29

1969

Deposit the original stone alongside the corner.

The cor. is located on NE. slope of spur, 50 lks. dist.
N. of top that projects N. 30° W., approx. $5\frac{1}{2}$ chs. dist.
E. of small wash in draw that drains N. 30° W. in scat-
tered pine and cedar growth.

CHAINS

Remonumentation of Corner in T. 22 S., R. 2 E.

At the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, marked with a trachyte stone 16x10x8 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

From which,

A cedar, 8 ins. in diam., bears S. 71° W., 27 lks. dist., mkd. $\frac{1}{4}$ S31 BT, (Record S. 60° W., 22 lks. dist.).

A cedar, 12 ins. in diam., bears N. 61° W., $35\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S30 BT, (record N. 50° W., 32 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, N. of corner. Brass cap mkd.

T22S R2E

$\frac{1}{4}$ $\frac{S30}{S31}$

1969

Deposit the original stone alongside the cor.

The cor. is located on gentle N. slope of draw, that drains N. in cedar and pinon growth.

Remonumentation of Corners in T. 22 S., R. 4 E.

Township 22 South, Range 4 East, Salt Lake Meridian, is located partially within the Fishlake National Forest. The following cor. was established by A. D. Ferron in 1869.

At the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, marked with a sandstone 16x10x4 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T22S R4E

$\frac{1}{4}$ $\frac{S9}{S16}$

1969

Deposit the original stone alongside the corner.

From which I mark

An aspen, 5 ins. in diam., bears S. 28° W., 56 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

CHAINS

An aspen, 8 ins. in diam., bears N. 45° W., 25 lks. dist., mkd. $\frac{1}{2}$ S9 BT.

The cor. is located on nearly level hill top approx. 3½ chs. dist. S. of trail road that bears E. and W. in scattered aspen and pine growth.

Remonumentation of Corners in T. 22 S., R. 4 W

Township 22 South, Range 4 West, Salt Lake Meridian, is located within the Fishlake National Forest. Surveyed by Adolphe Jessen in 1879, and portions resurveyed by Page and Swan in 1898.

At the closing cor. of secs. 10 and 11, on the S. bdy. of sec. 2, marked with a granite stone 20x12x6 ins., firmly set and plainly mkd. with 5 notches on the S. and 2 on the E., CC on S. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 3 ft. base, to brass cap mkd.

T22S R4W

S2	
S10	S11
C C	
1969	

Deposit the original stone alongside the corner.

The cor. is located on top of ridge that bears N. 40° W. and S. 40° E., 75 lks. dist. E. of trail road that bears N. and S. in thick oakbrush.

At the cor. of secs. 3, 4, 9 and 10, marked with a sandstone 51x9x7 ins., firmly set and plainly mkd. with 5 notches on the S. and 3 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 6 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T22S R4W

S4	S3
S9	S10
1969	

Original stone in mound alongside the corner.

Remonumentation of Corners in T. 22 S., R. 4 W.

CHAINS

The cor. is located on gentle NW. slope of hill at the cor. of net wire fence that bears N., S. and W. in sage and oakbrush.

At the SE. cor. of sec. 18, marked with a sandstone 36x14x8 ins., (same as record) firmly set and plainly mkd. with 5 notches on the E. and 3 on the S. edge.

From which,

The closing cor. of secs. 17 and 19, bears N. 1° 35' E., 50 lks. dist. (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 8 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T22S R4W

S18

S19

1969

Original stone in mound alongside the corner.

The cor. is located on top of rocky spur that projects N. 20° E. approx. 8 chs. dist. W. of trail road that bears N. 20° W. and S. 70° E., on turn in scattered cedar and pinon growth.

At the closing cor. of secs. 17 and 19, on the E. bdy. of sec. 18, marked with a sandstone 30x14x4 ins., firmly set and plainly mkd. with 5 notches on the E. and 3 on the S. edge, CC on the E. face.

From which,

A cedar, 16 ins. in diam., bears N. 70° W., 8 lks. dist., mkd. T22S R4W S18 BT, (same as record).

A cedar, 10 ins. in diam., bears N. 45° E., 57 lks. dist., mkd. T22S R4W S17 BT, (same as record).

The SE. cor. of sec. 18, bears S. 1° 35' W., 50 lks. dist., (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 10 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T22S R4W

S18 S17 CC
S19

1969

Original stone in mound alongside the corner.

Remonumentation of Corners in T. 22 S., R. 4 W.

CHAINS

The cor. is located on top of rocky spur projecting N. 20° E. approx. 8 chs. dist. W. of trail road that bears S. 70° E. and N. 20° W., on turn in scattered cedar and pinon growth.

Remonumentation of Corners in T. 23 S., R. 1 E.

Township 23 South, Range 1 East, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by A. D. Ferron in 1877.

At the 1/4 sec. cor. of secs. 23 and 24, marked with a basalt stone 13x12x12 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, W. of cor. Brass cap mkd.

T23S R1E
 ½
S23|S24
1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land 13 lks. dist. E. of five strand fence that bears N. and S., 340 lks. dist. E. of dirt road that bears N. and S. in sagebrush growth. No timber.

At the cor. of secs. 1, 2, 11 and 12, marked with a trachyte stone 24x18x6 ins., firmly set and plainly mkd. with 5 notches on the S. and 1 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T23S R1E
 S2|S1
 S11|S12
1969

Deposit the original stone alongside the corner.

The cor. is located on W. slope of hill in sage and oakbrush approx. 10 chs. dist. E. of trail road that bears N. and S.

Remonumentation of Corners in T. 23 S., R. 1 E.

CHAINS

At the cor. of secs. 2, 3, 10 and 11, marked with a porphyry stone 29x16x5 ins., firmly set and plainly mkd. with 5 notches on the S. and 2 on the E. edge.

From which,

A mahogany 7 ins. in diam., bears S. 88° E., 13 lks. dist., mkd. T23S R1E S11 BT, (same as record).

No remaining evidence of the other two bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 12 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T23S R1E

S3	S2
S10	S11

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle NW. slope of hill, in thick oak and mahogany growth approx. 5 chs. dist. E. of trail road that bears N. 45° E. and S. 45° W.

Remonumentation of Corners in T. 23 S., R. 2 E.

Township 23 South, Range 2 East, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by A. D. Ferron in 1877.

At the cor. of secs. 8, 9, 16 and 17, marked with a sandstone 20x12x6 ins., firmly set and plainly mkd. with 4 notches on the S. and E. edge, (record sandstone 30x30x16 ins.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, W. of the cor. Brass cap mkd.

T23S R2E

S8	S9
S17	S16

1969

From which I mark

A pinon pine, 6 ins. in diam., bears N. 6° E., 107 lks. dist., mkd. T23S R2E S9 BT.

Remonumentation of Corners in T. 23 S., R. 2 E.

CHAINS

Deposit the original stone alongside the corner.

The cor. is located on gentle SW. slope of hill in thick oakbrush approx. 5 chs. dist. E. of main dirt road in Gooseberry Canyon that bears N. 30° W. and S. 30° E.

At the cor. of secs. 7, 8, 17 and 18, marked with a sandstone 14x8x6 ins., firmly set and plainly mkd. with 5 notches on the E. and 4 on the S. edge.

From which,

A cedar, 16 ins. in diam., bears N. 55° E., 123 lks. dist., mkd. T23S R2E S8 BT, (record N. 45° E., 160 lks. dist.).

A cedar, 14 ins. in diam., bears S. 51° W., 32 lks. dist., mkd. T23S R2E S18 BT, (record S. 46° W., 29 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 16 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T23S R2E

S7	S8
S18	S17

1969

From which I mark

A cedar, 6 ins. in diam., bears N. 29° W., 4 lks. dist., mkd. T23S R2E S7 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle SE. slope of hill, in scattered cedar and pinon growth 40 lks. dist. W. of small wash, 10 lks. wide, 1 ft. deep, that drains S.

At the 1/4 sec. cor. of secs. 7 and 8, marked with a trachyte stone 14x12x5 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a collar of stone, brass cap mkd.

T23S R2E

½	S8
S7	

1969

From which I mark

Remonumentation of Corners in T. 23 S., R. 2 E.

CHAINS

A cedar, 7 ins. in diam., bears S. $72^{\circ} 30'$ E., 88 lks. dist., mkd. $1/4$ S8 BT.

A cedar, 6 ins. in diam., bears S. $52^{\circ} 30'$ W., 24 lks. dist., mkd. $1/4$ S7 BT.

Deposit the original stone alongside the corner.

The cor. is located on N. slope of hill, in thick oak, cedar and pinon growth 6 lks. dist. E. and 13 lks. dist. N. of fence cor. projecting S. 45° E. and S. 45° W.

At the cor. of secs. 5, 6, 7 and 8, marked with a sandstone $18 \times 10 \times 8$ ins., firmly set and plainly marked with 5 notches on the S. and E. edges.

From which,

A cedar, 24 ins. in diam., bears N. 48° E., 41 lks. dist., mkd. T23S R2E S5 BT, (record N. 60° E., 44 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Brass cap mkd.

T23S R2E

S6 | S5

S7 | S8

1969

From which I mark

A pine, 4 ins. in diam., bears S. 38° E., 12 lks. dist., mkd. T23S R2E S8 BT.

A cedar, 4 ins. in diam., bears S. 53° W., 31 lks. dist., mkd. BT.

A cedar, 6 ins. in diam., bears N. 67° W., 43 lks. dist., mkd. T23S R2E S6 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle W. slope in thick cedar and pine growth approx. $5\frac{1}{2}$ chs. dist. E. of main dirt road in Gooseberry Canyon that bears S. 45° E. and N. 45° W.

At the $1/4$ sec. cor. of secs. 6 and 7, marked with a sandstone $18 \times 15 \times 8$ ins., firmly set and plainly mkd. $1/4$ on N. face.

From which,

Remonumentation of Corners in T. 23 S., R. 2 E.

CHAINS

A cedar, 24 ins. in diam., bears S. 81° W., 13 lks. dist., mkd. 1/4 S BT, (record S. 89° W., 26 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, N. of cor. Brass cap mkd.

T23S R2E

$$\frac{1}{2} \begin{array}{r} S6 \\ S7 \end{array}$$

1969

From which I mark

A cedar, 6 ins. in diam., bears N. 26° E., 70 lks. dist., mkd. 1/4 S6 BT.

Deposit the original stone alongside the corner.

The cor. is located on SW. slope of hill, in cedar and pinon growth approx. 4 chs. dist. E. of old fence that bears N. and S., about 9 chs. dist. E. of trail road that bears N. and S.

Remonumentation of Corners in T. 23 S., R. 3 W.

Township 23 South, Range 3 West, Salt Lake Meridian, is located within the Fishlake National Forest. The following corners were established by Charles Mogo in 1856 and resurveyed by John T. Breckon in 1896.

At the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., marked with a trachyte stone 16x10x6 ins., firmly set but dimly mkd. and witnessed by a mound of stone W. of the cor. (same as record).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 12 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T23S
R3W R2W

$$\frac{1}{2} \begin{array}{r} S13 \\ S18 \end{array}$$

1969

Deposit the original stone alongside the corner.

The cor. is located on rocky S. slope of hill in sagebrush growth at the head of small draw that drains S., approx. 8 chs. dist. E. of trail road that bears N. and S.

Remonumentation of Corners in T. 23 S., R. 3 W.

CHAINS

At the 1/4 sec. cor. of secs. 12 and 13, marked with a flintstone 14x10x8 ins., firmly set and plainly mkd. 1/4 on N. face, witnessed by a mound of stone to N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to N. Brass cap mkd.

T23S R3W

¼ $\frac{S12}{S13}$

1969

Deposit the original stone alongside the corner.

The cor. is located on SE. slope of hill, in scattered cedar growth 120 lks. dist. N. of jeep trail that bears E. and W.

At the 1/4 sec. cor. of secs. 14 and 23, marked with a quartzite stone 14x8x6 ins., firmly set and plainly mkd. 1/4 on N. face, witnessed by a mound of stone to N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T23S R3W

¼ $\frac{S14}{S23}$

1969

Deposit the original stone alongside the corner.

The cor. is located on top of broken, rocky spur projecting S. 35 lks. dist. E. of steep, ledgy descent into canyon that bears N. and S. in scattered cedar growth.

Remonumentation of Corners in T. 23 S., R. 5 W.

Township 23 South, Range 5 West, Salt Lake Meridian, is located partially within the Fishlake National Forest. The S. bdy. was surveyed by A. J. Stewart in 1876, and the subdivisional lines by Adolphe Jessen in 1879.

At the cor. of secs. 33 and 34 on the S. bdy. of the Tp., marked with a sandstone 20x11x5 ins., firmly set and plainly mkd. with 3 notches on the E. and W. edges.

At the cor. point

Remonumentation of Corners in T. 23 S., R. 5 W.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. in diam., 16 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T23S R5W
S33|S34
S1
T24S R5W
1969

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope of rolling foothills, in scattered cedar growth 11 lks. dist. S. of four strand fence cor. that bears N. and W.

At the 1/4 sec. cor. of sec. 33 on the S. bdy. of the Tp., marked with a sandstone 24x12x6 ins., firmly set and plainly mkd. 1/4 on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T23S R5W
½ S33
T24S
1969

Deposit the original stone alongside the corner.

The cor. is located on gentle NE. slope of rolling foothills, in oak and scattered cedar growth 8 lks. dist. S. of four strand fence line and reseeded area that bears E. and W., 140 lks. dist. W. of small draw that drains N., 130 lks. dist. E. of trail road that bears N. and S.

At the 1/4 sec. cor. of sec. 32 on the S. bdy. of the Tp., marked with a limestone 18x12x5 ins., (record sandstone 20x15x5 ins.), firmly set and dimly mkd. 1/4 on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T23S R5W
½ S32
T24S
1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 23 S., R. 5 W.

CHAINS

The cor. is located on rolling foothills, in scattered cedar growth 49 lks. dist. N. of four strand fence line that bears E. and W. 3 chs. dist. E. of small creek that flows N.

At the 1/4 sec. cor. of sec. 31 on the S. bdy. of the Tp., marked with a white sandstone 25x12x10 ins., firmly set and plainly mkd. 1/4 on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a mound of stone to brass cap mkd.

T23S R5W

¼ S31

T24S

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope of rolling land, and in scattered cedar growth 4 lks. dist. N. of four strand fence that bears E. and W.

At the cor. of secs. 31 and 36, on the S. bdy. between Rs. 5 and 6 W., marked with a quartzite stone 24x12x8 ins., firmly set and plainly mkd. with 6 notches on the E., W., and N. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, N. of cor. Brass cap mkd.

T23S

R6W R5W

S36|S31

S4

T24S R5W

1969

Deposit the original stone alongside the corner.

The cor. is located in bottom of draw, 3 chs. wide, that drains N. in scattered cedar growth 15 lks. dist. S. of four strand fence that bears E. and W.

At the cor. of secs. 13, 14, 23 and 24, marked with a sandstone 30x18x6 ins., firmly set and plainly mkd. with 3 notches on the S. and 1 on the E. edge.

At the cor. point

Remonumentation of Corners in T. 23 S., R. 5 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 12 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T23S R5W

S14	S13
S23	S24

1969

Deposit the original stone alongside the corner.

The cor. is located on steep W. slope of hill in scattered cedar growth 90 lks. dist. S. of four strand fence that bears E. and W.

At the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, marked with a sandstone $20 \times 15 \times 5$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 12 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T23S R5W

$\frac{1}{2}$	
S14	S13

1969

Deposit the original stone alongside the corner.

From which I mark

A cedar, 10 ins. in diam., bears N. $81^{\circ} 30'$ E., 30 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

A cedar, 12 ins. in diam., bears S. $56^{\circ} 30'$ W., 32 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

The cor. is located at head of small draw that drains S. 40° W. in scattered cedar growth.

At the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, marked with a quartzite stone $20 \times 15 \times 6$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 17 ins. in the ground and in a collar of stone to brass cap mkd.

T23S R5W

$\frac{1}{2}$	S14
	S23

1969

Remonumentation of Corners in T. 23 S., R. 5 W.

CHAINS

Deposit the original stone alongside the corner.

The cor. is located on W. slope of rolling foothills in scattered cedar growth 2 chs. dist. E. of trail road that bears S. 30° W. and N. 30° E., at the cor. of four strand fence that bears S. and E.

At the cor. of secs. 14, 15, 22 and 23, marked with a limestone 14x7x4 ins., firmly set and plainly mkd. with 3 notches on the S. and 2 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 6 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T23S R5W

S15	S14
S22	S23

1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land in sagebrush growth 50 lks. dist. N. of trail road that bears E. and W., 150 lks. dist. N. of three strand fence that bears E. and W.

At the 1/4 sec. cor. of secs. 33 and 34, marked with a sandstone 14x10x6 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T23S R5W

½	
S33	S34

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope of rolling foothills, in scattered cedar growth 3 lks. dist. E. of four strand fence that bears N. and S.

CHAINS

Blank

Page

CERTIFICATE OF SURVEY

(I) ~~(ME)~~,

Ferrel D. Reynolds

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day

of February, 1961, (I) ~~(ME)~~ have remonumented corners in T. 15 S., R. 3 W., T. 16 S., R. 3 W., T. 18 S., R. 3 W., T. 19 S., R. 3 W., T. 20 S., R. 2 W., T. 21 S., R. 2 W., T. 21 S., R. 4 W., T. 22 S., R. 1 E., T. 22 S., R. 2 E., T. 22 R. 4 E., T. 22 S., R. 4 W., T. 23 S., R. 1 E., T. 23 S., R. 2 E., T. 23 S., R. and T. 23 S., R. 5 W.

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(ME)~~ and under (my) remonumentation ~~(ME)~~ direction; and that said ~~SURVEY~~ has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 13, 1970

(Date)



Surveying Technician

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date JUN 2 1970

BUREAU OF LAND MANAGEMENT
Washington, D.C.


The foregoing field notes of the remonumentation of corners in T. 15 S., R. 3 W., T. 16 S., R. 3 W., T. 18 S., R. 3 W., T. 19 S., R. 3 W., T. 20 S., R. 2 W., T. 21 S., R. 2 W., T. 21 S., R. 4 W., T. 22 S., R. 1 E., T. 22 S., R. 2 E., T. 22 S., R. 4 E., T. 22 S., R. 4 W., T. 23 S., R. 1 E., T. 23 S., R. 2 E., T. 23 S., R. 3 W., and T. 23 S., R. 5 W., Salt Lake Meridian, Utah

executed by

having been critically examined and found correct, are hereby approved.

DEC 1 1971

(Date)



(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
 , is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) ~~CRS 11/1/71~~

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

205

FIELD NOTES

OF THE

REMONUMENTATION OF CORNERS

IN

TOWNSHIP 29 SOUTH, RANGE 4 EAST

TOWNSHIP 33 SOUTH, RANGE 3 EAST

TOWNSHIP 34 SOUTH, RANGE 2 WEST

TOWNSHIP 34 SOUTH, RANGE 8 WEST

TOWNSHIP 35 SOUTH, RANGE 3 WEST

TOWNSHIP 35 SOUTH, RANGE 6 WEST

TOWNSHIP 35 SOUTH, RANGE 7 WEST

TOWNSHIP 35 SOUTH, RANGE 8 WEST

TOWNSHIP 36 SOUTH, RANGE 7 WEST

TOWNSHIP 36 SOUTH, RANGE 9 WEST

TOWNSHIP 37 SOUTH, RANGE 9 WEST

TOWNSHIP 37 SOUTH, RANGE 13 WEST

TOWNSHIP 37 SOUTH, RANGE 14 WEST

Of the SALT LAKE

In the State of UTAH

RECEIVED
BUREAU OF LAND MANAGEMENT
DEC 23 PM 1:55
Meridian

EXECUTED BY

Ferrel D. Reynolds

Surveying Technician

Under special instructions dated February 15, 19 61, which provided for the surveys
included under Group Number 447, approved February 16, 1961,
and assignment instructions dated May 26, 19 69.

Survey commenced August 25, 19 69

Survey completed September 30, 19 69

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 29 S. R. 4 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Monument locations for Tp. 29 S., R. 4 E., Mer. Salt Lake:

- Section 23: Monument 2 at the intersection of the section line and the east line.
- Section 26: Monument 1 at the intersection of the section line and the east line.
- Section 28: Monument 3 at the intersection of the section line and the east line.

Tp. 33 S. R. 3 E. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Monument locations for Tp. 33 S., R. 3 E., Mer. Salt Lake:

- Section 14: Monument 1 at the intersection of the section line and the east line.
- Section 24: Monument 3 at the intersection of the section line and the east line.

Tp. 34 S. R. 2 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Monument locations for Tp. 34 S., R. 2 W., Mer. Salt Lake:

- Section 26: Monument 4 at the intersection of the section line and the east line.
- Section 25: Monument 4 at the intersection of the section line and the east line.

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION
CORNER MONUMENTS

Tp. 34 S. R. 8 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31 ⁷	32 ⁶	33	34	35 ⁵	36 ⁵

Tp. 35 S. R. 3 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23 ⁸	24
30	29	28	27	26 ⁷	25
31	32	33	34	35	36

Tp. 35 S. R. 6 W. Mer. Salt Lake

6	5	4	3	2	1
7	12 ¹²	10 ¹⁰	10	11	12
18	12 ¹²	16 ¹⁶	15	14	13
19	20 ¹⁰	21	22 ⁹	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

211

INDEX TO SECTION CORNER MONUMENTS

Tp. 35 S. R. 7 W. Mer. Salt Lake

6 15	5	4	3 16	2	1
15 7 17	18 8	9	10	11	12
14 18	17 17 16	16	15	14	13
14 9 13	20	21	22	23	24
13 30	29	28	27	26	25
31	32	33	34	35	36

Tp. 35 S. R. 8 W. Mer. Salt Lake
21

6	5 32	4	3 27	2 25	1	21
7	8	9 27	10	11	12 24	21
18	17	30 29 16	26	15	14 23 22	20
19	20 31	28 21	22	23	24	20
30	29	28	27	26	25	19
31	32	33	34	35	36	18

Tp. 36 S. R. 7 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14 33	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 36 S. R. 9 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	35 11 34 36	12
18	17	16	15	14	34 13 34
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 37 S. R. 9 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11 42 39	39 12 39
18	17	16	15	41 42 40 41	13 37 38
19	20 43	21 43	22	23 40	24 37
30 36	29	28	27	26	25
31	32	33	34	35	36

Tp. 37 S. R. 13 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	44 32	33	34	35	36

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

215

INDEX TO SECTION
CORNER MONUMENTSTp. 37 S. R. 14 W. Mer. Salt Lake

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

45
44

Tp. _____ R. _____ Mer. _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. _____ R. _____ Mer. _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank

Page

Remonumentation of Corners

CHAINS

The following field notes are those of the remonumentation of certain identified corners selected by the U.S. Forest Service as being located in or controlling the boundaries of Forest Service lands, situated in the Dixie National Forest. A Forester's Compass was used to determine the new bearings of corner accessories. The mean magnetic declination was found to be as follows:

T. 29 S., R. 4 E.,	Salt Lake Meridian,	15° 10' E.
T. 33 S., R. 3 E.,	" " "	15° 10' E.
T. 34 S., R. 2 W.,	" " "	15° 10' E.
T. 34 S., R. 8 W.,	" " "	15° 20' E.
T. 35 S., R. 3 W.,	" " "	15° 10' E.
T. 35 S., R. 6 W.,	" " "	15° 15' E.
T. 35 S., R. 7 W.,	" " "	15° 20' E.
T. 35 S., R. 8 W.,	" " "	15° 20' E.
T. 36 S., R. 7 W.,	" " "	15° 20' E.
T. 36 S., R. 9 W.,	" " "	15° 20' E.
T. 37 S., R. 9 W.,	" " "	15° 20' E.
T. 37 S., R. 13 W.,	" " "	15° 40' E.
T. 37 S., R. 14 W.,	" " "	15° 40' E.

The position of each corner was marked by the original monument or determined from corner accessories recorded in the survey record. The monumentation was requested by and accomplished in cooperation with the Forest Service.

Remonumentation of Corners in T. 29 S., R. 4 E.

Township 29 South, Range 4 East, Salt Lake Meridian, is located partially within the Dixie National Forest. The subdivisional lines were surveyed by A. D. Ferron in 1883 and portions of the same resurveyed by John P. Walker in 1904.

At the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, marked with a trachyte stone 24x12x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T29S R4E

$\frac{1}{4}$
S26 | S25

1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land in scattered cedar and pinon growth approx. 25 chs. dist. N. of base of hill that bears E. and W.

At the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, marked with a trachyte stone 24x14x8 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

From which,

Remonumentation of Corners in T. 29 S., R. 4 E.

CHAINS

A pinon pine, 7 ins. in diam., bears S. 24° W.,
41 lks. dist., mkd. $\frac{1}{2}$ S35 BT, (same as record)

A pinon pine, 7 ins. in diam., bears N. 42° W.,
27 lks. dist., mkd. $\frac{1}{2}$ S26 BT, (same as record)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 16 ins.
in the ground and in a mound of stone 3 ft. base to brass
cap mkd.

T29S R4E

$\frac{1}{2}$ — S26
S35
1969

Deposit the original stone alongside the corner.

The cor. is located on rocky N. slope of hill in pinon
and cedar growth, 60 lks. dist. E. of small draw, that
drains N. 30° E.

At the $\frac{1}{2}$ sec. cor. of secs. 23 and 26, marked with a
trachyte stone 15x8x6 ins., firmly set and plainly mkd.
 $\frac{1}{2}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins.
in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$
ft. high, to N. Brass cap mkd.

T29S R4E

$\frac{1}{2}$ — S23
S26
1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level land in sagebrush
growth 70 lks. dist. W. of old fence that bears N. and
S.; 90 lks. dist. N. of trail road that bears E. and W.

At the $\frac{1}{2}$ sec. cor. of secs. 22 and 23, marked with a
granite stone 14x8x6 ins., firmly set and plainly mkd.
 $\frac{1}{2}$ on W. face.

From which,

A pinon pine, 12 ins. in diam., bears N. 31° W.
46 lks. dist., mkd. $\frac{1}{2}$ S. BT, (record N. 45° W.,
45 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins.
in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$
ft. high, to W. Brass cap mkd.

Remonumentation of Corners in T. 29 S., R. 4 E.

CHAINS

T29S R4E

 $\frac{1}{4}$

S22|S23

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle S. slope of hill in scattered pinon and cedar growth approx. 12 chs. dist. N. of dirt road that bears E. and W.

At the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, marked with a trachyte stone 17x12x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

T29S R4E

$$\frac{1}{4} \begin{array}{r} \text{S21} \\ \hline \text{S28} \end{array}$$

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope of hill in scattered pinon and cedar growth 16 lks. dist. N. or netwire fence that bears E. and W.

Remonumentation of Corners in T. 33 S., R. 3 E.

Township 33 South, Range 3 East, Salt Lake Meridian, is located within the Dixie National Forest. The following cor. was established by Frank T. Roberts in 1908.

At the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, marked with a trachyte stone 16x10x5 ins. (same as record), firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

From which,

A cedar, 12 ins. in diam., bears S. $3^{\circ} 30'$ E., 50 lks. dist., mkd. T33S R3E S25 BT.

A cedar, 12 ins. in diam., bears N. 25° W., 42 lks. dist., mkd. T33S R3E S24 BT.

There is no record of any original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

Remonumentation of Corners in T. 33 S., R. 3 E.

CHAINS

T33S R3E

$$\frac{1}{2} \begin{array}{r} S24 \\ S25 \end{array}$$

1969

Deposit the original stone alongside the corner.

The cor. is located on S. slope of hill in cedar and pinon growth 130 lks. dist. N. of trail road that bears E. and W.

Remonumentation of Corners in T. 34 S., R. 2 W.

Township 34 South, Range 2 West, Salt Lake Meridian, is located partially within the Dixie National Forest. The following corners were established by Bailey and Burrill in 1876.

At the cor. of secs. 25, 26, 35 and 36, marked with a sandstone 20x10x8 ins., firmly set and plainly mkd. with 1 notch on the S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T34S R2W

$$\begin{array}{r|l} S26 & S25 \\ S35 & S36 \end{array}$$

1969

From which I mark

A ponderosa pine, 14 ins. in diam., bears N. 77° E., 45½ lks. dist., mkd. T34S R2W S25 BT.

Deposit the original stone alongside the corner.

The cor. is located on NE. slope of hill in scattered pinon growth 1 ch. W. of small wash in draw that drains N. 30° W. 1½ chs. dist. N. of trail road that bears S. 60° E. and N. 60° W.

At the 1/4 sec. cor. of secs. 25 and 26, marked with a sandstone 18x10x8 ins., firmly set and plainly mkd. 1/4 on W. face.

From which,

A ponderosa pine, 30 ins. in diam., bears S. 2° W., 32 lks. dist., mkd. 1/4 S. 26 BT (there is no record of any bearing tree).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

Remonumentation of Corners in T. 34 S., R. 2 W.

CHAINS

T34S R2W

$\frac{1}{2}$
S26|S25

1969

Deposit the original stone alongside the corner.

The cor. is located on S. slope of hill in scattered pine and cedar growth, 45 lks. dist. E. of bottom of draw that drains N.

Remonumentation of Corners in T. 34 S., R. 8 W.

Township 34 South, Range 8 West, Salt Lake Meridian, borders the Dixie National Forest. The S. bdy. of the Tp. was surveyed by A. J. Stewart in 1873 and the W. 3 miles of the S. bdy. were resurveyed by J. R. and Quinby Stewart in 1910.

At the cor. of secs. 35 and 36, on the S. bdy. of the Tp. marked with a volcanic stone 24x15x8 ins., firmly set and plainly mkd. with 5 notches on the W. and 1 notch on the E. edge.

There is no remaining evidence of the four original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 6 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T34S R8W

S35|S36

S2

T35S R8W

1969

From which I mark

A fir, 12 ins. in diam., bears N. 74° E., $16\frac{1}{2}$ lks. dist., mkd. T34S R8W S36 BT.

A fir, 8 ins. in diam., bears N. 44° 30' W., 25 lks. dist., mkd. T34S R8W S35 BT.

The original stone in mound alongside the corner.

The cor. is located on NW. slope of hill in thick pine and aspen growth 30 lks. dist. S. of pole fence that bears E. and W.

At the cor. of secs. 34 and 35 on the S. bdy. of the Tp., marked with a volcanic stone 16x9x6 ins., firmly set and plainly mkd. with 4 notches on the W. and 2 on the E. edge.

Remonumentation of Corners in T. 34 S., R. 8 W.

CHAINS

There is no remaining evidence of the aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 16 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T34S R8W

S34|S35

S3

T35S R8W

1969

From which I mark

A pine, 16 ins. in diam., bears N. 46° E., 19 lks. dist., mkd. T34S R8W S35 BT.

A pine, 10 ins. in diam., bears N. 47° W., 39 lks. dist., mkd. T34S R8W S34 BT.

Deposit the original stone alongside the corner.

The corner is located 1 ch. E. of top of hill that bears N. and S., in thick aspen and pine growth at the cor. of old pole fence that bears E. and N:

At the cor. of secs. 31 and 32 on the S. bdy. of the Tp, marked with a red granite stone 16x12x6 ins., firmly set and plainly mkd. with 5 notches on the E. and 1 on the W. edge.

From which,

A cedar, 14 ins. in diam., bears N. 40° W., 20 lks. dist., mkd. T34S R8W S31 BT, (record, N. 50° W., 36 lks. dist.).

There is no remaining evidence of the other bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., on solid rock, over an X, and in a mound of stone 4 ft. base to brass cap mkd.

T34S R8W

S31|S32

S6

T35S R8W

1969

The original stone in mound alongside the corner.

Remonumentation of Corners in T. 34 S., R. 8 W.

CHAINS

The cor. is located on steep rocky W. slope in scattered pinon and cedar growth 45 lks. dist. E. of draw that drains S. 20° W. approx. 10 chs. dist. N. of road to Yankee Meadows Reservoir that bears E. and W.

At the 1/4 sec. cor. of sec. 31 on the S. bdy. of the Tp., marked with a broken flintstone 16x10x4 ins., firmly set, but dimly mkd. 1/4 on N. face.

From which,

A pinon pine, 14 ins. in diam., bears N. 40° W., 25 lks. dist., mkd. with dim scrib mks. (same as record).

There is no evidence of the other bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T34S R8W

½ S31

T35S R8W

1969

The original stone in mound alongside the corner.

The cor. is located on steep N. slope of canyon in pinon and mahogany growth approximately 10 chs. dist. S. of oiled road that bears E. and W.

Remonumentation of Corners in T. 35 S., R. 3 W.

Township 35 South, Range 3 West, Salt Lake Meridian, is located partially within the Dixie National Forest. The following corners were established by Bailey and Burrill in 1876.

At the 1/4 sec. cor. of secs. 26 and 27, marked with a limestone 13x8x7 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T35S R3W

½

S27|S26

1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 35 S., R. 3 W.

CHADNS

The cor. is located on nearly level land in very scattered pine and cedar growth 90 lks. dist. E. of old trail road that bears N. and S. approx. 9 chs. dist. W. of main dirt road in Widsoe Valley that bears N. 40° E. and S. 40° W.

At the cor. of secs. 22, 23, 26 and 27, marked with a limestone 16x8x6 ins., firmly set and plainly mkd. with 2 notches on the E. and S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground with a steel fence post alongside. Brass cap mkd.

T35S R3W

S22	S23
S27	S26

1969

Deposit the original stone and glass alongside the corner.

The cor. is located on nearly level sagebrush flat approximately 7 chs. dist. S. of fence cor. that bears N. and S. 45° E.

Remonumentation of Corners in T. 35 S., R. 6 W.

Township 35 South, Range 6 West, Salt Lake Meridian, is located partially within the Dixie National Forest. The following corners were established by Bailey and Burrill in 1874.

At the cor. of Tps. 34 and 35 S., Rs. 6 and 7 W., mkd. with a granite stone 15x10x10 Ins., firmly set and plainly mkd. with 6 notches on the N., S., E. and W. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 12 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T34S

R7W R6W

S36	S31
S1	S6

T35S

1969

The original stone in mound alongside the corner.

The cor. is located 1 ch. W. of top of ridge that bears N. and S. in sagebrush growth approx. 17 chs. dist. E. of trail road in Pole Hollow that bears S. and N. 25° W.

CHAINS

At the cor. of secs. 21, 22, 27 and 28, marked with a granite stone 16x12x5 ins., firmly set and plainly mkd. with 3 notches on the E. and 2 on the S. edge.

From which,

A pine stump, 20 ins. in diam., 36 ins. high, bears N. 61° E., 79 lks. dist., mkd. S22 BT, (same as record).

A pine stump, 36 ins. in diam., 36 ins. high, bears S. 66° E., 182 lks. dist., mkd. T35S R6W S27 BT, (record S. 66° E., 180 lks. dist.).

There is no remaining evidence of the other two bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 15 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T35S R6W

S21	S22
S28	S27

1969

The cor. is located on nearly level land in scattered pine growth approx. $8\frac{1}{2}$ chs. dist. E. of trail road that bears N. and S.

At the cor. of secs. 16, 17, 20 and 21, marked with a granite boulder 4x4x3 ft. above ground, plainly mkd. with 4 notches on the E., 3 notches on the S., and an X on top for true point.

From which,

A pine, 29 ins. in diam., bears N. $52^{\circ} 30'$ E., 200 lks. dist., with dim scribe marks (record N. 50° E., 196 lks. dist.). Remarked T. 35S R6W S16 BT.

There is no remaining evidence of the other bearing tree.

True point for the cor. cannot be perpetuated with a $2\frac{1}{2}$ inch iron post.

Therefore at a point S. 15 lks. dist.,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 4 ft. base, $1\frac{1}{2}$ ft. high, to W., for the witness cor. mkd.

T35S R6W

WC

S17	S16
S20	S21

1969

Remonumentation of Corners in T. 35 S., R. 6 W.

CHAINS

From which,

The original bearing tree, now bears N. 49° E.,
210 lks. dist.

The original stone in place at true point.

The cor. is located on rocky NW. slope of hill in pine
and mahogany growth approx. 6 chs. dist. E. of draw that
drains N. 50° W.

At the $1/4$ sec. cor. of secs. 8 and 9, mkd. with a
granite stone $14 \times 12 \times 8$ ins., firmly set and plainly
mkd. $1/4$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 15
ins. in the ground and in a mound of stone 3 ft. base
to brass cap mkd.

T35S R6W

$\frac{1}{2}$

S8|S9

1969

Deposit the original stone alongside the corner.

The cor. is located on NE. slope of hill in sagebrush
growth 4 chs. dist. N. of top of ridge that bears S.
 45° E. and N. 45° W. approx. 9 chs. dist. S. of hollow
that drains S. 45° E.

At the cor. of secs. 19, 20, 29 and 30, marked with a
granite stone $16 \times 12 \times 10$ ins., firmly set and plainly
mkd. with 5 notches on the E. and 2 on the S. edge.

From which,

A pine, 24 ins. in diam., bears S. $22^{\circ} 30'$ E., 130
lks. dist., mkd. T35S R6W S29 BT, (record S. 25° E.
158 lks. dist.).

The other bearing tree is dead on ground at approx.
bearing and dist., dimly mkd.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 12
ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base
to brass cap mkd.

T35S R6W

S19|S20

S30|S29

1969

The original stone in mound alongside the corner.

CHAINS

The cor. is located on top of spur that projects N. in scattered pine, cedar and mahogany growth, 30 lks. dist. N. of trail road that bears E. and W. 180 lks. dist. W. of draw that drains N. 15° W.

At the 1/4 sec. cor. of secs. 17 and 20, marked with a granite stone 15x12x6 ins., firmly set and plainly mkd. 1/4 on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 6 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T35S R6W

½ — S17
S20

1969

The original stone in mound alongside the corner.

The cor. is located on gentle W. slope of hill 170 lks. dist. S. of 2 strand telephone line that bears E. and W. approx. 10 chs. dist. E. of trail road that bears N. and S.

At the 1/4 sec. cor. of secs. 18 and 19, marked with a granite stone 16x12x12 ins., firmly set and plainly mkd. 1/4 on N. face.

From which,

A dead mahogany, on ground, bears S. 22° E., 128 lks. dist., dimly mkd. 1/4 S BT, (record S. 22° E., 120 lks. dist.).

A dead mahogany, on ground, bears S. 65° E., 96 lks. dist., mkd. 1/4 S BT, (same as record).

At the corner point

Set an iron post, 30 ins. long, 2½ ins. in diam., 12 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T35S R6W

½ — S18
S19

1969

Deposit the original stone alongside the corner.

The cor. is located on E. slope of hill in scattered mahogany growth approx. 12 chs. dist. W. of base of hill and old trail road that bears N. and S.

Remonumentation of Corners in T. 35 S., R. 6 W.

CHAINS

At the 1/4 sec. cor. of secs. 17 and 18, marked with a granite stone 16x12x9 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 8 ins. in the ground and in a mound of stone 5 ft. base to brass cap mkd.

T35S R6W

½
S18|S17

1969

The original stone in mound alongside the corner.

The corner is located on SW. slope of hill in sagebrush growth 9 lks. dist. W. of netwire fence that bears N. and S. approx. 17 chs. dist. N. of hollow that drains S. 45° E.

At the 1/4 sec. cor. of secs. 7 and 8, marked with a granite stone 14x12x6 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 6 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T35S R6W

½
S7|S8

1969

The original stone in mound alongside the corner.

From which I mark

A cedar, 7 ins. in diam., bears S. 49° W., 28 lks. dist., mkd. 1/4 S7 BT.

The cor. is located on E. slope of hill in scattered cedar growth 2½ chs. dist. W. of base of hill that bears N. and S.

At the cor. of secs. 5, 6, 7 and 8, marked with a granite stone 16x10x6 ins., firmly set and plainly mkd. with 5 notches on the S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 10 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

Remonumentation of Corners in T. 35 S., R. 6 W.

CHAINS

T35S R6W

$\frac{S6}{S7} \frac{S5}{S8}$

1969

The original stone in mound alongside the corner.

The cor. is located on top of spur projecting S. 45° E., in scattered cedar and pinon growth.

Remonumentation of Corners in T. 35 S., R. 7 W.

Township 35 South, Range 7 West, Salt Lake Meridian, is located within the Dixie National Forest. The following corners were established by Shadrach M. Richardson in 1883 and 1884.

At the 1/4 sec. cor. of sec. 30 on the W. bdy. of the Tp., marked with a volcanic stone 15x8x6 ins., firmly set and plainly mkd. 1/4 on E. face.

From which,

An aspen, 6 ins. in diam., bears N. 48° E., 13 lks. dist., dead but with faint scribe marks.

The 1/4 sec. cor. of sec. 25, bears S. 3° 30' E., 116 lks. dist. (record S. 0° 6' E., 116 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and in a collar of stone to brass cap mkd.

T35S
R8W R7W
 $\frac{1}{2}$
S30

1969

From which I mark

An aspen, 5 ins. in diam., bears S. 73° E., 11 lks. dist., mkd. 1/4 S30 BT.

Deposit the original stone alongside the corner.

The cor. is located on NW. slope of hill in thick aspen growth, approx. 6 chs. dist. S. of clearing that bears N. 45° E. and S. 45° W.

At the cor. of secs. 19 and 30 on the W. bdy. of the Tp., marked with a volcanic stone 14x10x6 ins., firmly set and plainly mkd. with 4 notches on the N. and 2 on the S. edge.

At the cor. point

Remonumentation of Corners in T. 35 S., R. 7 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to E. Brass cap mkd.

T35S
R8W R7W
S24 | $\frac{S19}{S30}$

1969

From which I mark

An aspen, 8 ins. in diam., bears N. 63° E., 19 lks. dist., mkd. T35S R7W S19 BT.

An aspen, 6 ins. in diam., bears S. 41° E., $7\frac{1}{2}$ lks. dist., mkd. T35S R7W S30 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle S. slope of hill in thick aspen growth.

At the $\frac{1}{4}$ sec. cor. of sec. 19 on the W. bdy. of the Tp., marked with a volcanic stone $16 \times 10 \times 6$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on E. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to brass cap mkd.

T35S
R8W R7W
| $\frac{1}{2}$
| S19

1969

From which I mark

A pine, 15 ins. in diam., bears S. 23° E., 25 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

Deposit the original stone alongside the corner.

The cor. is located on E. slope of hill in thick pine and aspen growth approx. 575 lks. dist. S. of draw that drains S. 45° E.

At the $\frac{1}{4}$ sec. cor. of sec. 18 on the W. bdy. of the Tp., mkd. with a volcanic stone $15 \times 10 \times 4$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

From which,

A balsam, 10 ins. in diam., bears S. 51° E., $20\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S BT, (record S. 80° E., 15 lks. dist.).

Remonumentation of Corners in T. 35 S., R. 7 W.

CHAINS

A balsam, 11 ins. in diam., bears N. 70° W., 5 lks. dist., mkd. $1/4$ S BT, (record W. 7 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T35S
R8W R7W
| $\frac{1}{2}$
S18
1969

Deposit the original stone alongside the corner.

The cor. is located on NW. slope of hill in thick aspen and pine growth approx. 15 chs. dist. S. of edge of grassy flat that bears NE. and SW.

At the $1/4$ sec. cor. of sec. 7 on the W. bdy. of the Tp., marked with a volcanic stone $16 \times 10 \times 6$ ins., firmly set and plainly mkd. $1/4$ on E. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to E. Brass cap mkd.

T35S
R8W R7W
| $\frac{1}{2}$
S7
1969

Deposit the original stone alongside the corner.

The cor. is located on W. edge of grassy flat 150 lks. dist. E. of timber line that bears N. and S. at the cor. of netwire fence that bears E. and S.

At the cor. of secs. 6 and 7 on the W. bdy. of the Tp., marked with a volcanic stone $18 \times 12 \times 8$ ins., firmly set and plainly mkd. with 5 notches on the S. and 1 on the N.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

Remonumentation of Corners in T. 35 S., R. 7 W.

CHAINS

T35S
R8W R7W
S1 | S6
 | S7
1969

The original stone in mound alongside the corner.

The cor. is located at the W. edge of large grassy flat 200 lks. dist. E. of timber edge that bears N. and S.

At the cor. of secs. 3, 4, 9 and 10, marked with a volcanic stone 18x16x14 ins., firmly set and plainly mkd. with 5 notches on the S. and 3 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T35S R7W
S4 | S3
S9 | S10
1969

Deposit the original stone alongside the corner.

The cor. is located in small pass near top of hill that bears N. 45° W. and S. 45° E., in scattered mahogany growth approx. 14 chs. dist. N. of base of hill and dirt road that bears E. and W.

At the cor. of secs. 17, 18, 19 and 20, marked with a volcanic stone 19x12x12 ins., firmly set and plainly mkd. with 5 notches on the E. and 3 notches on the S.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 4 ft. base, 2 ft. high, to W. Brass cap mkd.

T35S R7W
S18 | S17
S19 | S20
1969

From which I mark

An aspen, 7 ins. in diam., bears N. 37° 30' E., 16 lks. dist., mkd. T35S R7W S17 BT.

An aspen, 7 ins. in diam., bears S. 36° E., 6 lks. dist., mkd. T35S R7W S20 BT.

CHAINS

An aspen, 4 ins. in diam., bears S. 64° W., 9 lks. dist., mkd. T35S R7W S19 BT.

An aspen, 4 ins. in diam., bears N. 13° 39' W., 28 lks. dist., mkd. T35S R7W S18 BT.

Deposit the orig. stone alongside the corner.

The cor. is located on gentle E. slope of hill in thick aspen growth 245 lks. dist. W. of trail road that bears N. 30° W. and S. 30° E.

At the 1/4 sec. cor. of secs. 17 and 18, marked with a lava stone 14x14x8 ins., firmly set and plainly mkd. 1/4 on W. face.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T35S R7W

½
S18|S17

1969

From which I mark

A pine, 8 ins. in diam., bears S. 43° E. 36 lks. dist., mkd. 1/4 S17 BT.

A pine, 14 ins. in diam., bears N. 27° 30' W., 43 lks. dist., mkd. 1/4 S18 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle NW. slope of hill in thick aspen and pine growth.

At the 1/4 sec. cor. of secs. 7 and 18, marked with a lava stone 14x9x4 ins., firmly set and plainly mkd. 1/4 on N. face.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 16 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T35S R7W

½ S7
 S18

1969

Remonumentation of Corners in T. 35 S., R. 7 W.

CHAINS

From which I mark

An aspen, 8 ins. in diam., bears S. 22° E., 20 lks. dist., mkd. 1/4 S18 BT.

A pine, 14 ins. in diam., bears N. 76° W., 40 lks. dist., mkd. 1/4 S7 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle W. slope of hill in thick aspen and pine growth, 1 ch. dist. E. of steep descent, 7 lks. dist. S. of netwire fence that bears W. and E., 20 lks. dist.; thence N.

At the 1/4 sec. cor. of secs. 7 and 8, marked with a lava stone 24x12x9 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 12 ins. in the ground and in a mound of stone 4 ft. base to brass cap, raise a mound of stone 5 ft. base, 3 ft. high, to W. Brass cap mkd.

T35S R7W

½

S7|S8

1969

The original stone in mound alongside the corner.

The cor. is located on steep SW. slope of hill in small grassy clearing surrounded by aspens.

Remonumentation of Corners in T. 35 S., R. 8 W.

Township 35 South, Range 8 West, Salt Lake Meridian, is located within the Dixie National Forest. The E. bdy. was surveyed by Shadrach M. Richardson in 1883 and re-surveyed by R.E.L. Collier in 1895. Portions of the subdivisional lines were surveyed by R.E.L. Collier in 1895, Mayhew H. Dalley in 1908 and Elliot Bird in 1927.

At the 1/4 sec. cor. of sec. 25 on the E. bdy. of the Tp. marked with a volcanic stone 12x8x7 ins., firmly set and plainly mkd. 1/4 on W. face.

From which

The 1/4 sec. cor. of sec. 30, bears N. 3° 30' W., 116 lks. dist., (record N. 0° 6' W., 116 lks. dist.)

CHAINS

There is no remaining evidence of the original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T35S
R8W R7W

$\frac{1}{2}$
S25

1969

From which I mark

A ponderosa pine, 20 ins. in diam., bears S. 7° W., 226 lks. dist., mkd. $1/4$ S25 BT.

The cor. is located on top of a small rise that bears N. 45° E. and S. 45° W. in thick aspen growth.

At the cor. of secs. 24 and 25 on the E. bdy. of the Tp., marked with a volcanic stone $20 \times 12 \times 6$ ins., firmly set and plainly mkd. with 4 notches on the N. and 2 on the S.

There is no remaining evidence of the 2 original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T35S
R8W R7W

$\frac{S24}{S25}$ S30

1969

From which I mark

An aspen, 8 ins. in diam., bears S. 87° W., 14 lks. dist., mkd. T35S R8W S25 BT.

An aspen, 8 ins. in diam., bears N. 48° W., 11 lks. dist., mkd. T35S R8W S24 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle S. slope of hill in thick aspen growth 120 lks. dist. N. of clearing that bears E. and W.

Remonumentation of Corners in T. 35 S., R. 8 W.

CHAINS

At the 1/4 sec. cor. of sec. 24 on the E. bdy. of the Tp., marked with a volcanic stone 14x10x5 ins., firmly set and plainly mkd. 1/4 on W. face.

From which

An aspen, 12 ins. in diam., bears N. 10° W., 12 lks. dist., mkd. 1/4 S BT, (same as record).

There is no remaining evidence of the other aspen bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T35S
R8W R7W
½
S24
1969

From which I mark

A pine, 40 ins. in diam., bears S. 60° W., 38 lks. dist., mkd. 1/4 S24 BT.

Deposit the original stone alongside the corner.

The cor. is located on E. slope of hill in thick aspen and pine growth 60 lks. dist. E. of small clearing that bears E. and W.

At the 1/4 sec. cor. of sec. 13 on the E. bdy. of the Tp., marked with a volcanic stone 14x10x8 ins., firmly set and plainly mkd. 1/4 on W. face.

From which

An aspen, 8 ins. in diam., bears N. 48° E., 20 lks. dist., mkd. 1/4 S BT, (record NE., 33 lks. dist.).

There is no remaining evidence of the other aspen bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T35S
R8W R7W
½
S13
1969

From which I mark

Remonumentation of Corners in T. 35 S., R. 8 W.

CHAINS

A balsam, 12 ins. in diam., bears N. 75° W., 24 lks. dist., mkd. 1/4 S13 BT.

Deposit the original stone alongside the corner.

The cor. is located on NW. slope of hill in thick aspen and pine growth.

At the cor. of secs. 12 and 13 on the E. bdy. of the Tp., marked with a volcanic stone 14x8x6 ins., firmly set and plainly mkd. with 4 notches on the S. and 2 on the N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground with a steel fence post alongside. Brass cap mkd.

T35S
R8W R7W
S12 S18
S13
1969

Deposit the original stone alongside the corner.

The corner is located in large grassy flat 360 lks. dist. S. of fence cor. that bears N. and E.

At the cor. of secs. 1 and 12 on the E. bdy. of the Tp., marked with a volcanic stone 30x8x8 ins., firmly set and plainly mkd. with 5 notches on the S. and 1 on the N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 10 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T35S
R8W R7W
S1 S7
S12
1969

The original stone in mound alongside the corner.

The cor. is located at W. edge of grassy flat 1 ch. W. of old trail road that bears N. 45° W. and S. 45° E. 250 lks. dist. E. of timber edge that bears N. and S.

At the closing cor. of secs. 2 and 3 on the N. bdy. of the Tp., marked with a volcanic stone 24x12x10 ins., firmly set and plainly mkd. with 4 notches on the W., 2 on the E. and CC on S. face.

Remonumentation of Corners in T. 35 S., R. 8 W.

CHAINS

An aspen, 12 ins. in diam., bears S. 66° E., 84 lks. dist., mkd. T35S R8W S2 CC BT, (record S. 60° E., 84 lks. dist.).

An aspen, 7 ins. in diam., bears S. $28^{\circ} 30'$ W., 20 lks. dist., mkd. T35S R8W S3 CC BT, (record S. 15° W., 20 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to S. Brass cap mkd.

T34S R8W
S35
 S3 | S2
 CC
 T35S R8W
 1969

Deposit the original stone alongside the corner.

The cor. is located on W. slope of hill in pine and aspen growth at the cor. of pole fence that bears S. and E. approx. 10 chs. dist. E. of Hoosier Lake.

At the cor. of secs. 13, 14, 23 and 24, marked with a red sandstone $16 \times 12 \times 6$ ins., firmly set and plainly mkd. with 3 notches on the S. and 1 on the E.

From which,

An aspen, 7 ins. in diam., bears N. 67° E., 11 lks. dist., mkd. with faint scribe mks., (record N. 77° E., 11 lks. dist.); remarked T35S R8W S13 BT.

An aspen, 6 ins. in diam., bears S. 57° E., 21 lks. dist., mkd. with faint scribe mks., (record S. 67° E., 24 lks. dist.); remarked T35S R8W S24 BT.

An aspen, 8 ins. in diam., bears S. 8° W., 50 lks. dist., mkd. with faint scribe mks., (record S. 17° W., 47 lks. dist.); remarked T35S R8W S23 BT.

An aspen, 8 ins. in diam., bears N. 83° W., 54 lks. dist., mkd. with faint scribe mks., (record N. 86° W., 56 lks. dist.); remarked T35S R8W S14 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T35S R8W
S14 | S13
 S23 | S24
 1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 35 S., R. 8 W.

CHAINS

The cor. is located on E. slope of hill in thick aspen and pine growth.

At the 1/4 sec. cor. of secs. 13 and 14, marked with a volcanic stone 16x14x6 ins., firmly set and plainly mkd. 1/4 on W. face.

There is no remaining evidence of the original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 4 ft. base 2 ft. high, to W. Brass cap mkd.

T35S R8W

$\frac{1}{4}$
S14|S13

1969 ,

From which I mark

A balsam, 10 ins. in diam., bears N. 81° E., 61 lks. dist., mkd. 1/4 S13 BT.

A balsam, 13 ins. in diam., bears S. 81° W., 38 lks. dist., mkd. 1/4 S14 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle E. slope of hill in thick aspen and pine growth.

At the cor. of secs. 11, 12, 13 and 14, marked with a volcanic stone 12x8x6 ins., firmly set and plainly mkd. with 4 notches on the S. and 1 on the E. edge.

From which,

A balsam, 12 ins. in diam., bears N. 19° W., $24\frac{1}{2}$ lks. dist., mkd. T35S R8W S11 BT. (Record N. 15° W., 25 lks. dist.)

A balsam, 14 ins. in diam., bears S. 62° W., 69 lks. dist., mkd. T35S R8W S14 BT. (Record S. 61° W., 63 lks. dist.)

There is no remaining evidence of the other aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground with a steel fence post to the W. Brass cap mkd.

T35S R8W

S11|S12

S14|S13

1969

Remonumentation of Corners in T. 35 S., R. 8 W.

CHAINS

From which I mark

A balsam, 10 ins. in diam., bears N. 29° E., $16\frac{1}{2}$ lks. dist., mkd. T35S R8W S12 BT.

A balsam, 14 ins. in diam., bears S. $56^{\circ} 30'$ E., $41\frac{1}{2}$ lks. dist., mkd. T35S R8W S13 BT.

Deposit the original stone alongside the corner.

The corner is located on W. slope of hill in thick aspen and pine growth approx. 10 chs. dist. E. of trail road in bottom of draw that drains S.

At the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, marked with a sandstone $18 \times 14 \times 6$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

There is no remaining evidence of the original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T35S R8W

$\frac{1}{4}$ S12
S13

1969

From which I mark

A pine, 10 ins. in diam., bears N. 1° W., 45 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

A pine, 12 ins. in diam., bears S. 83° E., 26 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

Deposit the original stone alongside the corner.

The cor. is located on E. slope of hill in thick aspen and pine growth at the cor. of old pole fence that bears S. and E.

At the cor. of secs. 22, 23, 26 and 27, marked with a volcanic stone $18 \times 10 \times 8$ ins., firmly set and plainly mkd. with 2 notches on the S. and E. edges.

From which,

An aspen, 14 ins. in diam., bears S. $29^{\circ} 30'$ E., 50 lks. dist., mkd. T35S R8W S26 BT. (Record S. 35° E., 51 lks. dist.)

An aspen, 12 ins. in diam., bears S. 22° W., 65 lks. dist., mkd. T35S R8W S27 BT. (Record S. 20° W., 65 lks. dist.)

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T35S R8W

S22	S23
S27	S26

1969

From which I mark

An aspen, 6 ins. in diam., bears N. 36° E., 46 lks. dist., mkd. T35S R8W S23 BT.

An aspen, 8 ins. in diam., bears S. 43° E., 68 lks. dist., mkd. T35S R8W S26 BT.

An aspen 7 ins. in diam., bears N. 82° W., 19 lks. dist., mkd. T35S R8W S22 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle SE. slope of hill in thick aspen growth at the cor. of old pole fence bearing N. and E.

At the cor. of secs. 2, 3, 10 and 11, marked with a volcanic stone $24 \times 10 \times 6$ ins., firmly set in a mound of stone and plainly mkd. with 5 notches on the S. and 2 on the E. edge.

There is no remaining evidence of the original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 8 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T35S R8W

S3	S2
S10	S11

1969

From which I mark

An aspen, 9 ins. in diam., bears N. 67° E., 47 lks. dist., mkd. T35S R8W S2 BT.

An aspen, 7 ins. in diam., bears S. 34° E., 38 lks. dist., mkd. T35S R8W S11 BT.

An aspen, 8 ins. in diam., bears S. 10° W., 45 lks. dist., mkd. T35S R8W S10 BT.

The original stone in mound alongside the corner.

Remonumentation of Corners in T. 35 S., R. 8 W.

CHAINS

The cor. is located on top of small rocky knoll that bears E. and W. in thick aspen and pine growth about 5 chs. dist. N. of draw that drains W.

At the cor. of secs. 21, 22, 27 and 28, marked with a volcanic stone 36x14x10 ins., firmly set and plainly mkd. with 3 notches on the E. and 2 on the S. edge.

From which,

An aspen, 7 ins. in diam., bears N. 52° E., 63 lks. dist., mkd. T35S R8W S22 BT. (Record N. 55° E., 53 lks. dist.)

A pine, 24 ins. in diam., bears S. 82° W., 39½ lks. dist., mkd. T35S R8W S28 BT. (Record S. 85° W., 35 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap; raise a mound of stone 4 ft. base, 2 ft. high, to W. brass cap mkd.

T35S R8W

S21	S22
S28	S27

1969

From which I mark

An aspen, 6 ins. in diam., bears S. 63° 30' E., 56 lks. dist., mkd. T35S R8W S27 BT.

Deposit the original stone alongside the corner.

The cor. is located on W. slope of hill in scattered aspen and pine growth about 2½ chs. dist. W. of top of hill that bears N. and S. in large lava flow.

At the cor. of secs. 9, 10, 15 and 16, as determined by an old mound of stone, with no visible markings.

From which,

An aspen, 8 ins. in diam., bears N. 9° E., 166 lks. dist., (record N. 13° 30' E., 165 lks.); remarked T35S R8W S10 BT.

An aspen, 8 ins. in diam., bears S. 54° W., 44 lks. dist., (record S. 41° W., 43 lks.); remarked T35S R8W S16 BT.

An aspen, 8 ins. in diam., bears N. 36° 45' W., 94 lks. dist., (record N. 39° W., 95 lks.); remarked T35S R8W S9 BT.

At the cor. point

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T35S R8W

$\frac{S9}{S16} | \frac{S10}{S15}$

1969

From which I mark

A ponderosa pine, 20 ins. in diam., bears N. 16° E., 29 lks. dist., mkd. T35S R8W S10 BT.

A ponderosa pine, 20 ins. in diam., bears N. 14° W., 26 lks. dist., mkd. T35S R8W S9 BT.

The cor. is located on W. slope of hill in aspen and pine growth 3 chs. dist. E. of small clearing that bears N. and S.

At the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, marked with a volcanic stone $24 \times 12 \times 10$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

There is no remaining evidence of the two original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T35S R8W

$\frac{S9}{S10} | \frac{S10}{S15}$

1969

From which I mark

An aspen, 7 ins. in diam., bears S. 71° E., 15 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

An aspen, 5 ins. in diam., bears S. 84° W., 4 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

Deposit the original stone alongside the corner.

The cor. is located on W. slope of hill in aspen growth, 60 lks. dist. W. of trail road that bears N. and S.

At the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, marked with a sandstone $18 \times 10 \times 10$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Remonumentation of Corners in T. 35 S., R. 8 W.

	CHAINS	<p>Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.</p> <p style="text-align: center;">T35S R8W ½ $\frac{S3}{S10}$ 1969</p> <p>From which I mark</p> <p style="padding-left: 40px;">A cedar, 7 ins. in diam., bears S. 4° W., 92 lks. dist., mkd. ¼ S10 BT.</p> <p style="padding-left: 40px;">Deposit the original stone alongside the corner.</p> <p>The cor. is located on SE. slope of hill in scattered aspen, pine and cedar growth 240 lks. dist. W. of trail road that bears N. and S. in small draw.</p> <hr/> <p>At the ¼ sec. cor. of secs. 20 and 21, marked with a volcanic stone 14x12x4 ins., firmly set and plainly mkd. ¼ on W. face.</p> <p>From which,</p> <p style="padding-left: 40px;">An aspen, 10 ins. in diam., (dead), bears S. 87° W., 18 lks. dist., mkd. ¼ S. BT.</p> <p style="padding-left: 40px;">There is no remaining evidence of the other aspen bearing tree.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.</p> <p style="text-align: center;">T35S R8W ½ S20 S21 1969</p> <p>From which I mark</p> <p style="padding-left: 40px;">A pine, 10 ins. in diam., bears S. 83° 30' E., 20 lks. dist., mkd. ¼ S21 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. in diam., bears N. 62° 30' W., 19 lks. dist., mkd. ¼ S20 BT.</p> <p style="padding-left: 40px;">Deposit the original stone alongside the corner.</p> <p>The cor. is located on N. slope of hill in thick aspen and pine growth approx. 6 chs. dist. S. of trail road that bears E. and W.</p> <hr/>
--	--------	---

CHAINS

At the cor. of secs. 16, 17, 20 and 21, marked with a volcanic stone 18x14x6 ins., firmly set and plainly mkd. with 4 notches on the E. and 3 on the S. edge.

From which,

An Aspen, 10 ins. in diam., bears N. 35° W., 41 lks. dist., mkd. T35S R8W S17 BT. (Same as record.)

There is no remaining evidence of the other aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T35S R8W

S17	S16
S20	S21

1969

From which I mark

An aspen, 12 ins. in diam., bears N. 64° E., 60 lks. dist., mkd. T35S R8W S16 BT.

An aspen, 9 ins. in diam., bears S. 68° E., 59 lks. dist., mkd. T35S R8W S21 BT.

A pine, 10 ins. in diam., bears S. 40° 20' W., 5 lks. dist., mkd. T35S R8W S20 BT.

A pine, 8 ins. in diam., bears N. 84° W., 19½ lks. dist., mkd. T35S R8W S17 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle N. slope of hill in thick aspen and pine growth approx. 10 chs. dist. N. of trail road that bears E. and W.

At the 1/4 sec. cor. of secs. 16 and 17, marked with a sandstone 14x12x4 ins., firmly set and plainly mkd. 1/4 on W. face.

From which,

A ponderosa pine, 16 ins. in diam., bears N. 80° E., 36 lks. dist., mkd. 1/4 S BT. (Record N. 75° E., 37 lks. dist.)

A spruce, 20 ins. in diam., bears S. 15° 45' E., 36 lks. dist., mkd. 1/4 S BT. (Record S. 15° E., 34 lks. dist.)

At the cor. point

Remonumentation of Corners in T. 35 S., R. 8 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground with a steel fence post to the W. Brass cap mkd.

T35S R8W

$\frac{1}{4}$
S17|S16

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle E. slope of hill in scattered pine and aspen growth, 120 lks. dist. W. of trail road that bears N. and S.

At the cor. of secs. 8, 9, 16 and 17, marked with a sandstone 16x12x8 ins., firmly set and plainly mkd. with 4 notches on the S. and E. edge.

From which,

A pine, 10 ins. in diam., bears N. $28^{\circ} 30'$ W., 31 lks. dist., mkd. T35S R8W S8 BT. (Record N. 20° W., 35 lks. dist.)

There is no remaining evidence of the other 3 orig. bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T35S R8W

$\frac{1}{4}$
S8|S9
S17|S16

1969

From which I mark

A pine, 5 ins. in diam., bears S. $48^{\circ} 30'$ E., $19\frac{1}{2}$ lks. dist., mkd. T35S R8W S16 BT.

A pine, 5 ins. in diam., bears S. 80° W., $13\frac{1}{2}$ lks. dist., mkd. T35S R8W S17 BT.

Deposit the original stone alongside the corner.

The cor. is located on steep NE. slope of hill in pine and cedar growth 45 lks. dist. S. of draw that drains E. near top of hill that bears N. and S.

At the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, marked with a volcanic stone 22x10x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

From which,

CHAINS

A yellow pine, 60 ins. in diam., bears S. $16^{\circ} 30'$ E., 110 lks. dist., mkd. $1/4$ S BT. (Record S. 15° E., 112 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T35S R8W

$\frac{1}{4}$ S9
S16

1969

Deposit the original stone alongside the corner and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to N.

The cor. is located on S. end of grassy flat at edge of aspen and pine growth that bears E. and W.

At the cor. of secs. 19 and 20 on the N. bdy. of sec. 30, marked with a flintstone $18 \times 16 \times 8$ ins., firmly set and plainly mkd. with 5 notches on the E. and 2 on the S. edge.

From which,

A ponderosa pine, 20 ins. in diam., bears N. 49° $30'$ E., 121 lks. dist., mkd. T35S R8W S20 Bt. (Record N. 55° E., 130 lks. dist.)

A ponderosa pine, (dead), 30 ins. in diam., bears N. 57° W., 70 lks. dist., mkd. T35S R8W S19 BT. (Record N. 75° W., 80 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T35S R8W

S19|S20
S30

1969

Deposit the original stone alongside the corner.

The cor. is located on steep SW. slope of hill in thick cedar and pine growth 75 lks. dist. E. of small draw that drains S. 40° W approx. 10 chs. dist. W. of trail road that bears N. and S.

Remonumentation of Corners in T. 35 S., R. 8 W.

CHAINS

At the S. 1/4 sec. cor. of sec. 20, marked with a volcanic stone 24x12x5 ins., firmly set and plainly mkd. 1/4 on N. face.

From which,

A pine, 10 ins. in diam., bears S. 75° E., 21 lks. dist., mkd. 1/4 S BT. (Same as record.)

A pine, (dead), 8 ins. in diam., bears S. 30° W., 26 lks. dist., mkd. 1/4 S BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T35S R8W

1/4 S20

1969

From which I mark

A pine, 8 ins. in diam., bears N. 26° E., 24 lks. dist., mkd. 1/4 S20 BT.

Deposit the original stone alongside the corner.

The cor. is located on W. slope of hill in thick pine growth 10 lks. dist. S. of cor. of fence that bears N. and W.

At the cor. of secs. 5, 6, 7 and 8, marked with a white sandstone 18x6x6 ins., firmly set and plainly mkd. with 5 notches on the S. and E. edges.

From which,

A pinon pine, 9 ins. in diam., bears N. 48° 30' E., 12 lks. dist., mkd. T35S R8W S5 BT. (Same as record.)

A cedar, 10 ins. in diam., bears S. 38° 45' W., 80 lks. dist., mkd. T35S R8W S7 BT. (Same as record.)

A pinon pine, 10 ins. in diam., bears N. 72° W., 24 lks. dist., mkd. T35S R8W S6 BT. (Same as record)

There is no remaining evidence of the other bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T35S R8W

S6|S5

S7|S8

1969

Deposit the original stone alongside the corner.

CHAINS

The cor. is located on steep SW. slope of hill in scattered pinon and cedar growth approx. $6\frac{1}{2}$ chs. dist. N. of dirt road in canyon that bears E. and W.

Remonumentation of Corners in
T. 36 S., R. 7 W.

Township 36 South, Range 7 West, Salt Lake Meridian, is located within the Dixie National Forest. The following cor. was established by Shadrach M. Richardson in 1884.

At the $1/4$ sec. cor. of secs. 13 and 14 as determined by an old mound of stone, (in fence line that bears E. and W.), with no visible markings.

From which,

A pine, 16 ins. in diam., bears N. 15° E., $51\frac{1}{2}$ lks. dist., mkd. $1/4$ S BT. (Record N. 15° E., 35 lks.)

A pine, 24 ins. in diam., bears S. 40° W., $29\frac{1}{2}$ lks. dist., mkd. $1/4$ S BT. (Record S. 40° W., 25 lks.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

T36S R7W

$\frac{1}{2}$

S14|S13

1969

From which,

A small stock pond, bears S. 45° W., 4 chs. dist.

The cor. is located on SW. slope of hill in scattered pine and cedar growth 140 lks. dist. E. of base of hill that bears N. 30° W. and S. 30° E.

Remonumentation of Corners in T. 36 S., R. 9 W.

Township 36 South, Range 9 West, Salt Lake Meridian, is located within the Dixie National Forest. The following corners were established by Jenkins and West in 1897 and Mayhew H. Dalley in 1910.

Remonumentation of Corners in T. 36 S., R. 9 W.

CHAINS

At the 1/4 sec. cor. of secs. 13 and 24, marked with a volcanic stone 15x8x6 ins., firmly set and plainly mkd. 1/4 on N. face.

From which,

A balsam, 14 ins. in diam., bears S. 24° E., 14 lks. dist., mkd. 1/4 S BT. (Same as record.)

There is no remaining evidence of the other bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T36S R9W

½ — S13
S24

1969

From which I mark

A balsam, 9 ins. in diam., bears N. 9° W., 13 lks. dist., mkd. 1/4 S13 BT.

Deposit the original stone alongside the corner.

The cor. is located on gentle NE. slope of hill in scattered pine growth.

At the 1/4 sec. cor. of secs. 13 and 14, marked with a volcanic stone 20x12x10 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T36S R9W

½
S14|S13

1969

Deposit the original stone alongside the corner.

The cor. is located on grassy S. slope of hill, no timber; at the cor. of netwire fence that bears W. and S.

At the cor. of secs. 10, 11, 14 and 15, marked with a volcanic stone 12x10x6 ins., firmly set and plainly mkd. with 4 notches on the S. and 2 on the E. edge.

CHAINS

From which,

A spruce, 20 ins. in diam., bears N. $21^{\circ} 45'$ E., 44 lks. dist., mkd. T36S R9W S11 BT. (Same as record.)

A balsam, 15 ins. in diam., bears S. $66^{\circ} 15'$ E., 53 lks. dist., mkd. T36S R9W S14 BT. (Same as record.)

A spruce, 18 ins. in diam., bears S. $25^{\circ} 15'$ W., 39 lks. dist., mkd. T36S R9W S15 BT. (Same as record.)

A spruce, 20 ins. in diam., bears N. $83^{\circ} 45'$ W., 100 lks. dist., mkd. T36S R9W S10 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 14 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T36S R9W

S10 | S11

S15 | S14

1969

Deposit the original stone alongside the corner.

The cor. is located near the top of small rise that bears N. and S., in thick aspen and pine growth 30 lks. dist. N. of old trail road that bears N. 40° W. and S. 40° E.

At the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, marked with a volcanic stone 20x10x10 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W. face.

There is no remaining evidence of the original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T36S R9W

$\frac{1}{2}$
S10 | S11

1969

From which I mark

A balsam, 24 ins. in diam., bears N. 78° E., $37\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S11 BT.

Remonumentation of Corners in T. 36 S., R. 9 W.

CHAINS

A balsam, 15 ins. in diam., bears N. 20° 45' W., 55 lks. dist., mkd. 1/4 S10 BT.

Deposit the original stone alongside the corner.

The cor. is located on NW. slope of hill in thick pine growth 60 lks. dist. N. of 3 strand power line that bears N. 37° W. and S. 37° E.

At the 1/4 sec. cor. of secs. 10 and 15, marked with a trachyte stone 14x12x5 ins., firmly set and plainly mkd. 1/4 on N. face.

From which,

An aspen, 9 ins. in diam., bears N. 25° 15' E., 19 lks. dist., mkd. 1/4 S10 BT. (Record N. 29° 30' E., 22 lks. dist.)

There is no remaining evidence of the other bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T36S R9W

¼ S10

S15

1969

From which I mark

An aspen, 7 ins. in diam., bears S. 22° E., 29½ lks. dist., mkd. 1/4 S15 BT.

Deposit the original stone alongside the corner.

The cor. is located on steep SW. slope of hill in thick aspen growth.

Remonumentation of Corners in T. 37 S., R. 9 W.

Township 37 South, Range 9 West, Salt Lake Meridian, is located within the Dixie National Forest. The following corners were established by Mayhew H. Dalley in 1910.

At the closing cor. of secs. 30 and 31 on the W. bdy. of the Tp., marked with a volcanic stone 16x10x8 ins., firmly set and plainly mkd. with 5 notches on the N., 1 on the S. and CC on the E. face.

From which,

CHAINS

An aspen, 14 ins. in diam., bears N. 52° E., 71 lks. dist., mkd. T37S R9W S30 BT. (Record N. 55° 30' E., 72 lks. dist.)

An aspen, 15 ins. in diam., bears S. 55° E., 144 lks. dist., mkd. T37S R9W S31 BT. (Record S. 50° 30' E., 145 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to E. Brass cap mkd.

T37S R9W
 S25 | S30 CC
 R10W | S31
 1969

Deposit the original stone alongside the corner.

The cor. is located on gentle S. slope of hill in thick aspen growth in netwire fence that bears N. and S. approx. 15 chs. dist. S. of trail road that bears E. and W.

At the cor. of secs. 23, 24, 25 and 26 as determined from the two original bearing trees.

A balsam, 15 ins. in diam., bears N. 23° 30' E., 263 lks. dist., mkd. T37S R9W S24 BT. (Same as record.)

A spruce, 20 ins. in diam., bears N. 38° 15' W., 135 lks. dist., mkd. T37S R9W S23 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 14 ins. in the ground and in a mound of stone 3 ft. base to brass cap mkd.

T37S R9W
 S23 | S24
 S26 | S25
 1969

The cor. is located on N. end of grassy meadow 47 lks. N. of State Highway 14 that bears E. and W. 100 lks. dist. S. of timber edge that bears E. and W.

At the cor. of secs. 13, 14, 23 and 24, marked with a trachyte stone 18x10x6 ins., firmly set and plainly mkd. with 3 notches on the S. and 1 on the E. edge.

From which,

Remonumentation of Corners in T. 37 S., R. 9 W.

CHAINS

A spruce, 28 ins. in diam., bears N. 4° E., 176 lks. dist., mkd. T37S R9W S13 BT. (Same as record.)

A spruce, 15 ins. in diam., bears S. $14^{\circ} 15'$ E., 111 lks. dist., mkd. T37S R9W S24 BT. (Same as record.)

A balsam, 12 ins. in diam., bears S. $36^{\circ} 30'$ W., $70\frac{1}{2}$ lks. dist., mkd. T37S R9W S23 BT. (Same as record.)

There is no remaining evidence of the other bearing tree.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T37S R9W

S14 | S13

S23 | S24

1969

Deposit the original stone alongside the corner.

The cor. is located in small grassy clearing, 3 chs. long 1 ch. wide, that bears N. and S. $4\frac{1}{2}$ chs. dist. W. of large grassy meadow that bears E. and W. Surrounded by spruce and balsam trees.

At the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, marked with a volcanic stone $18 \times 12 \times 4$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.

From which,

A spruce, 28 ins. in diam., bears N. 35° E., 51 lks. dist., mkd. $\frac{1}{4}$ S13 BT. (Same as record.)

A spruce, 14 ins. in diam., bears S. 81° W., 19 lks. dist., mkd. $\frac{1}{4}$ S24 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

T37S R9W

$\frac{1}{4}$ S13

S24

1969

Deposit the original stone alongside the corner.

CHAINS

The cor. is located at N. end of grassy flat and at timber edge that bears E. and W. approx. 10 chs. dist. W. of trail road that bears N. and S. in scattered pine growth.

At the cor. of secs. 11, 12, 13 and 14, marked with a volcanic stone 16x10x5 ins., firmly set and plainly mkd. with 4 notches on the S. and 1 on the E. edge.

A spruce, 14 ins. in diam., bears N. 84° 15' E., 107 lks. dist., mkd. T37S R9W S12 BT. (Same as record.)

A spruce, 16 ins. in diam., bears S. 31° E., 76 lks. dist., mkd. T37S R9W S13 BT. (Same as record.)

A spruce, 16 ins. in diam., bears S. 29° 45' W., 143 lks. dist., mkd. T37S R9W S14 BT. (Same as record.)

A spruce, 16 ins. in diam., bears N. 41° W., 109 lks. dist., mkd. T37S R9W S11 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground with a steel fence post to W. brass cap mkd.

T37S R9W

S11|S12

S14|S13

1969

Deposit the original stone alongside the corner.

The cor. is located on N. slope of hill in scattered pine growth approx. 6 chs. dist. S. of draw that drains E.

At the 1/4 sec. cor. of secs. 11 and 12, marked with a sandstone 16x10x9 ins., firmly set and plainly mkd. 1/4 on W. face.

From which,

A spruce, 24 ins. in diam., bears N. 16° E., 377 lks. dist., mkd. 1/4 S12 BT. (Record N. 15° 15' E., 371 lks. dist.)

A balsam, 8 ins. in diam., bears N. 20° 30' W., 292 lks. dist., mkd. 1/4 S11 BT. (Record N. 22° 30' W., 247 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3½ ft. base, 1½ ft. high, to W. Brass cap mkd.

T37S R9W

½

S11|S12

1969

Remonumentation of Corners in T. 37 S., R. 9 W.

CHAINS

Deposit the original stone alongside the corner.

The cor. is located on gentle E. slope of hill $3\frac{1}{2}$ chs. dist. N. of small wash, 15 lks. wide, 2 ft. deep, that drains E. 2 chs. dist. W. of draw that drains S. at the cor. of old fence that bears S. and E.

At the cor. of secs. 22, 23, 26 and 27, marked with a limestone 16x12x6 ins., firmly set and plainly mkd. with 2 notches on the S. and E. edges.

From which,

A spruce, 20 ins. in diam., bears N. $41^{\circ} 30'$ E., 25 lks. dist., mkd. T37S R9W S23 BT. (Record N. $41^{\circ} 30'$ E., 248 lks. dist.)

A spruce, 18 ins. in diam., bears S. 30° E., 25 lks. dist., mkd. T37S R9W S26 BT. (Same as record.)

A balsam, 10 ins. in diam., bears S. $47^{\circ} 15'$ W., 20 lks. dist., mkd. T37S R9W S27 BT. (Same as record.)

A balsam, 15 ins. in diam., bears N. 29° W., 58 lks. dist., mkd. T37S R9W S22 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 12 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T37S R9W

S22|S23

S27|S26

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle NE. slope of hill in thick spruce, balsam and aspen growth.

At the cor. of secs. 14, 15, 22 and 23, marked with a volcanic stone 24x10x5 ins., firmly set and plainly mkd. with 3 notches on the S. and 2 on the E. edge.

From which,

A spruce, 30 ins. in diam., bears N. $6^{\circ} 15'$ E., 89 lks. dist., mkd. T37S R9W S14 BT. (Same as record.)

A balsam, 15 ins. in diam., bears S. $4^{\circ} 15'$ E., 362 lks. dist., mkd. T37S R9W S23 BT. (Same as record.)

A spruce, 18 ins. in diam., bears S. 53° W., 117 lks. dist., mkd. T37S R9W S22 BT. (Same as record.)

Remonumentation of Corners in T. 37 S., R. 9 W.

CHAINS

A spruce, 30 ins. in diam., bears N. 12° W., 231 lks. dist., mkd. T37S R9W S15 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T37S R9W

S15	S14
S22	S23

1969

Deposit the original stone alongside the corner.

The cor. is located on gentle E. slope of hill in scattered pine growth at the W. edge of grassy meadow and timber line that bears N. and S.

At the $1/4$ sec. cor. of secs. 14 and 23, marked with a volcanic stone $17 \times 14 \times 10$ ins., firmly set and plainly mkd. $1/4$ on N. face.

From which,

A spruce, 22 ins. in diam., bears N. 2° W., 176 lks. dist., mkd. $1/4$ S14 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, to N. Brass cap mkd.

T37S R9W

$\frac{1}{4}$	S14
	S23

1969

Deposit the original stone alongside the corner.

The cor. is located at N. end of grassy flat 1 ch. S. of timber line that bears E. and W.

At the $1/4$ sec. cor. of secs. 14 and 15, marked with a volcanic stone $16 \times 12 \times 4$ ins., firmly set and plainly mkd. $1/4$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 20 ins. in the ground and in a collar of stone to brass cap mkd.

T37S R9W

$\frac{1}{4}$	S15	S14
---------------	-----	-----

1969

Remonumentation of Corners in T. 37 S., R. 9 W.

CHAINS

Deposit the original stone alongside the corner.

The cor. is located near center of large grassy flat approx. 10 chs. dist. W. of State Highway 55 that bears N. and S. about 8 chs. dist. E. of timber line that bears N. and S.

At the 1/4 sec. cor. of secs. 11 and 14, marked with a trachyte stone 18x10x6 ins., firmly set in a mound of stone and plainly mkd. 1/4 on N. face.

From which,

A spruce, 12 ins. in diam., bears S. 64° W., 109 lks. dist., mkd. 1/4 S14 BT. (Same as record.)

A spruce, 8 ins. in diam., bears N. 70° 15' W., 102 lks. dist., mkd. 1/4 S11 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to N. Brass cap mkd.

T37S R9W

½ $\frac{S11}{S14}$
1969

Deposit the original stone alongside the corner.

The cor. is located on nearly level ridge top that bears N. and S. 1 ch. E. of timber line that bears N. and S.

At the 1/4 sec. cor. of secs. 15 and 22, marked with a volcanic stone 16x14x5 ins., firmly set and plainly mkd. 1/4 on N. face.

From which,

A spruce, 15 ins. in diam., bears N. 17° E., 172 lks. dist., mkd. 1/4 S15 BT. (Record N. 12° 15' E., 172 lks. dist.)

A spruce, 20 ins. in diam., bears S. 22° E., 97 lks. dist., mkd. 1/4 S22 BT. (Same as record.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T37S R9W

½ $\frac{S15}{S22}$
1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 37 S., R. 9 W.

CHAINS

The cor. is located on gentle SE. slope of hill in scattered pine growth.

At the 1/4 sec. cor. of secs. 20 and 21, marked with a sandstone 15x8x6 ins., firmly set and plainly mkd. 1/4 on W. face.

From which,

A balsam (dead), 36 ins. in diam., bears N. 74° 45' E., 84 lks. dist., mkd. 1/4 S21 BT. (Same as record.)

There is no remaining evidence of the aspen bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T37S R9W

½
S20|S21

1969

From which I mark

An aspen, 12 ins. in diam., bears S. 47° W., 80 lks. dist., mkd. 1/4 S20 BT.

The cor. is located on SW. slope of hill in thick aspen growth approx. 4½ chs. dist. S. of trail road that bears E. and W.

At the cor. of secs. 19, 20, 29 and 30, marked with a sandstone 30x15x12 ins., firmly set and plainly mkd. with 5 notches on the E. and 2 on the S. edge.

There is no remaining evidence of the four original aspen bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3 ft. base, 1½ ft. high, to W. Brass cap mkd.

T37S R9W

S19|S20
S30|S29

1969

From which I mark

An aspen, 8 ins. in diam., bears N. 30° E., 135 lks. dist., mkd. T37S R9W S20 BT.

Remonumentation of Corners in T. 37 S., R. 9 W.

CHAINS

An aspen, 14 ins. in diam., bears S. 6° 30' E., 201 lks. dist., mkd. T37S R9W S29 BT.

An aspen, 8 ins. in diam., bears S. 13° W., 205 lks. dist., mkd. T37S R9W S30 BT.

An aspen, 12 ins. in diam., bears N. 40° W., 144 lks. dist., mkd. T37S R9W S19 BT.

Deposit the original stone alongside the corner.

The cor. is located in small clearing surrounded by aspen growth approx. 8 chs. dist. E. of trail road that bears N. and S.

Remonumentation of Corners in T. 37 S., R. 13 W.

Township 37 South, Range 13 West, Salt Lake Meridian, is located partially within the Dixie National Forest. The following corner was established by A. J. Stewart Jr. in 1873.

At the 1/4 sec. cor. of secs. 31 and 32, marked with a granite stone 18x12x7 ins., firmly set and plainly mkd. 1/4 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 6 ins. in the ground and in a mound of stone 3½ ft. base to brass cap mkd.

T37S R13W

½
S31|S32

1969

The original stone in mound alongside the corner.

The cor. is located on E. slope of hill in thick oak and mahogany growth 40 lks. dist. S. of top of spur projecting E. approx. 15 chs. dist. S. of trail road in canyon.

Remonumentation of Corners in T. 37 S., R. 14 W.

Township 37 South, Range 14 West, Salt Lake Meridian, is located partially within the Dixie National Forest. The following corners were established by A. J. Stewart Jr. in 1873.

At the cor. of secs. 35 and 36 on the S. bdy. of the Tp., marked with a granite stone 20x12x10 ins., firmly set and plainly mkd. with 5 notches on the W. and 1 on the E. edge.

Remonumentation of Corners in T. 37 S., R. 14 W.

CHAINS

From which,

A pinon pine, 15 ins. in diam., bears N. 19° 30' E.,
25 lks. dist., mkd. T37S R14W S36 BT. (Record N.
25° E., 23 lks. dist.)

A pinon pine, 14 ins. in diam., bears S. 24° E.,
45 lks. dist., mkd. T38S R14W S1 BT. (Record S.
35° E., 52 lks. dist.)

A cedar, 12 ins. in diam., bears S. 47° 30' W.,
112 lks. dist., mkd. T38S R14W S2 BT. (Record S.
45° W., 100 lks. dist.)

A cedar, 14 ins. in diam., bears N. 47° 30' W.,
157 lks. dist., mkd. T37S R14W S35 BT. (Record N.
47° 30' W., 173 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20
ins. in the ground and in a collar of stone to brass
cap; raise a mound of stone 3½ ft. base, 1½ ft. high,
to N. Brass cap marked.

T37S R14W

S35|S36

1969

Deposit the original stone alongside the corner.

The cor. is located on steep, rocky S. slope of hill
in scattered oak, mahogany, cedar and pinon growth
75 lks. dist. N. of wash in draw, 15 lks. wide, 2
ft. deep, that drains E.

At the 1/4 sec. cor. of secs. 35 and 36 as determined by
an old mound of stone with no visible markings.

From which,

A pinon pine, 7 ins. in diam., bears N. 87° 30' E.,
53 lks. dist., mkd. 1/4 S BT. (Same as record.)

A pinon pine, 12 ins. in diam., bears N. 76° W.,
30 lks. dist., mkd. 1/4 S BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 8 ins.
in the ground and in a mound of stone 4 ft. base to brass
cap mkd.

T37S R14W

S35|S36

1969

The cor. is located on gentle N. slope of hill in
scattered cedar and pinon growth 48 lks. dist. S.
of old 4 strand fence that bears N. 35° W. and S.
35° E. approx. 20 chs. dist. S. of trail road that
bears E. and W.

Blank

Page

CERTIFICATE OF SURVEY

(I) ~~(XX)~~,

Ferrel D. Reynolds

, HEREBY


CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day

of February, 1961, (I) ~~(XX)~~ have remonumented corners in T. 29 S., R. 4 E. T. 33 S., R. 3 E., Tps. 34 S., Rs. 2 and 8 W., Tps. 35 S., R. 3, 6, 7 and 8 W. Tps. 36 S., Rs. 7 and 9 W., and Tps. 37 S., Rs. 9, 13 and 14 W.

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(XX)~~ and under (my) ~~(XX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 21, 1970

(Date)



Surveying Technician

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date JUN 2 1970

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of corners in T. 29 S., R. 4 E., T. 3 R. 3 E., Tps. 34 S., Rs. 2 and 8 W., Tps. 35 S., Rs. 3, 6, 7 and 8 W., Tps. 36 Rs. 7 and 9 W., and Tps. 37 S., Rs. 9, 13 and 14 W., Salt Lake Meridian, Utah

executed by Ferrel D. Reynolds, Surveying Technician

having been critically examined and found correct, are hereby approved.

DEC 1 1970

(Date)



(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

, is a true copy of the original field notes.

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

REMONUMENTATION OF CORNERS

IN

TOWNSHIP 1 NORTH, RANGE 6 WEST

TOWNSHIP 2 NORTH, RANGE 6 WEST

TOWNSHIP 6 SOUTH, RANGE 7 WEST

OF THE

UINTAH MERIDIAN, UTAH

RECEIVED
BUREAU OF LAND MGMT.
DEC 23 PM 1:56

Of the UINTAH

Meridian,

In the State of UTAH

EXECUTED BY

Ferrel D. Reynolds

Surveying Technician

Under special instructions dated February 15, 19 61, which provided for the surveys
included under Group Number 447, approved February 16, 1961,
and assignment instructions dated May 26, 19 69.

Survey commenced June 4, 19 69

Survey completed June 25, 19 69

INDEX DIAGRAM

Township _____, Range _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION
CORNER MONUMENTS

Tp. 1 N. R. 6 W. Mer. UINTAH

6	3 5	4	3	2	1
7	2 8	9	10	11	12
18	2 17	16	15	14	13
19	20	1 21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 2 N. R. 6 W. Mer. UINTAH

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
4 30	29	28	27	26	25
31	4 32	33	34	35	36

Tp. 6 S. R. 7 W. Mer. UINTAH

6	5	4	3	2	1
7	8	9	6 10	6 11	5 12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Blank

Page

Remonumentation of Corner

CHAINS

The following field notes are those of the remonumentation of certain identified corners selected by the U. S. Forest Service as being located in or controlling the boundaries of Forest Service lands, situated in the Ashley National Forest. A Forester's Compass was used to determine the bearings of new corner accessories. The mean magnetic declinations were found to be as follows:

T. 1 N., R. 6 W., Uintah Meridian, 15° 40' E.
 T. 2 N., R. 6 W., " " 15° 40' E.
 T. 6 S., R. 7 W., " " 15° 40' E.

The position of each corner was marked by the original monument or determined from corner accessories recorded in the survey records. The monumentation was requested by and accomplished in cooperation with the Forest Service.

Remonumentation of Corners in T. 1 N., R. 6 W.

Township 1 North, Range 6 West, Uintah Meridian, is located partially within the Ashley National Forest. Surveyed by Harvey D. Heist in 1903.

At the cor. of secs. 16, 17, 20 and 21, marked with a sandstone 18x14x8 ins., firmly set and plainly mkd. with 4 notches on E. and 3 on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T1N R6W

S17	S16
S20	S21

1969

Deposit original stone alongside the cor. and raise a mound of stone W. of cor.

This cor. is located on N. edge of small sagebrush flat at the cor. of 5 strand fence which bears N. and W. in sage and chokecherry growth, no timber.

At the ¼ sec. cor. of secs. 8 and 17, marked with a trachyte stone, 18x12x6 ins., firmly set and plainly mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

Remonumentation of Corners in T. 1 N. R. 6 W.

CHAINS

T1N R6W

$$\frac{1}{4} \begin{array}{r} S8 \\ S17 \\ 1969 \end{array}$$

Deposit the original stone alongside the cor.

This cor. is located 2 chs. dist. E. of the top of rocky spur projecting N. approx. 900 ft. above Rock Creek that drains S.

At the cor. of secs. 7, 8, 17 and 18, marked with a trachyte stone 15x10x6 ins., firmly set and plainly mkd. with 5 notches on E. and 4 on S. edge.

From which,

A pine, 20 ins. in diam., bears S. 28° E., 97 lks. dist., mkd. T1N R6W S17 BT. (Same as record)

A pine, 24 ins. in diam., bears N. 88° W., 125 lks. dist., mkd. T1N R6W S7 BT. (Same as record)

There is no remaining evidence of the other two original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 15 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

T1N R6W

$$\begin{array}{r} S7|S8 \\ S18|S17 \end{array}$$

1969

Deposit the original stone alongside the cor.

This cor. is located on SE. slope of hill 350 lks. dist. N. of small creek, 5 lks. wide, 2 ft. deep, that drains N. 40° E. in dense aspen and pine growth.

At the cor. of secs. 5, 6, 7 and 8, marked with a sandstone, 36x8x8 ins., firmly set and plainly mkd. with 5 notches on the S. and E. edges.

There is no remaining evidence of original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone, 3½ ft. base, 1½ ft. high, to W. Brass cap mkd.

T1N R6W

$$\begin{array}{r} S6|S5 \\ S7|S8 \end{array}$$

1969

CHAINS

Re monumentation of Corners in T. 1 N., R. 6 W.

From which I mark

A pine, 12 ins. in diam., bears S. 87° E., 255 lks. dist., mkd. T1N R6W S8 BT.

Deposit the original stone alongside the cor.

This cor. is located on NW. slope of hill 40 lks. S. of dim trail road that bears N. 34° E. and S. 34° W., 100 lks. E. of aspen grove and 5 chs. N. of top of spur projecting E. 3 chs. S. of draw that drains N. 34° E.

At the closing cor. of secs. 5, and 6 on the N. bdy. of the Tp., marked with a trachyte stone, 24x10x5 ins., firmly set and plainly mkd. with 5 notches on E. and 1 on W. edge, CC on S. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a mound of stone, to brass cap. Raise a mound of stone, 3½ ft. base, 1½ ft. high to S.

T2N R6W

S31

S6 | S5

CC

T1N R6W

1969

Deposit the original stone alongside the cor.

This cor. is located at edge of sharp descend into Rock Creek at edge of small grove of aspen.

Remonumentation of Corners in T. 2 N., R. 6 W.

Township 2 North, Range 6 West, Uintah Meridian, is located within the Ashley National Forest. The S. bdy. was surveyed by H. D. Heist in 1903, the W. bdy. and subdivisional lines by James F. Trotter in 1903.

At the cor. of secs. 32 and 33 on the S. bdy. of the Tp., mkd. with a sandstone, 20x10x8 ins., firmly set but dimly mkd. with 4 notches on E. and 2 on W. edge,

From which,

A pine, 7 ins., in diam., bears N. 31° E., 22 lks. dist., mkd. T2N R6W S33 BT. (Same as record)

A pine, 8 ins. in diam., bears N. 52° W., 37 lks. dist., mkd. T2N R6W S32 BT. (Same as record)

At the cor. point

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 10 ins. in the ground and in a mound of stone 4 ft. base to brass cap mkd.

T2N R6W

S32|S33

S4

T1N R6W

1969

Deposit the original stone alongside the cor.

This cor. is located on steep broken W. slope of hill in scattered cedar and pine growth.

At the cor. of secs. 19, 24, 25 and 30, on the west bdy. of the Tp., mkd. with a trachyte stone, 18x12x6 ins., firmly set and plainly mkd. with 4 notches on the N. and 2 notches on S. edge.

There are remains of original bearing trees (dead) scattered around area.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W. Brass cap mkd.

T2N

R7W R6W

S24|S19

S25|S30

1969

Deposit the original stone alongside the cor.

From which I mark

A pine, 4 ins. in diam., bears N. 77° E., 34 lks. dist., mkd. BT.

A pine, 6 ins. in diam., bears S. 51° E., 41 lks. dist., mkd. T2N R6W S30 BT.

A pine, 4 ins. in diam., bears S. 43° W., 19 lks. dist., mkd. BT.

An aspen, 6 ins. in diam., bears N. 20° W., 55 lks. dist., mkd. T2N R7W S24 BT.

This cor. is located on steep W. slope of hill 2 chs. W. of jeep trail that bears N. and S. approx. 4 chs. dist. E. of canyon that drains S. 45° W. into Rock Creek in dense aspen and pine growth.

At the cor. of secs. 29, 30, 31 and 32, marked with a sandstone, 20x8x5 ins., firmly set and plainly mkd. with 5 notches on E. and 1 on S. edge.

There is no remaining evidence of original aspen bearing trees.

Remonumentation of Corners in T. 2 N., R. 6 W.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground and raise a mound of stone $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high to W. Brass cap mkd.

T2N R6W

S30|S29

S31|S32

1969

Deposit the original stone alongside the iron post. From which I mark

A pine, 12 ins. in diam., bears N. 12° E., 59 lks. dist., mkd. T2N R6W S29 BT.

This cor. is located on E. slope of small hill 1 ch. N. of edge of aspen grove that bears E. and W.; also the edge of steep descent into Rock Creek.

Remonumentation of Corners in T. 6 S., R. 7 W.

Township 6 South, Range 7 West, Uintah Meridian, is located within the Ashley National Forest. The following corners were established by S. P. Stewart and C. S. Jarvis in 1905.

At the cor. of secs. 2, 3, 10 and 11, marked with a sandstone, $18 \times 14 \times 4$ ins., firmly set and plainly mkd. with 5 notches on the S. and 2 on the E. edge.

From which,

A red pine, 10 ins. in diam., bears N. 64° E., 53 lks., mkd. T6S R7W S2 BT. (Same as record.)

A red pine, 14 ins. in diam., bears S. $18^{\circ} 10'$ E., 82 lks. dist., mkd. T6S R7W S11 BT. (Same as record)

A red pine, 16 ins. in diam., bears S. $81^{\circ} 30'$ W., 91 lks. dist., mkd. T6S R7W S10 BT. (Same as record)

A pinon pine, 12 ins. in diam., bears N. $42^{\circ} 30'$ W., 41 lks. dist., mkd. T6S R7W S3 BT. (Same as record.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 18 ins. in the ground and in a collar of stone to brass cap mkd.

T6S R7W

S3|S2

S10|S11

1969

Deposit the original stone alongside the corner.

Remonumentation of Corners in T. 6 S., R. 7 W.

CHAINS

This cor. is located on steep W. slope of hill approx. 15 chs. dist. E. of small creek in canyon that drains N. in cedar and pine growth.

At the 1/4 sec. cor. of secs. 3 and 10, marked with a sandstone, 16x8x7 ins., firmly set and plainly mkd. 1/4 on N. face.

From which,

A pinon pine, 8 ins. in diam., bears S. 55° W., 37 lks. dist., mkd. 1/4 S10 BT. (Record is S. 26° W., 28 lks. dist.)

A pinon pine, 6 ins. in diam., bears N. 30° W., 34 lks. dist., mkd. 1/4 S3 BT. (Record is N. 52° 10' E., 39 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone, 3½ ft. base, 1½ ft. high, to N. Brass cap mkd.

T6S R7W

½ $\frac{S3}{S10}$

1969

Deposit the original stone alongside the corner.

This cor. is located on steep NW. slope of hill in scattered pine growth.

At the cor. of secs. 3, 4, 9 and 10, marked with a sandstone, 16x10x7 ins., firmly set and plainly mkd. with 5 notches on S. and 3 on E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. in diam., 24 ins. in the ground and raise a mound of stone 3½ ft. base, 1½ ft. high, to W. Brass cap mkd.

T6S R7W

$\frac{S4|S3}{S9|S10}$

1969

Deposit the original stone alongside the corner.

This cor. is located on old N-S fence line 378 lks. N. and 430 lks. W. of road in Indian Creek Canyon that bears N. 50° E. and S. 50° W. in sagebrush growth, no timber.

CERTIFICATE OF SURVEY

I, Ferrel D. Reynolds, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 15th day of February, 19 61,
I have remonumented corners in T. 1 N., R. 6 W., T. 2 N., R. 6 W., T. 6 S.,
R. 7 W.,

of the Uintah Meridian, in the State of Utah, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

February 12, 1970

(Date)

Ferrel D. Reynolds
~~(Signature)~~

Surveying Technician

(Date)

(Cadastral Surveyor)

SUBMITTED FOR APPROVAL
Date JUN 2 1970

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumentation of corners in T. 1 N., R. 6 W.,
T. 2 N., R. 6 W., T. 6 S., R. 7 W., Uintah Meridian, Utah

executed by Ferrel D. Reynolds, Surveying Technician

having been critically examined and found correct, are hereby approved.

DEC 1 1971

(Date)

Clark F. Humm
~~(Chief, Division of Engineering)~~

Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~

~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Engineering)

Blank Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE

KOLOB GUIDE MERIDIAN (WEST BOUNDARY)

AND THE SUBDIVISIONAL LINES,

WITH THE SUBDIVISION OF SECTION 30

TOWNSHIP 39 SOUTH, RANGE 10 WEST

RECEIVED
UTAH STATE OFFICE
JUL 25 PM 12:43
DEPT. OF INTERIOR
BUREAU OF LAND MGMT.

Of the SALT LAKE Meridian,

In the State of UTAH

EXECUTED BY

SHIRLEY B. HJELLUM

SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated April 14, 1970, which provided for the surveys
Supplemental Special Instructions October 23, 1973
included under Group Number 527, approved April 23, 1970,
and assignment instructions dated October 23, 1973.

Survey commenced October 25, 1973

Survey completed November 7, 1973

INDEX DIAGRAM

Township 39 South, Range 10 West,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
4 30 1	6 5	29	28	27	26
25	24	23	22	21	20
31	32	33	34	35	36

NW 1/4 of sec. 30 . . . pp. 7 - 8

Township 39 South, Range 10 West
Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of portions of the Kolob Guide Meridian (west boundary) and the subdivisional lines, with the subdivision of section 30, Township 39 South, Range 10 West, Salt Lake Meridian, Utah.

The Kolob Guide Meridian through Township 39 South (west boundary) was originally surveyed by U. S. Deputy Surveyor A. D. Ferron in 1877 and resurveyed by U. S. Deputy Surveyor A. P. Hanson in 1899. Surveyor Hanson also made the survey of the subdivisional lines in 1899. Gilbert V. Olson, Cadastral Surveyor, partially subdivided sections 30 and 31 in 1970.

These surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, the Special Instructions dated April 14, 1970, and the Supplemental Special Instructions dated October 23, 1973.

The directions of the lines were determined by polaris observations, carried forward by angulation, and confirmed by succeeding a.m. and p.m. altitude observations of the sun. They refer to the true meridian. The Hewlett-Packard 3800, an electronic distance measuring instrument, was used to obtain all distances. Certain items of topography were omitted.

Prior to restoration of any corners, all necessary lines of the original surveys were retraced and a diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The data furnished with the Special Instructions gives the geographic position of the 1/4 section corner of sections 30 and 31 as:

Latitude: 37° 22.0' N.
Longitude: 113° 00.0' W.

The observed mean magnetic declination is 14½° E.

Dependent Resurvey of a Portion of the
Kolob Guide Meridian (West Boundary)
Township 39 South, Range 10 West
Salt Lake Meridian, Utah

Reestablishment of the Resurvey Executed by
Andrew P. Hanson, U.S. Deputy Surveyor, in 1899

Beginning at the cor. of secs. 13 and 24, T. 39 S., R. 11 W., monumented with a lava stone, 26x10x8 ins., projecting 4 ins. above the ground, and in a mound of stone, 3 ft. base to top, mkd. with 3 notches on the N. and 3 notches on the S. edges.

At the corner point

Dependent Resurvey of a Portion of the
Kolob Guide Meridian (West Boundary)
Township 39 South, Range 10 West
Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T39S
R11W R10W
 $\frac{S}{S} \frac{13}{24} | S 30$

1973

Bury the original corner stone alongside the iron post.

This corner is located on an E. slope in dense oak brush, 17 ft. S. of center line of a trail road bearing generally E. and W.

From this corner, the closing cor. of secs. 30 and 31, T. 39 S., R. 10 W., bears S. $4^{\circ} 50'$ W., 16.68 chs. dist., monumented with a brass cap, 4 ins. diam., set in concrete 10 ins. square, projecting 6 ins. above the ground, mkd.

Washington
County
 $\frac{S}{S} \frac{30}{31}$

This corner was established by the Washington County Surveyor and is accepted as the best available evidence of the original corner position.

From this same corner a Geological Survey Vertical Bench Mark, bears S. $61^{\circ} 12'$ E., 42.01 chs. dist., monumented with a standard brass cap, $3\frac{1}{2}$ ins. diam., firmly cemented into a lava rock, mkd. Reference Mark, V. Elev., 7890, and an arrow pointing northwesterly, and the northeast corner of the National Park Service, Zion National Park, Lava Point Lookout Tower bears S. $60^{\circ} 20'$ E., 42.32 chs. dist.

N. $0^{\circ} 24'$ W., on the W. boundary of the township.

Over rolling terrain, through timber and medium undergrowth, and occasional rock slides.

23.20

Point for the $\frac{1}{4}$ sec. cor. of sec. 30 at midpoint in latitude between adjacent closing cors. and on the Kolob Guide Meridian.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T39S
R11W R10W
 $\frac{1}{4} | S 30$

1973

from which

A white fir, 4 ins. diam., bears N. $43\frac{1}{4}^{\circ}$ E., 40 lks. dist., mkd. X BT.

Dependent Resurvey of a Portion of the
Kolob Guide Meridian (West Boundary)
Township 39 South, Range 10 West
Salt Lake Meridian, Utah

CHAINS

A white fir, 4 ins. diam., bears S. $78\frac{1}{4}^{\circ}$ E., 102
lks. dist., mkd. X BT.

This corner is located on nearly level ground, in dense
timber.

- 39.76 The $1/4$ sec. cor. of sec. 13, T. 39 S., R. 11 W., monu-
mented with a black lava stone, $27 \times 10 \times 8$ ins., painted
white, set in a mound of stone, 4 ft. base to top, plainly
mkd. $1/4$ on the W. face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over an
X chiseled on top of a lava boulder, and in a mound of
stone, 4 ft. base to top, with brass cap mkd.

T39S
R11W R10W
 $\frac{1}{4}$
S 13

1973

Deposit the original corner stone alongside the iron
post.

from which

An X chiseled on SW. face of a black lava boulder,
 $12 \times 10 \times 8$ ft., bears N. $41\frac{1}{4}^{\circ}$ E., 14 lks. dist.

An X chiseled on N. face of a black lava boulder,
 $15 \times 10 \times 8$ ft., bears S. 5° E., $11\frac{1}{2}$ lks. dist.

This corner is located in a rock slide 200 ft. E. of
and 140 ft. lower than the top of a plateau.

N. $0^{\circ} 05'$ E., beginning new measurement.

Continue over rolling terrain, through timber and medium
undergrowth, with occasional rock slides.

- 3.35 Point for the N $1/16$ sec. cor. of sec. 30 only, not
monumented.
- 23.26 The closing cor. of secs. 19 and 30, monumented with a
black lava stone, $26 \times 9 \times 6$ ins., projecting 8 ins. above
the ground, and set in a mound of stone, 2 ft. base, 1
ft. high, mkd. with 4 notches on the N. edge, 2 notches
on the S. edge, and CC on the E. face.
- At the corner point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins.
in the ground to bedrock, and in a mound of stone, 4 ft.
base to top, with brass cap mkd.

T39S
R11W R10W
S 13 $\frac{S 19}{S 30}$ CC

1973

Dependent Resurvey of a Portion of the
Kolob Guide Meridian (West Boundary)
Township 39 South, Range 10 West
Salt Lake Meridian, Utah

CHAINS

Deposit the original corner stone alongside the iron post.
from which

A white fir, 4 ins. diam., bears N. $63\frac{1}{2}^{\circ}$ E., 38
lks. dist., mkd. X BT.

A white fir, 4 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ E., 21
lks. dist., mkd. X BT.

This corner is located on a NE. slope, in dense timber.

From this closing corner, the cor. of secs. 12 and 13,
T. 39 S., R. 11 W., bears N. $0^{\circ} 05'$ E., dist. not meas-
ured, monumented with a black lava stone, $24 \times 12 \times 7$ ins.,
projecting 6 ins. above the ground, mkd. with 4 notches
on the S. edge, and 2 notches on the N. edge, set in a
mound of stone, 3 ft. base to top. This monument was
used by the Washington County Surveyor and Private Sur-
veyors Coon and King, Cedar City, Utah, as the sec. cor.
of secs. 12 and 13, when they subdivided in these secs.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 39 South, Range 10 West
Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
Andrew P. Hanson, U.S. Deputy Surveyor, in 1899

From the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented
with an iron post, $2\frac{1}{2}$ ins. diam., projecting 3 ins.
above the ground, substantiated by a small mound of stone
N., established by Gilbert V. Olson, Cadastral Surveyor,
in 1970, with brass cap mkd.

T39S R10W

$\frac{1}{4}$ $\frac{S 19}{S 30}$

1970

S. $89^{\circ} 50'$ W., between secs. 19 and 30.

Over rugged mountainous terrain, through timber, occa-
sional dense oak brush, and rock slides.

80.692 Point for the $\frac{1}{16}$ sec. cor. of secs. 19 and 30.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T39S R10W

$\frac{1}{16}$ $\frac{S 19}{S 30}$ 120

1973

This corner is located on a NE. slope among dense oak
brush.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 39 South, Range 10 West
Salt Lake Meridian, Utah

CHAINS

100.865	Point for the 140-1/16 sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 2 ft. base to top, with brass cap mkd. T39S R10W 1/16 $\frac{S\ 19}{S\ 30}$ 140 1973 This corner is located on a steep SW. slope.
121.038	Point for the 160-1/16 sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T39S R10W 1/16 $\frac{S\ 19}{S\ 30}$ 160 1973 This corner is located on a steep W. slope among dense oak brush.
160.577	Intersect the Kolob Guide Meridian (W. boundary), at the closing cor. of secs. 19 and 30, hereinbefore described. From this closing cor., the 1/4 sec. cor. of sec. 13, T. 39 S., R. 11 W., bears S. 0° 05' W., 23.26 chs. dist., hereinbefore described.
Subdivision of Section 30	
	From the 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, set, mkd. and witnessed as described in the field notes of the subdivision of sec. 30, surveyed by Gilbert V. Olson, Cadastral Surveyor, in 1970. N. 0° 04' W., on the N. and S. center line of sec. 30. Over rugged mountainous terrain, through timber and medium undergrowth.
0.60	Drain, course E.
12.00	Top of ridge, bears E. and W.
14.80	Trail road, bears N. 76° E. and S. 58° W., begin descent over a steep N. slope.
23.35	Enter dense timber and medium undergrowth, edge bears E. and W., descend into a canyon.
40.05	Point for the center 1/4 sec. cor. of sec. 30, at the intersection with the E. and W. center line. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Township 36 South, Range 5 West, Salt Lake Meridian, Utah

CHAINS

T. 36 S., R. 5 W.

History of Surveys

Surveyed by Retr. or Resurveyed by

NORTH BOUNDARY (Seventh Standard Parallel South)

All	T. C. Bailey	1874		
E. 10.08 chs.			E. Bird	1925

SOUTH BOUNDARY

W. 5 miles	T. C. Bailey	1874		
			A. J. Stewart	1883
E. 1 mile	A. J. Stewart	1883		
			E. Bird	1925
S. bdy., Sec. 33			A. B. Lewis	1897

EAST BOUNDARY

N. 3 miles	T. C. Bailey	1874		
			E. Bird	1925
S. 3 miles	E. Bird	1925		

WEST BOUNDARY (Panguitch Guide Meridian)

All	T. C. Bailey	1874		
All			A. J. Stewart	1883
All			A. B. Lewis	1897

SUBDIVISIONS

All except portions of secs. 24, 25 and 36				
	T. C. Bailey	1874		
Portions Secs. 24, 25 and all 36				
	E. Bird	1925		

The following field notes are those of the dependent re-survey of a portion of the west boundary, a portion of the south boundary and a portion of the subdivisional lines of Township 36 South, Range 5 West. The dependent resurvey was executed in accordance with the specifications as set the Special Instructions dated May 5, 1972, Group No. 535, Utah.

The lines of this dependent resurvey were determined by altitude observations of the sun and hour angle observations of Polaris and carried forward with sustained angulation. The distances were determined by chaining and triangulation.

Before restoring the corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners, or other calls of the original field note record. The rules of proportionate measurement were applied to ascertain the position of the lost corners, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner.

The geographic position for the southeast corner of the Section 35 is at Latitude 37° 37' 45" N. and Longi-

Subdivision of Section 30
Township 39 South, Range 10 West
Salt Lake Meridian, Utah

CHAINS

Over rugged mountainous terrain, through timber and moderate undergrowth.

39.66 The center 1/4 sec. cor. of sec. 30.

200.21 Intersect the Kolob Guide Meridian (W. boundary), at the 1/4 sec. cor. of sec. 30, hereinbefore described.

From this corner, the 1/4 sec. cor. of sec. 13, T. 39 S., R. 11 W., bears N. 0° 24' W., 16.56 chs. dist., hereinbefore described.

From the 120-1/16 sec. cor. of secs. 19 and 30,

S. 0° 04' E., between lots 4 and 5.

Descend into Kolob Creek Canyon.

19.951 Point for the 120-N 1/16 sec. cor. of sec. 30, inaccessible, not monumented. Point falls north of Kolob Creek.

S. 89° 52' W., along the E. and W. center line of the NW 1/4 of sec. 30, between lots 5 and 12.

20.175 Point for the 140-N 1/16 sec. cor. of sec. 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T39S R10W
N $\frac{1/16}{S 30}$ 140

1973

This corner is located on a steep E. slope, in oak brush.
from which

The north end of a bulldozed trail extending southerly, bears S. 43½° W., 14.82 chs. dist.

Various points along the center of Kolob Creek, bears S. 13¼° E., 6.00 chs. dist.; S. 4 3/4° W., 8.97 chs. dist.; and S. 48 3/4° W., 14.12 chs. dist.

N. 0° 03' W., between lots 5 and 6.

19.942 The 140-1/16 sec. cor. of secs. 19 and 30.

From the 140-N 1/16 sec. cor. of sec. 30.

S. 89° 52' W., along the E. and W. center line of the NW 1/4 of sec. 30, between lots 6 and 11.

20.175 Point for the 160-N 1/16 sec. cor. of sec. 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 30
Township 39 South, Range 10 West
Salt Lake Meridian, Utah

CHAINS

T39S R10W
1/16
N $\frac{1/16}{S 30}$ 160

1973

This corner is located on a steep SW. slope in dense oak brush.

From this corner, a point in the center of Kolob Creek bears S. $2\frac{1}{4}^{\circ}$ E., 5.02 chs. dist.

N. $0^{\circ} 03'$ W., between lots 6 and 7.

19.932 The 160-1/16 sec. cor. of secs. 19 and 30.

General Description

The area surveyed and resurveyed within section 30, Township 39 South, Range 10 West, is mountainous and varies in elevation from approximately 6000 ft. in the bottom of Kolob Canyon in the northeast corner of the section to approximately 7890 ft. in elevation in the southwest corner of the section. There are some steep canyons within this section, with numerous rock slides. The soil varies from rocky to sandy. The vegetation consists of sage brush, oak brush, pinon, ponderosa pine, and douglas fir, with sparse native grasses.

There are numerous summer homes situated just west of the section.

The southeast corner of section 30 is approximately $13\frac{1}{2}$ air miles mostly north, but a little east of the village of Springdale, Utah, but approximately 42 miles via a paved and graveled road from Springdale. Access within the section is limited to a dirt vehicle trail, which requires 4 wheel drive on some steep areas.

Drainage within section 30 is generally easterly into Kolob Canyon which in turn drains into the Virgin River.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

[illegible]

CERTIFICATE OF SURVEY

(I) (~~Was~~), Shirley B. Hjellum

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day
Supplemental Special Instructions 23rdof April , 1970 , ~~(XXXXXX)~~

October , 1973 , I have dependently resurveyed portions of the

Kolob Guide Meridian (west boundary) and subdivisional lines, and subdivided
section 30 in Township 39 South, Range 10 West

of the Salt Lake Meridian, in the State of Utah , which
are represented in the foregoing field notes as having been executed by (me), (~~XX~~) and under (my)
~~KOL~~ direction; and that said survey has been made in strict conformity with said special instruc-
tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
specific manner described in the foregoing field notes.

March 1, 1974

(Date)

Shirley B. Hjellum
Shirley B. Hjellum (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL.

Date MAR 6 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of portions of the Kolob Guide
Meridian (west boundary) and the subdivisional lines, with the subdivision
of section 30 in Township 39 South, Range 10 West, Salt Lake Meridian, Utah

executed by Shirley B. Hjellum, Supervisory Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

JUN 21 1974

(Date)

Bernard W. Johnson
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY e foregoing transcript of the field notes of the above- 1 ed surveys in
, a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Surv

GPO 849-626